

ODJELJAK 1.: Identifikacija tvari/smjese i podaci o društvu/poduzeću

1.1. Identifikacijska oznaka proizvoda

Identifikacija preparata:

Trgovačko ime: AX 91 COMP.A

Trgovački kod: 749K

UFI: GA22-10HP-M00W-48KR

1.2. Utvrđene relevantne uporabe tvari ili smjese i uporabe koje se ne preporučuju

Preporučana upotreba: Epoksidno ljepilo

Nepreporučljiva upotreba: Nije prikladno za uporabu u igračkama ili proizvodima koje mogu staviti djeca u usta.

1.3. Podaci o dobavljaču koji isporučuje sigurnosno-tehnički list

Tvrtka: FASSA Srl

Via Lazzaris, 3 - 31027 Spresiano (TV) - ITALY

Tel. +39 0422 7222

Fax +39 0422 887509

Odgovorna osoba: laboratorio.spresiano@fassabortolo.it

1.4. Broj telefona za izvanredna stanja

+3851 2348 342

ODJELJAK 2.: Identifikacija opasnosti



2.1. Razvrstavanje tvari ili smjese

Uredba (EC) br. 1272/2008 (CLP)

Skin Irrit. 2 Nadražuje kožu.
Eye Irrit. 2 Uzrokuje jako nadraživanje oka.
Skin Sens. 1 Može izazvati alergijsku reakciju na koži.
Aquatic Chronic 3 Štetno za vodeni okoliš s dugotrajnim učincima.
Fizikalno-kemijski učinci štetni po ljudsko zdravlje i okoliš:
Nema ostalih rizika

2.2. Elementi označivanja

Uredba (EC) br. 1272/2008 (CLP):

Piktogrami i oznaka opasnosti



Upozorenje

Oznake upozorenja

H315 Nadražuje kožu.
H317 Može izazvati alergijsku reakciju na koži.
H319 Uzrokuje jako nadraživanje oka.
H412 Štetno za vodeni okoliš s dugotrajnim učincima.

Oznake obavijesti

P264 Temeljito oprati velikom količinom vodom i sapuna nakon rukovanja.
P273 Izbjegavati ispuštanje u okoliš.
P280 Nositi zaštitne rukavice te zaštitu za oči/zaštitu za lice.
P333+P313 U slučaju nadražaja ili osipa na koži: zatražiti savjet/pomoć liječnika.
P362+P364 Skinuti zagađenu odjeću i oprati je prije ponovne uporabe.

Posebna osiguranja:

EUH205 Sadrži epoksidne sastojke. Može izazvati alergijsku reakciju.

Sadržji:

oksiran, mono[(C12-14-alkiloksi)metil]-derivati

Ulje ljuske indijskog oraha

bis[4-(2,3-epoksipropoksi)fenil]propan

Produkti reakcije oligomerizacije i alkilacije 2-fenilpropen i fenol

Posebne odredbe prema Prilogu XVII REACH-a i naknadnih amandmana:

Niti jedan

2.3. Ostale opasnosti

PBT, vPvB ili drugi endokrini disruptori prisutni u koncentraciji > = 0,1 %:

Sastojak	Ident. Broj.	Količina	Svojstva:
Produkti reakcije oligomerizacije i alkilacije 2-fenilpropen i fenol	EINECS: 700-960-7	>=1 - <3 %	vPvB

Nema ostalih rizika

ODJELJAK 3.: Sastav/informacije o sastojcima

3.1. Tvari

Ne primjenjuje se.

3.2. Smjese

Identifikacija preparata: AX 91 COMP.A

Opasni sastojci u smislu CLP Uredbe koja se odnosi na razvrstavanje:

Količina	Naziv	Ident. Broj.	Klasifikacija	Broj registriranih slučajeva:	Svojstva:
≥5 - <10 %	bis[4-(2,3-epoksipropoksi)fenil]propan	CAS:1675-54-3 EC:216-823-5 Index:603-073-00-2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 Specifične granične vrijednosti koncentracije: 5% ≤ C < 100%: Skin Irrit. 2 H315 5% ≤ C < 100%: Eye Irrit. 2 H319	01-2119456619-26-xxxx	
≥1 - <3 %	oksiran, mono[(C12-14-alkiloksi)metil]-derivati	CAS:68609-97-2 EC:271-846-8 Index:603-103-00-4	Skin Irrit. 2, H315; Skin Sens. 1, H317	01-2119485289-22-xxxx	
≥1 - <3 %	Produkti reakcije oligomerizacije i alkilacije 2-fenilpropen i fenol	EC:700-960-7	Skin Irrit. 2, H315; Skin Sens. 1B, H317; Aquatic Chronic 3, H412	01-2119555274-38-xxxx	vPvB
≥0.5 - <1 %	Ulje ljuske indijskog oraha	CAS:8007-24-7 EC:700-991-6	Acute Tox. 4, H302 Acute Tox. 4, H312 Eye Dam. 1, H318 Skin Irrit. 2, H315 Skin Sens. 1A, H317 Procjena akutne toksičnosti: ATE - Oralno: 500mg/kg t.m. ATE - Dermalno: 1100mg/kg t.m.	01-2119502450-57-xxxx	

ODJELJAK 4.: Mjere prve pomoći

4.1. Opis mjera prve pomoći

U slučaju kontakta sa kožom:

Smjesta skinuti zagađenu odjeću i ukloniti je na bezbjedan način.

Odmah oprati obilnom količinom tekuće vode i eventualno sapunom dijelove tijela koji su došli u dodir s proizvodom, čak i u slučaju da samo sumnjate da je došlo do kontakta.

Oprati čitavo tijelo (istuširati se ili okupati).

U slučaju kontakta sa očima:

U slučaju kontakta sa očima, ispirati oči vodom neko vrijeme, držati otvorene kapke, a potom zatražiti pomoć oftalmologa.

Zaštititi neozlijeđeno oko.

U slučaju gutanja:

Ne poticati povraćanje, obratiti se liječniku i pokazati listić o sigurnosti i oznaku kemijskog rizika.

U slučaju udisanja:

Izloženu osobu treba iznijeti na svjež zrak, držati je na toplom, a ista mora mirovati.

4.2. Najvažniji simptomi i učinci, akutni i odgođeni

Simptomi i učinci su u skladu s očekivanjima od opasnosti kako je prikazano u 2. odjeljku.

4.3. Navod o potrebi za hitnom liječničkom pomoći i posebnom obradom

U slučaju nesreće ili slabosti smjesta se obratiti liječniku (ako je moguće, pokazati upute za uporabu ili sigurnosni list).

ODJELJAK 5.: Mjere za suzbijanje požara

5.1. Sredstva za gašenje

Prikladna sredstva za gašenje požara:

CO₂, aparati za gašenje požara prahom, pjena, raspršivanje vode.

Sredstva za gašenje požara koja ne treba koristiti iz bezbjednosnih razloga:

Voda u mlazovima.

5.2. Posebne opasnosti koje proizlaze iz tvari ili smjese

Sagorijevanjem se oslobađaju teški dimovi.

Ne udisati plinove nastale eksplozijom i/ili izgaranjem (ugljikov monoksid i ugljikov dioksid, dušikove okside).

5.3. Savjeti za gasitelje požara

Koristiti prikladne dišne aparate.

Posebno kupiti zaprljanu vodu, koja je korištena za gašenje požara. Ne bacati ovu vodu u kanalizacionu mrežu.

Neoštećene spremnike skloniti iz prostora neposredne opasnosti, ukoliko se to može izvršiti na bezbjedan način.

ODJELJAK 6.: Mjere kod slučajnog ispuštanja

6.1. Osobne mjere opreza, zaštitna oprema i postupci za izvanredna stanja

Za osobe koje se ne ubrajaju u interventno osoblje:

Koristiti sredstva za osobnu zaštitu.

Ukloniti osobe na sigurno mjesto.

Konzultirati mjere zaštite opisane u točkama 7. i 8.

Za interventno osoblje:

Koristiti sredstva za osobnu zaštitu.

6.2. Mjere zaštite okoliša

Spriječiti prodiranje u tlo/dublje slojeve zemlje. Spriječiti ulivanje u površinske vode ili u kanalizacionu mrežu.

U slučaju izlaska plina ili prodiranja u vodene tokove, tlo ili kanalizacionu mrežu, obavijestiti nadležna tijela.

6.3. Metode i materijal za sprečavanje širenja i čišćenje

Materijal je prikladan za skupljanje: inertni upijajući materijal (npr. pijesak, vermikulit)

Nakon što je proizvod sakupljen, isprati onečišćeno područje i predmete s vodom.

Zadržati vodu kojom ste izvršili pranje, pa je eliminirati.

6.4. Uputa na druge odjeljke

Pogledati također i paragrafe 8. i 13.

ODJELJAK 7.: Rukovanje i skladištenje

7.1. Mjere opreza za sigurno rukovanje

Izbjegavati dodir s kožom i očima, udisanje para i maglica.

Ne koristite prazne spremnike prije no što ih očistite.

Prije prijenosa proizvoda, uvjeriti se da u spremnicima nema ostataka nekompatibilnih tvari.

Savjeti o općoj higijeni na radnom mjestu:

Kontaminirana odjeća se smjesta mora zamijeniti prije ulaska u menze.

Ne konzumirati hranu i piće na radnom mjestu.

Pogledati i paragraf 8. u svezi sa preporučenim napravama za zaštitu.

7.2. Uvjeti sigurnog skladištenja, uzimajući u obzir moguće inkompatibilnosti

Čuvati spremnike dobro zatvorene na hladnom i dobro prozračenom mjestu daleko od izvora topline.

Držati podalje od hrane, pića i krmiva.

Inkompatibilne tvari:

Vidi točku 10.5

Upute za prostorije za skladištenje:

Aдекватно prozračene prostorije.

7.3. Posebna krajnja uporaba ili uporabe

Preporuke

Vidi točku 1.2

Specifične otopine za industrijski sektor

ODJELJAK 8.: Nadzor nad izloženosti/osobna zaštita

8.1. Nadzorni parametri

Granične vrijednosti izloženosti PNEC

bis[4-(2,3-epoksipropoksi)fenil]propan

CAS: 1675-54-3 Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.006 mg/l
Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.001 mg/l
Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 0.341 mg/kg
Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 0.034 mg/kg
Putevi izloženosti: Tlo (poljoprivredno); PNEC Ograničiti: 0.065 mg/kg
Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 10 mg/l

oksiran, mono[(C12-14-alkiloksi)metil]-derivati

CAS: 68609-97-2 Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.106 mg/l
Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.011 mg/l
Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 10 mg/l
Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 30.72 mg/kg
Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 307.16 mg/kg
Putevi izloženosti: Zemlja; PNEC Ograničiti: 1.234 mg/kg

Produkti reakcije oligomerizacije i alkilacije 2-fenilpropen i fenol

Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.014 mg/l
Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.001 µg/l
Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 1064 mg/kg
Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 106 mg/kg
Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 2.4 mg/l
Putevi izloženosti: Tlo (poljoprivredno); PNEC Ograničiti: 212.2 mg/kg

Ulje ljuske indijskog oraha

CAS: 8007-24-7 Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.003 mg/l
Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.03 mg/l
Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 0.97 mg/kg
Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 0.088 mg/kg
Putevi izloženosti: Tlo (poljoprivredno); PNEC Ograničiti: 6.71 mg/kg

Izvedena razina bez učinka. (DNEL)

bis[4-(2,3-epoksipropoksi)fenil]propan

CAS: 1675-54-3 Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 0.75 mg/kg; Potrošač: 0.089 mg/kg
Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 4.93 mg/m³; Potrošač: 0.87 mg/m³
Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Kratkotrajni, sistemski učinci
Potrošač: 0.5 mg/kg

oksiran, mono[(C12-14-alkiloksi)metil]-derivati

CAS: 68609-97-2 Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 3.6 mg/m³; Potrošač: 0.87 mg/m³
Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 1 mg/kg; Potrošač: 0.5 mg/kg
Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Potrošač: 0.5 mg/kg

Produkti reakcije oligomerizacije i alkilacije 2-fenilpropen i fenol

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Potrošač: 0.2 mg/kg

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 1.4 mg/m³; Potrošač: 0.35 mg/m³

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Potrošač: 1.7 mg/kg

Ulje ljuske indijskog oraha

CAS: 8007-24-7 Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 0.88 mg/m³; Potrošač: 0.2 mg/m³

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 0.5 mg/kg; Potrošač: 0.25 mg/kg

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Potrošač: 0.25 mg/kg

8.2. Nadzor nad izloženošću

Osigurati odgovarajuću ventilaciju. Kad je to razumno moguće, to se može postići upotrebom rezervne ventilacije i dobre opće aspiracije.

Zaštita očiju:

Čaše sa bočnom zaštitom (EN 166).

Zaštita kože:

Upotrebljavati odjeću prikladnu za potpunu zaštitu kože u skladu s aktivnošću i izloženošću (EN 14605/EN 13982), npr. radne kombinezone, pregače, sigurnosnu obuću, prikladnu odjeću.

Zaštita za ruke:

Ne postoji materijal ili kombinacija materijala za rukavice koji bi mogli jamčiti neograničenu otpornost na bilo koji kemijski proizvod ili kombinaciju proizvoda.

Ako je riječ o duljem ili ponavljanom rukovanju, koristite se rukavicama otpornim na kemijske proizvode.

FKM (fluorirana guma): debljina > = 0,4 mm; vrijeme prodiranja > = 480 min. NBR (nitrilna guma): debljina > = 0,4 mm; vrijeme prodiranja > = 480 min

Izbor prikladnih rukavica ne ovisi samo o materijalu, nego i o drugim karakteristikama kvalitete koje se razlikuju od proizvođača do proizvođača, i o načinima i vremenu upotrebe smjese.

Zaštita pri disanju:

Ako su radnici izloženi koncentracijama višima od granice izloženosti, moraju upotrebljavati odgovarajuće certificirane respiratore.

Kombinirana filtrirajuća naprava (EN 14387): maska s filtrom A-P2.

Kontrola izlaganja u okolišu:

Vidi točku 6.2

Higijenske i tehničke mjere

Vidi odlomak 7.

ODJELJAK 9.: Fizikalna i kemijska svojstva

9.1. Informacije o osnovnim fizikalnim i kemijskim svojstvima

Izgled: kašasta tekućina

Boja: bijelo/sivo

Miris: karakterističan

Talište/ledište: N.D.

Vrelište ili početno vrelište i raspon temperatura vrenja: N.D.

Zapaljivost: nezapaljivo

Donja i gornja granica eksplozivnosti: N.D.

Plamište: > 60°C / 93°C

Temperatura samozapaljenja: N.D.

Temperatura raspadanja: N.D.

pH: Ne primjenjuje se. (Ne odnosi se zbog prirode proizvoda)

Kinematička viskoznost: > 20.5 mm²/s (40 °C)

Gustoća i/ili relativna gustoća: 1.8 - 2.0 kg/l (Interna metoda)

Relativna gustoća pare: N.D.

Tlak pare: N.D.

Topljivost u vodi: Netopivo, Ne miješa se

Topljivost u ulje: Ne primjenjuje se.

Koeficijent raspodjele n-oktanol/voda (logaritamska vrijednost): Ne primjenjuje se.

Svojstva čestica:

Veličina čestica: Ne primjenjuje se.

9.2. Ostale informacije

Vodljivost: N.D.

Explozivne osobine: N.A.
Osobine oksidiranja: N.A.
Brzina isparavanja: Ne primjenjuje se.

ODJELJAK 10.: Stabilnost i reaktivnost

10.1. Reaktivnost

Stabilan u normalnim uvjetima

10.2. Kemijska stabilnost

Stabilan u normalnim uvjetima

10.3. Mogućnost opasnih reakcija

Može se zapaliti u kontaktu s jakim oksidansima.

Zbog djelovanja topline ili u slučaju požara može doći do oslobađanja ugljikovih oksida i para koji mogu biti štetni za zdravlje.

10.4. Uvjeti koje treba izbjegavati

Čuvati odvojeno od izvora topline.

10.5. Inkompatibilni materijali

Snažni oksidansi, snažna redukcijska sredstva, alifatski i aromatski amini.

Vidi točku 10.3

10.6. Opasni proizvodi raspadanja

Pri odgovarajućem skladištenju i rukovanju ne razvijaju se opasni proizvodi raspadanja.

Vidi točku 5.2

ODJELJAK 11.: Toksikološke informacije

11.1. Informacije o razredima opasnosti kako su definirani u Uredbi (EZ) br. 1272/2008

Ova tvar sadrži tekuću epoksi smolu koja uzrokuje manju iritaciju kože. Sve epoksi smole mogu uzrokovati osjetljivost kože. Učinci na kožu variraju od osobe do osobe.

Kod osoba koje dolaze u kontakt s tvari, alergijski dermatitis se može pojaviti nakon nekoliko dana ili tjedana učestalog i dugotrajnog kontakta. Zbog toga, i u slučaju da je iritacija kože slaba kontakt se treba izbjegavati.

Kad se jednom pojavi osjetljivost, izlaganje kože vrlo malim količinama može uzrokovati eritem i edem.

Podaci o toksičnosti proizvoda:

a) akutna toksičnost	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
b) kožno nagrizanje/nadraživanje	Proizvod je razvrstan kao: Skin Irrit. 2(H315)
c) teške očne ozljede/teško očno nadraživanje	Proizvod je razvrstan kao: Eye Irrit. 2(H319)
d) izazivanje kožne ili dišne preosjetljivosti	Proizvod je razvrstan kao: Skin Sens. 1(H317)
e) mutagenost zametnih stanica	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
f) kancerogenost	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
g) reproduktivna toksičnost	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
h) Specifična toksičnost za ciljne organe (STOT) jednokratno izlaganje	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
i) Specifična toksičnost za ciljne organe (STOT) opetovano izlaganje	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
j) opasnost u slučaju udisanja	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.

Podaci o toksičnosti glavnih sastojaka u proizvodu:

bis[4-(2,3-epoksi)propoksi]fenil]propan

CAS: 1675-54-3 a) akutna toksičnost LD50 Oralno Štakor > 2000 mg/kg
LD50 Koža Štakor > 2000 mg/kg

oksiran, mono[(C12-14-alkiloksi)metil]-derivati

CAS: 68609-97-2 a) akutna toksičnost LC0 Udisanje pare Štakor > 0.15 mg/l 7h
LD50 Oralno Štakor > 2000 mg/kg
LD50 Koža Kunić > 4000 mg/kg

Produkti reakcije oligomerizacije i alkilacije 2-fenilpropen i fenol

a) akutna toksičnost LD50 Koža Štakor > 2000 mg/kg
LD50 Oralno Štakor > 2000 mg/kg

Ulje ljuske indijskog oraha

CAS: 8007-24-7 a) akutna toksičnost ATE - Oralno: 500 mg/kg t.m.
ATE - Dermalno: 1100 mg/kg t.m.
LD50 Koža Štakor > 2000 mg/kg
LD50 Oralno Štakor 5000 mg/kg

11.2. Informacije o drugim opasnostima

Svojstva endokrine disrupcije:

Bez drugih endokrinih disruptora prisutnih u koncentraciji > = 0,1 %

ODJELJAK 12.: Ekološke informacije

Primjeniti dobre radne postupke da se produkt ne oslobađa u okoliš.

12.1. Toksičnost

Eko-Toksikološke informacije:

Štetno za vodeni okoliš s dugotrajnim učincima.

Popis eko-toksikoloških svojstava proizvoda

Proizvod je razvrstan kao: Aquatic Chronic 3(H412)

Popis sastojaka sa eko-toksikološkim svojstvima

bis[4-(2,3-epoksipropoksi)fenil]propan

CAS: 1675-54-3 a) Akutna otrovnost na vodene organizme: EC50 Daphnia 1.8 mg/l 48h
a) Akutna otrovnost na vodene organizme: LC50 Ribe 2 mg/l 96h
a) Akutna otrovnost na vodene organizme: EC50 Algae 11 mg/l 72h
b) Hronična otrovnost na vodene organizme: NOEC Daphnia 0.3 mg/l 21d

oksiran, mono[(C12-14-alkiloksi)metil]-derivati

CAS: 68609-97-2 a) Akutna otrovnost na vodene organizme: LL50 Ribe > 100 mg/l 96h
a) Akutna otrovnost na vodene organizme: EL50 Daphnia 7.2 mg/l 48h
a) Akutna otrovnost na vodene organizme: IC50 Algae 843.75 mg/l 72h

12.2. Postojanost i razgradivost

bis[4-(2,3-epoksipropoksi)fenil]propan

CAS: 1675-54-3 Nije brzo-biološki razgradiv

oksiran, mono[(C12-14-alkiloksi)metil]-derivati

CAS: 68609-97-2 Brzo-biološki razgradiv

Ulje ljuske indijskog oraha

CAS: 8007-24-7 Brzo-biološki razgradiv

12.3. Bioakumulacijski potencijal

Ne primjenjuje se.

12.4. Pokretljivost u tlu

Ne primjenjuje se.

12.5. Rezultati procjene svojstava PBT i vPvB

Popis sastojaka sa eko-toksikološkim svojstvima

Produkti reakcije oligomerizacije i alkilacije 2-fenilpropen i fenol

>=1 - <3 % vPvB

12.6. Svojstva endokrine disrupcije

Bez drugih endokrinih disruptora prisutnih u koncentraciji > = 0,1 %

12.7. Ostali štetni učinci

Ne primjenjuje se.

ODJELJAK 13.: Zbrinjavanje

13.1. Metode obrade otpada

Regenerirati ako je moguće. Pri tome se pridržavati propisanih lokalnih i državnih propisa.
Ne dopustiti prodor u kanalizaciju ili vodene tokove.
Zbrinite kontejnera onečišćenih proizvoda u skladu s lokalnim ili nacionalnim zakonskim odredbama.
Proizvod se nakon isteka roka trajanja mora odložiti prema propisima na snazi.

ODJELJAK 14.: Informacije o prijevozu

Nije klasificirano kao opasno po propisima za transport.

14.1. UN broj ili identifikacijski broj

N/A

14.2. Ispravno otpremno ime prema UN-u

ADR-Naziv za otpremu: N/A

IATA-Naziv za otpremu: N/A

IMDG-Naziv za otpremu: N/A

14.3. Razred(i) opasnosti pri prijevozu

ADR-Razred: N/A

IATA-Razred: N/A

IMDG-Razred: N/A

14.4. Skupina pakiranja

ADR-Grupa pakiranja: N/A

IATA-Grupa pakiranja: N/A

IMDG-Grupa pakiranja: N/A

14.5. Opasnosti za okoliš

Morski polutant: Ne

Zagađivači okoliša: Ne

IMDG-EMS: N/A

14.6. Posebne mjere opreza za korisnika

Ceste i Željeznica (ADR-RID):

ADR oslobađa:

ADR-Označavanje: N/A

ADR - Identifikacijski broj opasnosti: N/A

ADR-Posebne odredbe: N/A

ADR ograničenja prijevoza u tunelu:

Zrak (IATA):

IATA-Putnički zrakoplov: N/A

IATA-Teretni zrakoplov: N/A

IATA-Označavanje: N/A

IATA-Sporedni opasnosti: N/A

IATA-Erg: N/A

IATA-Posebne odredbe: N/A

More (IMDG):

IMDG-Skladištenje i rukovanje: N/A

IMDG-Segregacija: N/A

IMDG-Sporedni opasnosti N/A

IMDG-Posebne odredbe: N/A

14.7. Prijevoz morem u razlišenom stanju u skladu s instrumentima IMO-a

Ne primjenjuje se.

ODJELJAK 15.: Informacije o propisima

15.1. Propisi u području sigurnosti, zdravlja i okoliša/posebno zakonodavstvo za tvar ili smjesu

Direktiva 98/24/EC (Rizici koji nastaju od kemijskih agenasa na radu)

Direktiva 2000/39/EC (Granična vrijednost profesionalne izloženosti)

Direktiva 2010/75/EU

Uredba (EC) br. 1907/2006 (REACH)

Uredba (EC) br. 1272/2008 (CLP)

Uredba (EC) br. 790/2009 (ATP 1 CLP) i (EZ) br. 758/2013

Uredba (EZ) br. 2020/878

Uredba (EZ) br. 286/2011 (ATP 2 CLP)

Uredba (EZ) br. 618/2012 (ATP 3 CLP)

- Uredba (EZ) br. 487/2013 (ATP 4 CLP)
- Uredba (EZ) br. 944/2013 (ATP 5 CLP)
- Uredba (EZ) br. 605/2014 (ATP 6 CLP)
- Uredba (EZ) br. 2015/1221 (ATP 7 CLP)
- Uredba (EZ) br. 2016/918 (ATP 8 CLP)
- Uredba (EZ) br. 2016/1179 (ATP 9 CLP)
- Uredba (EZ) br. 2017/776 (ATP 10 CLP)
- Uredba (EZ) br. 2018/669 (ATP 11 CLP)
- Uredba (EZ) br. 2018/1480 (ATP 13 CLP)
- Uredba (EZ) br. 2019/521 (ATP 12 CLP)
- Uredba (EZ) br. 2020/217 (ATP 14 CLP)
- Uredba (EZ) br. 2020/1182 (ATP 15 CLP)
- Uredba (EZ) br. 2021/643 (ATP 16 CLP)
- Uredba (EZ) br. 2021/849 (ATP 17 CLP)
- Uredba (EZ) br. 2022/692 (ATP 18 CLP)

Ograničenja u vezi s produktom ili sadržajnim tvarima u skladu s Prilogom XVII Uredbe (EZ-a) 1907/2006 (REACH) i naknadne izmjene:

- Ograničenja koja se odnose na proizvod: 3
- Ograničenja koja se odnose na sadržane tvari: 75

Odredbe prema direktivi 2012/18/EU (Seveso III)

Niti jedan

Uredba (EU) br. 649/2012 (Uredba PIC)

Nijedna tvar nije navedena

Njemačka klasifikacija opasnosti za vodu.

Klasa 2: zagađuje vodu.

SVHC tvari:

Tvari na popisu kandidata (Člt. 59 Ur. 1907/2006, REACH):

Sastojak	Ident. Broj.	Količina	Svojstva:
Produkti reakcije oligomerizacije i alkilacije 2-fenilpropen i fenol	EINECS: 700-960-7	>=1 - <3 %	SVHC - vPvB

15.2. Procjena kemijske sigurnosti

Procjena kemijske sigurnosti nije provedena za smjesu

ODJELJAK 16.: Ostale informacije

Šifra	Opis
H302	Štetno ako se proguta.
H312	Štetno u dodiru s kožom.
H315	Nadražuje kožu.
H317	Može izazvati alergijsku reakciju na koži.
H318	Uzrokuje teške ozljede oka.
H319	Uzrokuje jako nadraživanje oka.
H411	Otrovno za vodeni okoliš s dugotrajnim učincima.
H412	Štetno za vodeni okoliš s dugotrajnim učincima.

Šifra	Razred opasnosti i kategorija opasnosti	Opis
3.1/4/Dermal	Acute Tox. 4	Akutna toksičnost (preko kože), kategorija 4
3.1/4/Oral	Acute Tox. 4	Akutna toksičnost (gutanje), kategorija 4
3.2/2	Skin Irrit. 2	Nadražujuće za kožu, kategorija 2
3.3/1	Eye Dam. 1	Teška ozljeda oka, kategorija 1
3.3/2	Eye Irrit. 2	Nadražujuće za oči, kategorija 2
3.4.2/1	Skin Sens. 1	Izazivanje preosjetljivosti kože, kategorija 1
3.4.2/1A	Skin Sens. 1A	Izazivanje preosjetljivosti kože, kategorija 1A
3.4.2/1B	Skin Sens. 1B	Izazivanje preosjetljivosti kože, kategorija 1B
4.1/C2	Aquatic Chronic 2	Kroničnu (dugoročnu) opasnost za organizme koji žive u vodi, kategorija 2
4.1/C3	Aquatic Chronic 3	Kroničnu (dugoročnu) opasnost za organizme koji žive u vodi,

Razvrstavanje i postupak razvrstavanja za smjese sukladno Uredbi (EZ) br. 1272/2008 (CLP):**Razvrstavanje prema Uredbi (EZ) br. 1272/2008 Postupak razvrstavanja**

Skin Irrit. 2, H315	Računska metoda
Eye Irrit. 2, H319	Računska metoda
Skin Sens. 1, H317	Računska metoda
Aquatic Chronic 3, H412	Računska metoda

Ovaj dokument izradila je tehnički kompetentna osoba za SDS, te koja je prikladno za to osposobljena.

Glavni bibliografski izvori:

ECDIN – Informacijska mreža za ekološke podatke za kemikalije – Zajednički istraživački centar, Komisija Europskih zajednica
SAX's OPASNE OSOBINE INDUSTRIJSKIH TVARI- Osmo izdanje - Van Nostrand Reinold
Sigurnosno-tehnički listovi dobavljača sirovina.

Ovdje objavljenе informacije se temelje na našem znanju u vrijeme gore navedenog datuma. Odnose se samo na navedene proizvode i ne predstavlja garanciju neke određene kvalitete.

Obaveza je korisnika da utvrdi da je ova informacija cjelovita i da odgovara specifičnoj upotrebi.

Ovaj MSDS poništava i zamjenjuje sva predhodna izdanja.

Legenda kratica i akronima upotrebljenih u sigurnosno-tehničkom listu:

ACGIH: Američka konferencija vladinih specijalista za industrijsku higijenu
ADR: Europski sporazum o međunarodnom cestovnom prijevozu opasnih tvari.
ATE: Procjena akutne toksičnosti
ATEmix: Procijenjena vrijednost akutne toksičnosti (Mješavine)
BEI: Indeks biološke izloženosti
CAS: CAS registarski broj (Američko kemijsko društvo)
CAV: Centar za otrove
CE: Europska zajednica
CLP: Razvrstavanje, označavanje, pakiranje.
CMR: Karcinogeno, Mutageno i Reprotoksično
COV: Hlapivi organski spoj
CSA: Procjena kemijske sigurnosti
CSR: Izvješće o kemijskoj sigurnosti
DNEL: Izvedena razina bez učinka.
EC50: Pulu maksimalna efektivna koncentracija
ECHA: Europska agencija za kemijske proizvode
EINECS: Europski propis postojećih trgovačkih kemijskih tvari.
ES: Scenario izloženosti
GefStoffVO: Propis o opasnim tvarima, Njemačka.
GHS: Globalno harmonizirani sustav razvrstavanja i označavanja kemikalija
IARC: Međunarodna agencija za istraživanja o karcinomu
IATA: Međunarodna udruga za zračni prijevoz.
IC50: Pulu maksimalna koncentracija inhibitora
IMDG: Međunarodni pomorski kodeks opasnog tereta.
LC50: Smrtna koncentracija u 50% slučajeva ispitivane populacije.
LD50: Smrtna doza u 50% slučajeva ispitivane populacije.
LDLo: Niska smrtonosna doza
N.A.: Nije primjenjivo
N/A: Nije primjenjivo
N/D: Nije definirano/Nije dostupno
N.D.: Nije dostupno
NIOSH: Državni institut za zaštitu na radu
NOAEL: Razina bez uočenih štetnih učinaka
OSHA: Upravljanje zaštitom na radu
PBT: Persistentno, bioakumulativno i toksično
PGK: Packaging Instruction
PNEC: Predviđena koncentracija bez učinka.
PSG: Putnici
RID: Propis o međunarodnom prijevozu opasnih tvari željeznicom
STEL: Granica kratkotrajne izloženosti.
STOT: Toksičnost za ciljani organ.
TLV: Granična vrijednost praga.
TLV-TWA: Granična vrijednost praga za vremenski ponderirani prosjek. (ACGIH standard)

vPvB: Vrlo persistentno, vrlo bioakumulativno
WGK: Njemačka klasifikacija opasnosti za vodu.

Odlomci promijenjeni u odnosu na prethodnu reviziju:

- ODJELJAK 2.: Identifikacija opasnosti
- ODJELJAK 3.: Sastav/informacije o sastojcima
- ODJELJAK 6.: Mjere kod slučajnog ispuštanja
- ODJELJAK 8.: Nadzor nad izloženošću/osobna zaštita
- ODJELJAK 9.: Fizikalna i kemijska svojstva
- ODJELJAK 11.: Toksikološke informacije
- ODJELJAK 12.: Ekološke informacije
- ODJELJAK 13.: Zbrinjavanje
- ODJELJAK 14.: Informacije o prijevozu
- ODJELJAK 15.: Informacije o propisima
- ODJELJAK 16.: Ostale informacije

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Substance identification

Chemical Name: bis-[4-(2,3-epoxipropoxy)phenyl]propane

CAS number: 1675-54-3

Date - Version: 29/12/2021 - 1.3

INDUSTRIAL USE - PROFESSIONAL USES: PUBLIC SECTOR (ADMINISTRATION, EDUCATION, ENTERTAINMENT, SERVICES, CRAFTS) (SU22).

1. TITLE SECTION

Exposure scenario name: Industrial use.

Structured short title: Professional uses: public sector (administration, education, entertainment, service, crafts) (SU22).

Substance: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EC number: 216-823-5

Registration number: 01-2119456619-26

ENVIRONMENT

SC 1: Use of non-reactive processing aid at industrial site (no inclusion in article) ERC4

WORKER

SC 2: Use as laboratory reagents PROC15

SC 3: Treatment of articles by dipping and pouring PROC13

SC 4: Tableting, compression, extrusion, pelletising, granulation PROC14

SC 5: General greasing/lubrication in high energy conditions PROC18

SC 6 Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8a

2. CONDITIONS OF USE AFFECTING EXPOSURE

2.1. ENVIRONMENTAL EXPOSURE CONTROL: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4)

Product features (article)

Physical form of the product: Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Daily amount per site: 0,6 ton/day

Annual amount per site: 20 ton/year

Conditions and measures related to sewage treatment plant

STP Type: Municipal wastewater treatment plant.

Learn more about STP: biological elimination.

STP sludge treatment: It may be landfilled when allowed by local regulations.

STP effluent: 2,000 m³/day

Other conditions affecting environmental exposure

Water flow on the receiving surface: 18,000 m³/day

Outdoor / Indoor Indoor use.

2.2. WORKERS EXPOSURE CONTROL: Use as laboratory reagents (PROC15)

Product features (article)

Covers the percentage of substance in the product up to 100%.

Physical form of the product: Liquid.

Temperature: < 40°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 30%.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 40°C

2.3. WORKERS EXPOSURE CONTROL: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: < 70°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 1 to 3 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 0%.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Wear suitable respirator.

Inhalation: minimum yield of 90%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 40°C

2.4. WORKERS EXPOSURE CONTROL: Tableting, compression, extrusion, pelletising, granulation (PROC14)

Product features (article)

Covers the percentage of substance in the product up to 100%.

Physical form of the product: Liquid.

Temperature: < 40°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 30%.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 40°C

2.5. WORKERS EXPOSURE CONTROL: General greasing/lubrication in high energy conditions (PROC18)

Product features (article)

Covers concentrations up to 20%.

Physical form of the product: Liquid.

Temperature: ≤ 800°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Wear suitable respirator.

Inhalation: minimum yield of 90%.

Other conditions affecting worker exposure

Outdoor / Indoor Outside.

Industrial or professional environments: Professional use.

Temperature: ≤ 800°C

2.6. WORKERS EXPOSURE CONTROL: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC8a)

Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Other conditions affecting worker exposure

Outdoor / Indoor Outside.

Industrial or professional environments: Professional use.

Temperature: A process temperature of up to < 40°C is assumed.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4)

Route release	Release rate	Method for estimating for release
water	1.2E-10kg/day	FEICA SPERC 5.1 a.v1
air	3E-4kg/day	FEICA SPERC 5.1 a.v1
Soil	0%	FEICA SPERC 5.1 a.v1

Protection target	Estimated Exposure (EUSES v2.1)	RCR
Fresh water	3.76E-4mg/l	0.063
Fresh water sediments	0.018mg/l	0.053
Sea water	2.95E-5mg/kg dry weight	0.049
Marine sediment	1.42E-3mg/kg dry weight	0.042
Sewage treatment plant	5.68E-11mg/l	< 0.01
Farmland	2.88E-6mg/kg dry weight	< 0.01
Prey for predators (freshwater)	mg/kg wet weight (EUSES v2.1)	< 0.01
Prey for predators (marine water)	9.13E-4mg/kg wet weight	< 0.01
Main predator prey (marine water)	9.13E-4mg/kg wet weight	< 0.01
Prey for Predators (Terrestrial)	1.68E-4mg/kg wet weight	< 0.01
Man through the environment - inhalation	7.65E-9mg/m ³	< 0.01
Man through the environment - oral	3E-5mg/kgbw/day	< 0.01
Population exposed through the environment	-	< 0.01

3.2. Worker exposure: Use as laboratory reagents (PROC15)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.993mg/m ³	0.201
inhalation	local	Long-term	0.993mg/m ³	-
inhalation	local	Short term	0.993mg/m ³	-
dermal	systemic	Long-term	0.172mg/kg bw/day	0.045
dermal	local	Short term	9.92E-3mg/cm ²	-
combined routes	-	-	-	0.247

3.3. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.085mg/m ³	0.017
inhalation	local	Long-term	0.085mg/m ³	-
inhalation	local	Short term	0.085mg/m ³	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.06mg/cm ²	-
combined routes	-	-	-	0.566

3.4. Worker exposure: Tableting, compression, extrusion, pelletising, granulation (PROC14)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.993mg/m ³	0.201
inhalation	local	Long-term	0.993mg/m ³	-
inhalation	local	Short term	0.993mg/m ³	-
dermal	systemic	Long-term	0.172mg/kg bw/day	0.229
dermal	local	Short term	0.0025mg/cm ²	-
combined routes	-	-	-	0.43

3.5. Worker exposure: General greasing/lubrication in high energy conditions (PROC18)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.596mg/m ³	0.121
inhalation	local	Long-term	0.596mg/m ³	-
inhalation	local	Short term	0.596mg/m ³	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.03mg/cm ²	-
combined routes	-	-	-	0.669

3.6. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.596mg/m ³	0.121
inhalation	local	Long-term	0.596mg/m ³	-
inhalation	local	Short term	0.596mg/m ³	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.03mg/cm ²	-
combined routes	-	-	-	0.669

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Predicted exposures are not expected to exceed the applicable exposure limits (given in Section 8 of the SDS) when the operational conditions/risk management measures given in Section 2 are implemented.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

PROFESSIONAL USE - PROFESSIONAL USES: PUBLIC SECTOR (ADMINISTRATION, EDUCATION, ENTERTAINMENT, SERVICES, CRAFTS) (SU22).

1. TITLE SECTION

Exposure scenario name: Professional.

Structured short title: Professional uses: public sector (administration, education, entertainment, service, crafts) (SU22).

Substance: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EC number: 216-823-5

Registration number: 01-2119456619-26

ENVIRONMENT

SC 1: Use at an industrial site leading to inclusion in article ERC5

WORKER

SC 2: Industrial spraying PROC7

SC 3 Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8a

SC 4: Transfer of substance or mixture (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC8b

SC 5: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC9

SC 6: Application with rollers or brushes PROC10

SC 7: Non-industrial spraying PROC11

2. CONDITIONS OF USE AFFECTING EXPOSURE

2.1. ENVIRONMENTAL EXPOSURE CONTROL: Use at an industrial site leading to inclusion in article (ERC5)

Product features (article)

Covers a percentage of substance in the product up to 100%.

Physical form of the product: Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Annual amount per site: 30,000 tons/year

Daily amount per site: 100 tons/day

Conditions and measures related to sewage treatment plant

STP Type: Municipal wastewater treatment plant.

Learn more about STP: biological elimination.

STP sludge treatment: It may be landfilled when allowed by local regulations.

STP effluent: 2,000 m³/day

Other conditions affecting environmental exposure

Water flow on the receiving surface: 18,000 m³/day

2.2. WORKERS EXPOSURE CONTROL: Industrial spraying (PROC7)

Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

Wear suitable respirator.

Dermal: minimum efficiency of 99%.

Inhalation: minimum yield of 90%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Industrial or professional environments Professional use.

Temperature: Process temperature up to 70°C is assumed.

2.3. WORKERS EXPOSURE CONTROL: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC8a)

Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: 70°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Provide a good standard of general ventilation (not less than 1 to 3 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 0%.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Industrial or professional environments Professional use.

Temperature: 70°C

2.4. WORKERS EXPOSURE CONTROL: Transfer of substance or mixture (charging/discharging) from/to vessels/large containers at dedicated facilities. (PROC8b)

Product features (article)

Covers the percentage of substance in the product up to 100%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: 70°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 1 to 3 air changes per hour).

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Wear suitable respirator.

Inhalation: minimum yield of 90%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: 70°C

2.5. WORKERS EXPOSURE CONTROL: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product features (article)

Covers concentrations up to 100%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: < 50°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 30%.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Wear suitable respirator.

Inhalation: minimum yield of 90%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 50°C

2.6. WORKERS EXPOSURE CONTROL: Application with rollers or brushes (PROC10)

Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: < 70°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 1 to 3 air changes per hour).

Local exhaust ventilation.

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 90%.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 99%.

Inhalation: minimum yield of 0%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 70°C.

2.7. WORKERS EXPOSURE CONTROL: Non-industrial spraying (PROC11)

Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Temperature: < 40°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

Wear suitable respirator.

Dermal: minimum efficiency of 99%.

Inhalation: minimum yield of 90%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 40°C.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. Environmental release and exposure: Use at an industrial site leading to inclusion in article (ERC5)

Route release	Release rate	Method for estimating for release
water	0.06 kg/day	FEICA SPERC 8c.1 b.v1
air	0 kg/day	FEICA SPERC 8c.1 b.v1
Soil	0%	FEICA SPERC 8c.1 b.v1

Protection target	Estimated Exposure (EUSES v2.1)	RCR
Fresh water	3.22E-3mg/l	0,536
Fresh water sediments	0.155mg/l	0,454
Sea water	3.14E-4mg/l	0,523
Marine sediment	0.015mg/kg dry weight	0,442
Sewage treatment plant	0.028mg/l	< 0.01
Farmland	0.05mg/kg dry weight	0,779
Prey for predators (freshwater)	0.048mg/kg wet weight	< 0.01
Prey for predators (marine water)	4.53E-3mg/kg wet weight	< 0.01
Main predator prey (marine water)	1.64E-3mg/kg wet weight	< 0.01
Prey for Predators (Terrestrial)	0.056mg/kg wet weight	< 0.01
Man through the environment - inhalation	Concentration in air: 3.45E-11 mg/m³	< 0.01
Man through the environment - oral	1.47E-3mg/kg pc/giorno	< 0.01
Population exposed through the environment	-	< 0.01

3.2. Worker exposure: Industrial spraying (PROC7)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	0.34mg/m ³ (ART v1.5)	0.069
inhalation	local	Long-term	0.34mg/m ³ (ART v1.5)	-
inhalation	local	Short term	0.78mg/m ³ (ART v1.5)	-
dermal	systemic	Long-term	0.257mg/kgbw/day (ECETOC TRA worker v3)	0.343
dermal	local	Short term	0.012mg/cm ² (ECETOC TRA worker v3)	-
combined routes	-	-	-	0.412

3.3. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.851mg/m ³	0.173
inhalation	local	Long-term	0.851mg/m ³	-
inhalation	local	Short term	0.851mg/m ³	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.03mg/cm ²	-
combined routes	-	-	-	0.721

3.4. Worker exposure: Transfer of a substance or a mixture (fill/discharge) at dedicated facilities (PROC8b)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.085mg/m ³	0.017
inhalation	local	Long-term	0.085mg/m ³	-
inhalation	local	Short term	0.0851mg/m ³	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.03mg/cm ²	-
combined routes	-	-	-	0.566

3.5. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.099mg/m ³	0.02
inhalation	local	Long-term	0.099mg/m ³	-
inhalation	local	Short term	0.993mg/m ³	-
dermal	systemic	Long-term	0.343mg/kgbw/day	0.457
dermal	local	Short term	0.05mg/cm ²	-
combined routes	-	-	-	0.659

3.6. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.085mg/m ³	0.017
inhalation	local	Long-term	0.085mg/m ³	-
inhalation	local	Short term	0.085mg/m ³	-
dermal	systemic	Long-term	0.165mg/kgbw/day	0.219
dermal	local	Short term	0.012mg/cm ²	-
combined routes	-	-	-	0.237

3.7. Worker exposure: Non-industrial spraying (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	0.34mg/m ³ (ART v1 .5)	0.069
inhalation	local	Long-term	0.34mg/m ³ (ART v1 .5)	-
inhalation	local	Short term	0.78mg/m ³ (ART v1 .5)	-
dermal	systemic	Long-term	0.643mg/kgbw/day (ECETOC TRA worker v3)	0.857
dermal	local	Short term	0.03mg/cm ² (ECETOC TRA worker v3)	-
combined routes	-	-	-	0.926

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Predicted exposures are not expected to exceed the applicable exposure limits (given in Section 8 of the SDS) when the operational conditions/risk management measures given in Section 2 are implemented.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

ODJELJAK 1.: Identifikacija tvari/smjese i podaci o društvu/poduzeću

1.1. Identifikacijska oznaka proizvoda

Identifikacija preparata:

Trgovačko ime: AX 91 COMP.B

Trgovački kod: 749K.B

UFI: E2RN-W0AQ-900W-6GRN

1.2. Utvrđene relevantne uporabe tvari ili smjese i uporabe koje se ne preporučuju

Preporučana upotreba: Poliaminsko sredstvo za stvrdnjavanje

1.3. Podaci o dobavljaču koji isporučuje sigurnosno-tehnički list

Tvrtka: FASSA Srl

Via Lazzaris, 3 - 31027 Spresiano (TV) - ITALY

Tel. +39 0422 7222

Fax +39 0422 887509

Odgovorna osoba: laboratorio.spresiano@fassabortolo.it

1.4. Broj telefona za izvanredna stanja

+3851 2348 342

ODJELJAK 2.: Identifikacija opasnosti



2.1. Razvrstavanje tvari ili smjese

Uredba (EC) br. 1272/2008 (CLP)

Skin Irrit. 2 Nadražuje kožu.
Eye Dam. 1 Uzrokuje teške ozljede oka.
Skin Sens. 1 Može izazvati alergijsku reakciju na koži.
Aquatic Chronic 3 Štetno za vodeni okoliš s dugotrajnim učincima.
Fizikalno-kemijski učinci štetni po ljudsko zdravlje i okoliš:
Nema ostalih rizika

2.2. Elementi označivanja

Uredba (EC) br. 1272/2008 (CLP):

Piktogrami i oznaka opasnosti



Opasnost

Oznake upozorenja

H315 Nadražuje kožu.
H317 Može izazvati alergijsku reakciju na koži.
H318 Uzrokuje teške ozljede oka.
H412 Štetno za vodeni okoliš s dugotrajnim učincima.

Oznake obavijesti

P261 Izbjegavati udisanje para.
P273 Izbjegavati ispuštanje u okoliš.
P280 Nositi zaštitne rukavice te zaštitu za oči/zaštitu za lice.
P302+P352 U SLUČAJU DODIRA S KOŽOM: oprati velikom količinom sapuna i vode.
P305+P351+P338 U SLUČAJU DODIRA S OČIMA: oprezno ispirati vodom nekoliko minuta. Ukloniti kontaktne leće ako ih nosite i ako se one lako uklanjaju. Nastaviti ispirati.
P310 Odmah nazvati CENTAR ZA KONTROLU OTROVANJA/liječnika.
P333+P313 U slučaju nadražaja ili osipa na koži: zatražiti savjet/pomoć liječnika.

Sadržji:

3-aminometil-3,5,5-trimetilcikloheksilamin

Masne kiseline, C18-nezasićene, dimeri, oligomerni produkti reakcije s masnim kiselinama iz tal ulja i trietilentetramina

Produkt reakcije masnih kiselina, C18 alkil s aminima, frakcija polietilenpoli-tetraetilenpentamina

Posebne odredbe prema Prilogu XVII REACH-a i naknadnih amandmana:

Niti jedan

2.3. Ostale opasnosti

Bez PBT-a, vPvB-a ili endokrinih disruptora prisutnih u koncentraciji > = 0,1 %.

Nema ostalih rizika

ODJELJAK 3.: Sastav/informacije o sastojcima

3.1. Tvari

Ne primjenjuje se.

3.2. Smjese

Identifikacija preparata: AX 91 COMP.B

Opasni sastojci u smislu CLP Uredbe koja se odnosi na razvrstavanje:

Količina	Naziv	Ident. Broj.	Klasifikacija	Broj registriranih slučajeva:
≥20 - <30 %	Produkt reakcije masnih kiselina, C18 alkil s aminima, frakcija polietilenpoli-tetraetilenpentamina	EC:701-046-0	Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1A, H317; Aquatic Chronic 2, H411	01-2119972321-42-xxxx
≥10 - <20 %	Masne kiseline, C18-nezasićene, dimeri, oligomerni produkti reakcije s masnim kiselinama iz tal ulja i trietilentetramina	CAS:68082-29-1 EC:500-191-5	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
≥3 - <5 %	2,4,6-tris(dimetilaminometil)fenol	CAS:90-72-2 EC:202-013-9 Index:603-069-00-0	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Procjena akutne toksičnosti: ATE - Oralno: 500mg/kg t.m.	01-2119560597-27-xxxx
≥1 - <3 %	3-aminometil-3,5,5-trimetilcikloheksilamin	CAS:2855-13-2 EC:220-666-8 Index:612-067-00-9	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Specifične granične vrijednosti koncentracije: C ≥ 0.001%: Skin Sens. 1A H317 Procjena akutne toksičnosti: ATE - Oralno: 1030mg/kg t.m.	01-2119514687-32-xxxx

ODJELJAK 4.: Mjere prve pomoći

4.1. Opis mjera prve pomoći

U slučaju kontakta sa kožom:

Smjesta skinuti zagađenu odjeću i ukloniti je na bezbjedan način.
Odmah oprati obilnom količinom tekuće vode i eventualno sapunom dijelove tijela koji su došli u dodir s proizvodom, čak i u slučaju da samo sumnjate da je došlo do kontakta.
ODMAH NAZVATI MEDICINSKU EKIPU ZA HITNU POMOĆ

U slučaju kontakta sa očima:

U slučaju kontakta sa očima, ispirati oči vodom neko vrijeme, držati otvorene kapke, a potom zatražiti pomoć oftalmologa.
Zaštititi neozlijeđeno oko.

U slučaju gutanja:

Ne poticati povraćanje, obratiti se liječniku i pokazati listić o sigurnosti i oznaku kemijskog rizika.

U slučaju udisanja:

Izloženu osobu treba iznijeti na svjež zrak, držati je na toplom, a ista mora mirovati.

4.2. Najvažniji simptomi i učinci, akutni i odgođeni

Simptomi i učinci su u skladu s očekivanjima od opasnosti kako je prikazano u 2. odjeljku.

4.3. Navod o potrebi za hitnom liječničkom pomoći i posebnom obradom

U slučaju nesreće ili slabosti smjesta se obratiti liječniku (ako je moguće, pokazati upute za uporabu ili sigurnosni list).

ODJELJAK 5.: Mjere za suzbijanje požara

5.1. Sredstva za gašenje

Prikladna sredstva za gašenje požara:

CO₂, aparati za gašenje požara prahom, pjena, raspršivanje vode.

Sredstva za gašenje požara koja ne treba koristiti iz bezbjednosnih razloga:

Voda u mlazovima.

5.2. Posebne opasnosti koje proizlaze iz tvari ili smjese

Sagorijevanjem se oslobađaju teški dimovi.

Ne udisati plinove nastale eksplozijom i/ili izgaranjem (ugljikov monoksid i ugljikov dioksid, dušikove okside).

5.3. Savjeti za gasitelje požara

Koristiti prikladne dišne aparate.

Posebno pokupiti zaprljanu vodu, koja je korištena za gašenje požara. Ne bacati ovu vodu u kanalizacionu mrežu.

Neoštećene spremnike skloniti iz prostora neposredne opasnosti, ukoliko se to može izvršiti na bezbjedan način.

ODJELJAK 6.: Mjere kod slučajnog ispuštanja

6.1. Osobne mjere opreza, zaštitna oprema i postupci za izvanredna stanja

Za osobe koje se ne ubrajaju u interventno osoblje:

Koristiti sredstva za osobnu zaštitu.

Ukloniti osobe na sigurno mjesto.

Konzultirati mjere zaštite opisane u točkama 7. i 8.

Za interventno osoblje:

Koristiti sredstva za osobnu zaštitu.

6.2. Mjere zaštite okoliša

Spriječiti prodiranje u tlo/dublje slojeve zemlje. Spriječiti ulivanje u površinske vode ili u kanalizacionu mrežu.

U slučaju izlaska plina ili prodiranja u vodene tokove, tlo ili kanalizacionu mrežu, obavijestiti nadležna tijela.

6.3. Metode i materijal za sprečavanje širenja i čišćenje

Materijal je prikladan za skupljanje: inertni upijajući materijal (npr. pijesak, vermikulit)

Nakon što je proizvod sakupljen, isprati onečišćeno područje i predmete s vodom.

Zadržati vodu kojom ste izvršili pranje, pa je eliminirati.

6.4. Uputa na druge odjeljke

Pogledati također i paragrafe 8. i 13.

ODJELJAK 7.: Rukovanje i skladištenje

7.1. Mjere opreza za sigurno rukovanje

Izbjegavati dodir s kožom i očima, udisanje para i maglica.

Ne koristite prazne spremnike prije no što ih očistite.

Prije prijenosa proizvoda, uvjeriti se da u spremnicima nema ostataka nekompatibilnih tvari.

Savjeti o općoj higijeni na radnom mjestu:

Kontaminirana odjeća se smjesta mora zamijeniti prije ulaska u menze.

Ne konzumirati hranu i piće na radnom mjestu.

Pogledati i paragraf 8. u svezi sa preporučenim napravama za zaštitu.

7.2. Uvjeti sigurnog skladištenja, uzimajući u obzir moguće inkompatibilnosti

Čuvati spremnike dobro zatvorene na hladnom i dobro prozračenom mjestu daleko od izvorā topline.

Držati podalje od hrane, pića i krmiva.

Inkompatibilne tvari:

Vidi točku 10.5

Upute za prostorije za skladištenje:

Aдекватно prozračene prostorije.

7.3. Posebna krajnja uporaba ili uporabe

Preporuke

Vidi točku 1.2

Specifične otopine za industrijski sektor

Nema posebne upotrebe

ODJELJAK 8.: Nadzor nad izloženošću/osobna zaštita

8.1. Nadzorni parametri

Granične vrijednosti izloženosti PNEC

Produkt reakcije masnih kiselina, C18 alkil s aminima, frakcija polietilenpoli-tetraetilenpentamina

Putevi izloženosti: Svježa voda; PNEC Ograničiti: 2.63 µg/l

Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.263 µg/l

Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 263.01 mg/kg

Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 26.301 mg/kg

Putevi izloženosti: Povremena ispuštanja (slatka voda); PNEC Ograničiti: 0.026 mg/l

Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 7.21 mg/l

Masne kiseline, C18-nezasićene, dimeri, oligomerni produkti reakcije s masnim kiselinama iz tal ulja i trietilentetramina

CAS: 68082-29-1 Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.004 mg/l

Putevi izloženosti: Morska voda; PNEC Ograničiti: 0 mg/l

Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 3.84 mg/l

Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 434.02 mg/kg

Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 43.4 mg/kg

Putevi izloženosti: Tlo (poljoprivredno); PNEC Ograničiti: 86.78 mg/kg

2,4,6-tris(dimetilaminometil)fenol

CAS: 90-72-2 Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.046 mg/l

Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.005 mg/l

Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 0.2 mg/l

Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 0.262 mg/kg

Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 0.026 mg/kg

Putevi izloženosti: Zemlja; PNEC Ograničiti: 0.025 mg/kg

3-aminometil-3,5,5-trimetilcikloheksilamin

CAS: 2855-13-2 Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.06 mg/l

Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.006 mg/l

Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 3.18 mg/l

Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 5.784 mg/kg

Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 0.578 mg/kg

Putevi izloženosti: Tlo (poljoprivredno); PNEC Ograničiti: 1.121 mg/kg

Izvedena razina bez učinka. (DNEL)

Produkt reakcije masnih kiselina, C18 alkil s aminima, frakcija polietilenpoli-tetraetilenpentamina

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Potrošač: 0.56

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 3.9 mg/m³; Potrošač: 0.97 mg/m³

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 1.1 mg/kg; Potrošač: 0.56 mg/m³

Masne kiseline, C18-nezasićene, dimeri, oligomerni produkti reakcije s masnim kiselinama iz tal ulja i trietilentetramina

CAS: 68082-29-1 Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 0.952 mg/m³; Potrošač: 0.169 mg/m³

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 0.272 mg/kg; Potrošač: 97.2 µg/kg

2,4,6-tris(dimetilaminometil)fenol

CAS: 90-72-2 Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 0.53 mg/m³; Potrošač: 0.13 mg/m³

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Kratkotrajni, sistemski učinci
Profesionalni djelatnik: 2.1 mg/m³; Potrošač: 0.13 mg/m³

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 0.15 mg/kg; Potrošač: 0.075 mg/kg

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Kratkotrajni, sistemski učinci
Profesionalni djelatnik: 0.6 mg/kg; Potrošač: 0.075 mg/kg

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Potrošač: 0.075 mg/kg

8.2. Nadzor nad izloženošću

Osigurati odgovarajuću ventilaciju. Kad je to razumno moguće, to se može postići upotrebom rezervne ventilacije i dobre opće aspiracije.

Zaštita očiju:

Čaše sa bočnom zaštitom (EN 166).

Zaštita kože:

Upotrebljavati odjeću prikladnu za potpunu zaštitu kože u skladu s aktivnošću i izloženošću (EN 14605/EN 13982), npr. radne kombinezone, pregače, sigurnosnu obuću, prikladnu odjeću.

Zaštita za ruke:

Ne postoji materijal ili kombinacija materijala za rukavice koji bi mogli jamčiti neograničenu otpornost na bilo koji kemijski proizvod ili kombinaciju proizvoda.

Ako je riječ o duljem ili ponavljanom rukovanju, koristite se rukavicama otpornim na kemijske proizvode.

NBR (nitrilna guma): debljina > = 0,4 mm; vrijeme prodiranja > = 480 min. FKM (fluorirana guma): debljina > = 0,4 mm; vrijeme prodiranja > = 480 min

Izbor prikladnih rukavica ne ovisi samo o materijalu, nego i o drugim karakteristikama kvalitete koje se razlikuju od proizvođača do proizvođača, i o načinima i vremenu upotrebe smjese.

Zaštita pri disanju:

Ako su radnici izloženi koncentracijama višima od granice izloženosti, moraju upotrebljavati odgovarajuće certificirane respiratore.

Kombinirana filtrirajuća naprava (EN 14387): maska s filtrom A-P2.

Kontrola izlaganja u okolišu:

Vidi točku 6.2

Higijenske i tehničke mjere

Vidi odlomak 7.

ODJELJAK 9.: Fizikalna i kemijska svojstva

9.1. Informacije o osnovnim fizikalnim i kemijskim svojstvima

Izgled: kašasta tekućina

Boja: žuto

Miris: amin

Talište/ledište: N.D.

Vrelište ili početno vrelište i raspon temperatura vrenja: > 180 °C (356 °F)

Zapaljivost: Ne primjenjuje se.

Donja i gornja granica eksplozivnosti: N.D.

Plamište: 110 °C (230 °F)

Temperatura samozapaljenja: N.D.

Temperatura raspadanja: N.D.

pH: Ne primjenjuje se. (Ne odnosi se zbog prirode proizvoda)

Kinematička viskoznost: > 20.5 mm²/s (40 °C)

Gustoća i/ili relativna gustoća: 1,20 ÷ 1,30 kg/l

Relativna gustoća pare: N.D.

Tlak pare: N.D.

Topljivost u vodi: Netopivo, Ne miješa se

Topljivost u ulje: Ne primjenjuje se.

Koeficijent raspodjele n-oktanol/voda (logaritamska vrijednost): Ne primjenjuje se.

Svojstva čestica:

Veličina čestica: Ne primjenjuje se.

9.2. Ostale informacije

Vodljivost: Ne primjenjuje se.

Eksplozivne osobine: N.A.

Osobine oksidiranja: N.A.

Brzina isparavanja: Ne primjenjuje se.

ODJELJAK 10.: Stabilnost i reaktivnost

10.1. Reaktivnost

Stabilan u normalnim uvjetima

10.2. Kemijska stabilnost

Stabilan u normalnim uvjetima

10.3. Mogućnost opasnih reakcija

Može se zapaliti u kontaktu s jakim oksidansima.

Zbog djelovanja topline ili u slučaju požara može doći do oslobađanja ugljikovih oksida i para koji mogu biti štetni za zdravlje.

10.4. Uvjeti koje treba izbjegavati

Čuvati odvojeno od izvora topline.

10.5. Inkompatibilni materijali

Snažni oksidansi, snažna redukcijska sredstva, alifatski i aromatski amini.

Vidi točku 10.3

10.6. Opasni proizvodi raspadanja

Pri odgovarajućem skladištenju i rukovanju ne razvijaju se opasni proizvodi raspadanja.

Vidi točku 5.2

ODJELJAK 11.: Toksikološke informacije

11.1. Informacije o razredima opasnosti kako su definirani u Uredbi (EZ) br. 1272/2008

Podaci o toksičnosti proizvoda:

a) akutna toksičnost	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
b) kožno nagrizanje/nadraživanje	Proizvod je razvrstan kao: Skin Irrit. 2(H315)
c) teške očne ozljede/teško očno nadraživanje	Proizvod je razvrstan kao: Eye Dam. 1(H318)
d) izazivanje kožne ili dišne preosjetljivosti	Proizvod je razvrstan kao: Skin Sens. 1(H317)
e) mutagenost zametnih stanica	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
f) kancerogenost	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
g) reproduktivna toksičnost	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
h) Specifična toksičnost za ciljne organe (STOT) jednokratno izlaganje	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
i) Specifična toksičnost za ciljne organe (STOT) opetovano izlaganje	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
j) opasnost u slučaju udisanja	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.

Podaci o toksičnosti glavnih sastojaka u proizvodu:

Produkt reakcije masnih kiselina, C18 alkil s aminima, frakcija polietilenpoli-tetraetilenpentamina

a) akutna toksičnost	LD50 Oralno Štakor > 2000 mg/kg LD50 Koža Štakor > 2000 mg/kg
----------------------	--

Masne kiseline, C18-nezasićene, dimeri, oligomerni produkti reakcije s masnim kiselinama iz tal ulja i trietilentetramina

CAS: 68082-29-1	a) akutna toksičnost	LD50 Oralno Štakor > 2000 LD50 Koža Štakor > 2000
-----------------	----------------------	--

2,4,6-tris(dimetilaminometil)fenol

CAS: 90-72-2	a) akutna toksičnost	ATE - Oralno: 500 mg/kg t.m. LD50 Koža Štakor > 1 mg/kg 6h
--------------	----------------------	---

3-aminometil-3,5,5-trimetilcikloheksilamin

CAS: 2855-13-2	a) akutna toksičnost	ATE - Oralno: 1030 mg/kg t.m.
----------------	----------------------	-------------------------------

11.2. Informacije o drugim opasnostima

Svojstva endokrine disrupcije:

Bez drugih endokrinih disruptora prisutnih u koncentraciji > = 0,1 %

ODJELJAK 12.: Ekološke informacije

Primjeniti dobre radne postupke da se produkt ne oslobađa u okoliš.

12.1. Toksičnost

Eko-Toksikološke informacije:

Štetno za vodeni okoliš s dugotrajnim učincima.

Popis eko-toksikoloških svojstava proizvoda

Proizvod je razvrstan kao: Aquatic Chronic 3(H412)

Popis sastojaka sa eko-toksikološkim svojstvima

Produkt reakcije masnih kiselina, C18 alkil s aminima, frakcija polietilenpoli-tetraetilenpentamina

- a) Akutna otrovnost na vodene organizme: LC50 Ribe 7.07 mg/l 96h
- a) Akutna otrovnost na vodene organizme: EC50 Daphnia 5.18 mg/l 48h
- a) Akutna otrovnost na vodene organizme: EC50 Algae 2.63 mg/l 72h
- b) Hronična otrovnost na vodene organizme: NOEC Ribe 5 mg/l
- b) Hronična otrovnost na vodene organizme: NOEC Algae 0.5 mg/l

Masne kiseline, C18-nezasićene, dimeri, oligomerni produkti reakcije s masnim kiselinama iz tal ulja i trietilentetramina

- CAS: 68082-29-1
- a) Akutna otrovnost na vodene organizme: LC50 Ribe 7.07 mg/l 96h
 - a) Akutna otrovnost na vodene organizme: EC50 Daphnia 5.18 mg/l 48h
 - a) Akutna otrovnost na vodene organizme: EC50 Algae 2.63 mg/l 72h
 - b) Hronična otrovnost na vodene organizme: NOEC Ribe 5 mg/l
 - b) Hronična otrovnost na vodene organizme: NOEC Algae 0.5 mg/l

2,4,6-tris(dimetilaminometil)fenol

- CAS: 90-72-2
- a) Akutna otrovnost na vodene organizme: LC50 Ribe 175 mg/l 96h
 - a) Akutna otrovnost na vodene organizme: LC50 Daphnia 718 mg/l 96h
 - a) Akutna otrovnost na vodene organizme: ErC50 Algae 84 mg/l 72h
 - a) Akutna otrovnost na vodene organizme: NOEC Algae 6.25 mg/l 72h

3-aminometil-3,5,5-trimetilcikloheksilamin

- CAS: 2855-13-2
- a) Akutna otrovnost na vodene organizme: LC50 Ribe 110 mg/l 96h
 - a) Akutna otrovnost na vodene organizme: EC50 Daphnia 23 mg/l 48h
 - a) Akutna otrovnost na vodene organizme: EC50 Algae > 50 mg/l 72h

12.2. Postojanost i razgradivost

Produkt reakcije masnih kiselina, C18 alkil s aminima, frakcija polietilenpoli-tetraetilenpentamina

Nepostojan i biorazgradiv

Masne kiseline, C18-nezasićene, dimeri, oligomerni produkti reakcije s masnim kiselinama iz tal ulja i trietilentetramina

CAS: 68082-29-1 Nije brzo-biološki razgradiv

2,4,6-tris(dimetilaminometil)fenol

CAS: 90-72-2 Nije brzo-biološki razgradiv

3-aminometil-3,5,5-trimetilcikloheksilamin

CAS: 2855-13-2 Nije brzo-biološki razgradiv

12.3. Bioakumulacijski potencijal

Ne primjenjuje se.

12.4. Pokretljivost u tlu

Ne primjenjuje se.

12.5. Rezultati procjene svojstava PBT i vPvB

Prema dostupnim podacima proizvod ne sadrži PBT/vPvB u postotku većem $\geq 0.1\%$.

12.6. Svojstva endokrine disrupcije

Bez drugih endokrinih disruptora prisutnih u koncentraciji $> = 0,1\%$

12.7. Ostali štetni učinci

Ne primjenjuje se.

ODJELJAK 13.: Zbrinjavanje

13.1. Metode obrade otpada

Regenerirati ako je moguće. Poslati ovlaštenim postrojenjima za odlaganje ili na spaljivanje pod kontroliranim uvjetima. Pri tome se pridržavati vrijedećih lokalnih i državnih regulativa.

Ne dopustiti prodor u kanalizaciju ili vodene tokove.

Zbrinite kontejnera onečišćenih proizvoda u skladu s lokalnim ili nacionalnim zakonskim odredbama.

Proizvod se nakon isteka roka trajanja mora odložiti prema propisima na snazi.

ODJELJAK 14.: Informacije o prijevozu

Nije klasificirano kao opasno po propisima za transport.

14.1. UN broj ili identifikacijski broj

N/A

14.2. Ispravno otpremno ime prema UN-u

ADR-Naziv za otpremu: N/A

IATA-Naziv za otpremu: N/A

IMDG-Naziv za otpremu: N/A

14.3. Razred(i) opasnosti pri prijevozu

ADR-Razred: N/A

IATA-Razred: N/A

IMDG-Razred: N/A

14.4. Skupina pakiranja

ADR-Grupa pakiranja: N/A

IATA-Grupa pakiranja: N/A

IMDG-Grupa pakiranja: N/A

14.5. Opasnosti za okoliš

Morski polutant: Ne

Zagađivači okoliša: Ne

IMDG-EMS: N/A

14.6. Posebne mjere opreza za korisnika

Ceste i Željeznica (ADR-RID):

ADR oslobađa:

ADR-Označavanje: N/A

ADR - Identifikacijski broj opasnosti: N/A

ADR-Posebne odredbe: N/A

ADR ograničenja prijevoza u tunelu:

Zrak (IATA):

IATA-Putnički zrakoplov: N/A

IATA-Teretni zrakoplov: N/A

IATA-Označavanje: N/A

IATA-Sporedni opasnosti: N/A

IATA-Erg: N/A

IATA-Posebne odredbe: N/A

More (IMDG):

IMDG-Skladištenje i rukovanje: N/A

IMDG-Segregacija: N/A

IMDG-Sporedni opasnosti: N/A

IMDG-Posebne odredbe: N/A

14.7. Prijevoz morem u različenom stanju u skladu s instrumentima IMO-a

Ne primjenjuje se.

ODJELJAK 15.: Informacije o propisima

15.1. Propisi u području sigurnosti, zdravlja i okoliša/posebno zakonodavstvo za tvar ili smjesu

Direktiva 98/24/EC (Rizici koji nastaju od kemijskih agenasa na radu)

Direktiva 2000/39/EC (Granična vrijednost profesionalne izloženosti)

Direktiva 2010/75/EU

Uredba (EC) br. 1907/2006 (REACH)

Uredba (EC) br. 1272/2008 (CLP)

Uredba (EC) br. 790/2009 (ATP 1 CLP) i (EZ) br. 758/2013

Uredba (EZ) br. 2020/878

Uredba (EZ) br. 286/2011 (ATP 2 CLP)

Uredba (EZ) br. 618/2012 (ATP 3 CLP)

Uredba (EZ) br. 487/2013 (ATP 4 CLP)

Uredba (EZ) br. 944/2013 (ATP 5 CLP)

- Uredba (EZ) br. 605/2014 (ATP 6 CLP)
- Uredba (EZ) br. 2015/1221 (ATP 7 CLP)
- Uredba (EZ) br. 2016/918 (ATP 8 CLP)
- Uredba (EZ) br. 2016/1179 (ATP 9 CLP)
- Uredba (EZ) br. 2017/776 (ATP 10 CLP)
- Uredba (EZ) br. 2018/669 (ATP 11 CLP)
- Uredba (EZ) br. 2018/1480 (ATP 13 CLP)
- Uredba (EZ) br. 2019/521 (ATP 12 CLP)
- Uredba (EZ) br. 2020/217 (ATP 14 CLP)
- Uredba (EZ) br. 2020/1182 (ATP 15 CLP)
- Uredba (EZ) br. 2021/643 (ATP 16 CLP)
- Uredba (EZ) br. 2021/849 (ATP 17 CLP)
- Uredba (EZ) br. 2022/692 (ATP 18 CLP)

Ograničenja u vezi s produktom ili sadržajnim tvarima u skladu s Prilogom XVII Uredbe (EZ-a) 1907/2006 (REACH) i naknadne izmjene:

- Ograničenja koja se odnose na proizvod: 3
- Ograničenja koja se odnose na sadržane tvari: 75

Odredbe prema direktivi 2012/18/EU (Seveso III)

Niti jedan

Uredba (EU) br. 649/2012 (Uredba PIC)

Nijedna tvar nije navedena

Njemačka klasifikacija opasnosti za vodu.

Klasa 3: iznimno opasni.

SVHC tvari:

Prema dostupnim podacima proizvod ne sadrži SVHC u postotku većem $\geq 0.1\%$.

15.2. Procjena kemijske sigurnosti

Procjena kemijske sigurnosti nije provedena za smjesu

ODJELJAK 16.: Ostale informacije

Šifra	Opis
H302	Štetno ako se proguta.
H314	Uzrokuje teške opekline kože i ozljede oka.
H315	Nadražuje kožu.
H317	Može izazvati alergijsku reakciju na koži.
H318	Uzrokuje teške ozljede oka.
H319	Uzrokuje jako nadraživanje oka.
H411	Otrovno za vodeni okoliš s dugotrajnim učincima.
H412	Štetno za vodeni okoliš s dugotrajnim učincima.

Šifra	Razred opasnosti i kategorija opasnosti Opis	
3.1/4/Oral	Acute Tox. 4	Akutna toksičnost (gutanje), kategorija 4
3.2/1B	Skin Corr. 1B	Nagrizajuće za kožu, kategorija 1B
3.2/2	Skin Irrit. 2	Nadražujuće za kožu, kategorija 2
3.3/1	Eye Dam. 1	Teška ozljeda oka, kategorija 1
3.3/2	Eye Irrit. 2	Nadražujuće za oči, kategorija 2
3.4.2/1	Skin Sens. 1	Izazivanje preosjetljivosti kože, kategorija 1
3.4.2/1A	Skin Sens. 1A	Izazivanje preosjetljivosti kože, kategorija 1A
4.1/C2	Aquatic Chronic 2	Kroničnu (dugoročnu) opasnost za organizme koji žive u vodi, kategorija 2
4.1/C3	Aquatic Chronic 3	Kroničnu (dugoročnu) opasnost za organizme koji žive u vodi, kategorija 3

Razvrstavanje i postupak razvrstavanja za smjese sukladno Uredbi (EZ) br. 1272/2008 (CLP):

Razvrstavanje prema Uredbi (EZ) br. 1272/2008	Postupak razvrstavanja
Skin Irrit. 2, H315	Računska metoda
Eye Dam. 1, H318	Računska metoda

Ovaj dokument izradila je tehnički kompetentna osoba za SDS, te koja je prikladno za to osposobljena.

Glavni bibliografski izvori:

ECDIN – Informacijska mreža za ekološke podatke za kemikalije – Zajednički istraživački centar, Komisija Europskih zajednica
SAX's OPASNE OSOBINE INDUSTRIJSKIH TVARI- Osmo izdanje - Van Nostrand Reinold
Sigurnosno-tehnički listovi dobavljača sirovina.

Ovdje objavljenе informacije se temelje na našem znanju u vrijeme gore navedenog datuma. Odnose se samo na navedene proizvode i ne predstavlja garanciju neke određene kvalitete.

Obaveza je korisnika da utvrdi da je ova informacija cjelovita i da odgovara specifičnoj upotrebi.

Ovaj MSDS poništava i zamjenjuje sva predhodna izdanja.

Legenda kratica i akronima upotrebljenih u sigurnosno-tehničkom listu:

ACGIH: Američka konferencija vladinih specijalista za industrijsku higijenu
ADR: Europski sporazum o međunarodnom cestovnom prijevozu opasnih tvari.
ATE: Procjena akutne toksičnosti
ATEmix: Procijenjena vrijednost akutne toksičnosti (Mješavine)
BEI: Indeks biološke izloženosti
CAS: CAS registarski broj (Američko kemijsko društvo)
CAV: Centar za otrove
CE: Europska zajednica
CLP: Razvrstavanje, označavanje, pakiranje.
CMR: Karcinogeno, Mutageno i Reprotoksično
COV: Hlapivi organski spoj
CSA: Procjena kemijske sigurnosti
CSR: Izvješće o kemijskoj sigurnosti
DNEL: Izvedena razina bez učinka.
EC50: Pulu maksimalna efektivna koncentracija
ECHA: Europska agencija za kemijske proizvode
EINECS: Europski propis postojećih trgovačkih kemijskih tvari.
ES: Scenario izloženosti
GefStoffVO: Propis o opasnim tvarima, Njemačka.
GHS: Globalno harmonizirani sustav razvrstavanja i označavanja kemikalija
IARC: Međunarodna agencija za istraživanja o karcinomu
IATA: Međunarodna udruga za zračni prijevoz.
IC50: Pulu maksimalna koncentracija inhibitora
IMDG: Međunarodni pomorski kodeks opasnog tereta.
LC50: Smrtna koncentracija u 50% slučajeva ispitivane populacije.
LD50: Smrtna doza u 50% slučajeva ispitivane populacije.
LDLo: Niska smrtonosna doza
N.A.: Nije primjenjivo
N/A: Nije primjenjivo
N/D: Nije definirano/Nije dostupno
N.D.: Nije dostupno
NIOSH: Državni institut za zaštitu na radu
NOAEL: Razina bez uočenih štetnih učinaka
OSHA: Upravljanje zaštitom na radu
PBT: Persistentno, bioakumulativno i toksično
PGK: Packaging Instruction
PNEC: Predviđena koncentracija bez učinka.
PSG: Putnici
RID: Propis o međunarodnom prijevozu opasnih tvari željeznicom
STEL: Granica kratkotrajne izloženosti.
STOT: Toksičnost za ciljani organ.
TLV: Granična vrijednost praga.
TLV-TWA: Granična vrijednost praga za vremenski ponderirani prosjek. (ACGIH standard)
vPvB: Vrlo persistentno, vrlo bioakumulativno
WGK: Njemačka klasifikacija opasnosti za vodu.

Odlomci promijenjeni u odnosu na prethodnu reviziju:

- ODJELJAK 2.: Identifikacija opasnosti
- ODJELJAK 6.: Mjere kod slučajnog ispuštanja
- ODJELJAK 8.: Nadzor nad izloženošću/osobna zaštita
- ODJELJAK 9.: Fizikalna i kemijska svojstva

- ODJELJAK 11.: Toksikološke informacije
- ODJELJAK 12.: Ekološke informacije
- ODJELJAK 13.: Zbrinjavanje
- ODJELJAK 14.: Informacije o prijevozu
- ODJELJAK 16.: Ostale informacije

2,4,6-tris(dimethylaminomethyl)phenol

Substance identification

Chemical Name: 2,4,6-tris(dimethylaminomethyl)phenol

CAS number: 90-72-2

EU index number: 603-069-00-0

EINECS number: 202-013-9

INDUSTRIAL APPLICATION OF COATINGS AND PAINTS - INDUSTRIAL USE

1. TITLE SECTION

Exposure scenario name: Industrial application of coatings and paints

Date - Version: 16/03/2020 - 1.0

Life cycle stage: Use at industrial sites

Main user group: Industrial uses

Sector(s) of use: Industrial uses (SU3)

Contributing scenario - Environment

CS1 Wet polymerization: ERC5

Contributing scenario - Worker

CS2 Roller, spray and stream application: PROC10

2. CONTRIBUTIVE SCENARIOS

2.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC5)

Environmental release categories: Industrial use leading to inclusion into/onto an article (ERC5)

Product features (article)

Physical form of the product: Liquid

Amount used, frequency and duration of use

Amounts used:

Daily quantity per site ≤ 0.8 tons/day

Annual amount per site ≤ 20 tons/year

Release Type: Continuous release

Issue days: 220 days a year

Measures and technical-organizational conditions

Control measures to prevent releases: No substance input into waste water.

Conditions and measures relating to municipal sewage treatment plants

Type of sewage treatment plant (STP): Municipal STP

STP effluent (m³/day): 2000

Conditions and measures for waste treatment (including the product waste)

Waste treatment: Collect and dispose of waste in accordance with local regulations. Refer to section 13.

Other operational conditions affecting environmental exposure

Flow rate of receiving surface water: 18000 m³/day

Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: For further data, see section 8 of the safety data sheet.

2.2. CS2 Contributing Scenario - Worker: Roller, spray and flow application (PROC10)

Process categories: Roller and brush application (PROC10)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 0,075 Pa

Concentration of the substance in the product: Includes substance shares in the product up to 25%

Amount used, frequency and duration of use/exposure

Duration: Covers up to 8 hours of daily exposure.

Measures and technical-organizational conditions

Technical organizational measures:

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Inhalation - minimum 30% efficiency. Local aspiration system. Ensure operating personnel are trained to minimize exposure. Inhalation - minimum 90% efficiency.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment:

During the specific training wear gloves resistant to chemicals (tested according to EN 374). Dermal - minimum 95% efficiency. Wear full face respirator conforming to EN136. Inhalation - minimum 99% efficiency. Wear waterproof clothing. Dermal - 97% minimum efficiency. For further data, see section 8 of the safety data sheet.

Other operational conditions affecting worker exposure

Temperature: A process temperature of up to 40°C is assumed.

Body parts exposed: Possible skin contact is believed to be limited to the hands.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC5)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
fresh water	0.001 mg/l	EUSES	0.017
fresh water sediment	0.006 mg/kg	EUSES	< 1
sea water	0.000138 mg/l	EUSES	0.016
Marine sediment	0.000564 mg/kg	EUSES	< 1
ground	0.001 mg/kg	EUSES	< 1
sewage treatment plant	0 mg/l	EUSES	< 0.01
environmentally exposed people - Inhalation	2.5E-05 mg/l	EUSES	< 1

3.2. CS2 Contributing Scenario - Worker: Roller, spray and flow application (PROC10)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, systemic, long-term	0.046 mg/m ³	chesar v 2.2	0.357
by inhalation, systemic, short-term	0.186 mg/m ³	chesar v 2.2	0.357
skin contact, systemic, long-term	0.025 mg/kg bw/day	chesar v 2.2	0.164
combined routes, systemic, long-term	N.d.	chesar v 2.2	0.521

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

INDUSTRIAL APPLICATION OF COATINGS AND PAINTS - PROFESSIONAL USE

1. TITLE SECTION

Exposure scenario name: Industrial application of coatings and paints

Date - Version: 16/03/2020 - 1.0

Life cycle stage: Generalized use by professional operators

Main user group: Professional uses

Sector(s) of use: Professional uses (SU22)

Contributing scenario - Environment

CS1 Wet polymerization: ERC8c

Contributing scenario - Worker

CS2 Roller, spray and stream application: PROC10

2. CONTRIBUTIVE SCENARIOS

2.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC8c)

Environmental release categories: Widespread use resulting in inclusion in or on the surface of an article (indoor use) (ERC8c)

Product features (article)

Physical form of the product: Liquid

Amount used, frequency and duration of use

Amounts used: Quantity per use ≤ 0.000218 tons/year

Measures and technical-organizational conditions

Control measures to prevent releases: No entry of substance into waste water.

Conditions and measures relating to municipal sewage treatment plants

Type of sewage treatment plant (STP): Municipal STP Water - minimum efficiency of 0.059%.

STP effluent (m³/day): 2000

Conditions and measures for waste treatment (including the product waste)

Waste treatment: Collect and dispose of waste in accordance with local regulations. Refer to section 13.

Other operational conditions affecting environmental exposure

Flow rate of receiving surface water: 18000 m³/day

Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: For further data, see section 8 of the safety data sheet.

2.2. CS2 Contributing Scenario - Worker: Roller, spray and flow application (PROC10)

Process categories: Roller and brush application (PROC10)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 0,075 Pa

Concentration of the substance in the product: Includes substance shares in the product up to 25%

Amount used, frequency and duration of use/exposure

Duration: Includes use up to 4 hours.

Measures and technical-organizational conditions

Technical organizational measures:

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Inhalation - minimum 30% efficiency.

Local aspiration system. Ensure operating personnel are trained to minimize exposure. Inhalation - minimum 80% efficiency.

Provide supplementary ventilation and other openings. Inhalation - minimum efficiency of 44%.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment:

During the specific training wear gloves resistant to chemicals (tested according to EN 374). Dermal - minimum 90% efficiency.

Wear full face respirator conforming to EN136. Inhalation - minimum 99% efficiency.

Wear waterproof clothing. Dermal - 97% minimum efficiency.

For further data, see section 8 of the safety data sheet.

Other operational conditions affecting worker exposure

Indoor use.

Temperature: A process temperature of up to 40°C is assumed.

Body parts exposed: Possible skin contact is believed to be limited to the hands.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC8c)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
fresh water	0.002 mg/l	EUSES	0.018
fresh water sediment	0.006 mg/kg	EUSES	< 1
sea water	0.000149 mg/l	EUSES	0.018
Marine sediment	0.000608 mg/kg	EUSES	< 1
ground	0.001 mg/kg	EUSES	< 1
sewage treatment plant	0.001 mg/l	EUSES	< 0.01
environmentally exposed people - Inhalation	1.03E-08 mg/l	EUSES	< 1

3.2. CS2 Contributing Scenario - Worker: Roller, spray and flow application (PROC10)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, systemic, long-term	0.078 mg/m ³	chesar v 2.2	0.599
by inhalation, systemic, short-term	0.52 mg/m ³	chesar v 2.2	1
skin contact, systemic, long-term	0.049 mg/kg bw/day	chesar v 2.2	0.329
combined routes, systemic, long-term	N.d.	chesar v 2.2	0.928

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Substance identification

Chemical Name: 3-aminomethyl-3,5,5-trimethylcyclohexylamine

CAS number: 2855-13-2

EU index number: 612-067-00-9

EINECS number: 220-666-8

ES1 Formulation or repackaging - INDUSTRIAL USES

1. TITLE SECTION

Exposure scenario name: Preparation and repackaging of substances and mixtures

Date - Version: 15/07/2020 - 1.0

Life cycle stage: Formulation or repackaging

Main user group: Industrial uses

Sector(s) of use: Industrial uses (SU3) - Large-scale production of basic chemicals (including petroleum products) (SU8) - Formulation [blending] of preparations and/or repackaging (SU10)

Contributing scenario - Environment

CS1 Wet formulation: ERC2

Contributing scenario - Worker

CS2 Use in closed systems: PROC3

CS3 Material Transfers: PROC8a

CS4 Material Transfers: PROC8b

CS5 Material Transfers: PROC9

CS6 Blend Operations: PROC5

2. CONDITIONS OF USE AFFECTING EXPOSURE

2.1. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Environmental release categories: Formulation of mixtures (ERC2)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use

Amounts used: Annual amount per site 2500 t

Release Type: Continuous release

Issue days: 300 days/year

Further environmental conditions:

Wet formulation

Air - minimum efficiency of: 0.25 %

Ground - minimum efficiency of: 0.01 %

Water - minimum efficiency of: 0.5 %

Measures and technical-organizational conditions

Control measures to prevent releases:

Air - minimum efficiency of: 0.25 %

Ground - minimum efficiency of: 0.01 %

Water - minimum efficiency of: 0.5 %

Conditions and measures for the municipal sewage treatment plant

Type of sewage treatment plant (STP): Municipal STP

STP effluent (m³/day): 8640

Conditions and measures for waste treatment (including the product waste)

Waste treatment: Do not spread industrial sludge on natural soils.

Other operational conditions affecting environmental exposure

Local seawater dilution factor: 100

Local fresh water dilution factor: 11

Flow rate of receiving surface water: 86400

Indoor use

2.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Process categories: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment:

Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency of: 95 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

2.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Process categories: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 240 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

2.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Process categories: Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 97%

Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

2.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Process categories: Transfer of a substance or preparation (filling/emptying) (dedicated filling line, including weighing) (PROC9)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

2.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Process categories: Mixing or Blending in Batch Processes (PROC5)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
sea water	1,025 kg/day	ECETOC TRA environment v2.0	0.81

3.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	4,258 mg/m ³	ECETOC TRA worker v2.0	0.212

3.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706
by inhalation, systemic, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706

3.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	2,129 mg/m ³	ECETOC TRA worker v2.0	0.106
by inhalation, systemic, short-term	2,129 mg/m ³	ECETOC TRA worker v2.0	0.106

3.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	7,096 mg/m ³	ECETOC TRA worker v2.0	0.353
by inhalation, systemic, short-term	7,096 mg/m ³	ECETOC TRA worker v2.0	0.353

3.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	7,096 mg/m ³	ECETOC TRA worker v2.0	0.353
by inhalation, systemic, short-term	7,096 mg/m ³	ECETOC TRA worker v2.0	0.353

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ES2 Formulation or repackaging - PROFESSIONAL USES

1. TITLE SECTION

Exposure scenario name: Preparation and repackaging of substances and mixtures

Date - Version: 10/03/2020 - 1.0

Life cycle stage: Formulation or repackaging

Main user group: Professional uses

Sector(s) of use: Manufacture of bulk, large scale chemicals (including petroleum products) (SU8) - Formulation [mixing] of preparations and/or re-packaging (SU10) - Professional uses (SU22)

Contributing scenario - Environment

CS1 Wet formulation: ERC2

Contributing scenario - Worker

CS2 Use in closed systems: PROC3

CS3 Material Transfers: PROC8a

CS3 Material Transfers: PROC8b

CS3 Material Transfers: PROC9

CS6 Blend Operations: PROC5

2. CONDITIONS OF USE AFFECTING EXPOSURE

2.2. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Environmental release categories: Formulation of mixtures (ERC2)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use

Amounts used: Annual amount per site 2500 t

Release Type: Continuous release

Issue days: 300 days/year

Further environmental conditions:

Wet formulation

Air - minimum efficiency of: 0.25 %

Ground - minimum efficiency of: 0.01 %

Water - minimum efficiency of: 0.5 %

Measures and technical-organizational conditions

Control measures to prevent releases:

Air - minimum efficiency of: 0.25 %

Ground - minimum efficiency of: 0.01 %

Water - minimum efficiency of: 0.5 %

Conditions and measures for the municipal sewage treatment plant

Type of sewage treatment plant (STP): Municipal STP

STP effluent (m³/day): 8640

Conditions and measures for waste treatment (including the product waste)

Waste treatment: Do not spread industrial sludge on natural soils.

Other operational conditions affecting environmental exposure

Local seawater dilution factor: 100

Local fresh water dilution factor: 11

Flow rate of receiving surface water: 86400

Indoor use

2.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Process categories: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 95 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

2.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Process categories: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 240 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

2.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Process categories: Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 240 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

2.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Process categories: Transfer of a substance or preparation (filling/emptying) (dedicated filling line, including weighing) (PROC9)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 240 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

2.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Process categories: Mixing or Blending in Batch Processes (PROC5)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 60 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
sea water	1,025 kg/day	ECETOC TRA environment v2.0	0.81

3.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	8,515 mg/m ³	ECETOC TRA worker v2.0	0.424

3.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	7,096 mg/m ³	ECETOC TRA worker v2.0	0.353
by inhalation, systemic, short-term	7,096 mg/m ³	ECETOC TRA worker v2.0	0.353

3.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706
by inhalation, systemic, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706

3.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706
by inhalation, systemic, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706

3.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.