

Sigurnosno-tehničkog lista**DILUENTE ADW**

Sigurnosno-tehničkog lista, datum: 12/06/2023 Opis version 1

Upozorenje: označavanje brojevima ide od 1.

ODJELJAK 1.: Identifikacija tvari/smjese i podaci o društvu/poduzeću**1.1. Identifikacijska oznaka proizvoda**

Identifikacija preparata:

Trgovačko ime: DILUENTE ADW

Trgovački kod: 583K

UFI: D2M1-00XS-S00R-AKV1

1.2. Utvrđene relevantne uporabe tvari ili smjese i uporabe koje se ne preporučuju

Preporučana upotreba: Razrjeđivač

1.3. Podaci o dobavljaču koji isporučuje sigurnosno-tehnički list

Tvrtka: FASSA Srl

Via Lazzaris, 3 - 31027 Spresiano (TV) - ITALY

Tel. +39 0422 7222

Fax +39 0422 887509

Odgovorna osoba: laboratorio.spresiano@fassabortolo.it

1.4. Broj telefona za izvanredna stanja

+3851 2348 342

ODJELJAK 2.: Identifikacija opasnosti**2.1. Razvrstavanje tvari ili smjese****Uredba (EC) br. 1272/2008 (CLP)**

Flam. Liq. 2	Lako zapaljiva tekućina i para.
Eye Irrit. 2	Uzrokuje jako nadraživanje oka.
STOT SE 3	Može izazvati pospanost ili vrtoglavicu.

Fizikalno-kemijski učinci štetni po ljudsko zdravlje i okoliš:

Nema ostalih rizika

2.2. Elementi označivanja**Uredba (EC) br. 1272/2008 (CLP):****Piktogrami i oznaka opasnosti**

Opasnost

Oznake upozorenja

H225	Lako zapaljiva tekućina i para.
H319	Uzrokuje jako nadraživanje oka.
H336	Može izazvati pospanost ili vrtoglavicu.

Oznake obavijesti

P210	Čuvati odvojeno od topline, vrućih površina, iskri, otvorenih plamena i ostalih izvora paljenja. Ne pušiti.
P233	Čuvati u dobro zatvorenom spremniku.
P261	Izbjegavati udisanje dima/plina/magle/pare/aerosola.
P280	Nositi zaštitne rukavice te zaštitu za oči/zaštitu za lice.
P312	U slučaju zdravstvenih tegoba nazvati CENTAR ZA KONTROLU OTROVANJA/liječnika.
P370+P378	U slučaju požara, rabiti suhi prah za gašenje.
P403+P235	Skladištiti na dobro prozračenom mjestu. Održavati hladnim.

Posebna osiguranja:

EUH066 Ponavljano izlaganje može prouzročiti sušenje ili pucanje kože.

Sadržji:

etil-acetat
n-butil-acetat

Posebne odredbe prema Prilogu XVII REACH-a i naknadnih amandmana:

Niti jedan

2.3. Ostale opasnosti

Bez PBT-a, vPvB-a ili endokrinih disruptora prisutnih
u koncentraciji > = 0,1 %.

Nema ostalih rizika

ODJELJAK 3.: Sastav/informacije o sastojcima

3.1. Tvari

Ne primjenjuje se.

3.2. Smjese

Identifikacija preparata: DILUENTE ADW

Opasni sastojci u smislu CLP Uredbe koja se odnosi na razvrstavanje:

Količina	Naziv	Ident. Broj.	Klasifikacija	Broj registriranih slučajeva
≥ 80%	etil-acetat	CAS:141-78-6 EC:205-500-4 Index:607-022-00-5	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	01-2119475103-46-xxxx
≥5 - <10 %	n-butil-acetat	CAS:123-86-4 EC:204-658-1 Index:607-025-00-1	Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	01-2119485493-29-xxxx

ODJELJAK 4.: Mjere prve pomoći

4.1. Opis mjera prve pomoći

U slučaju kontakta sa kožom:

Smjesta skinuti zagađenu odjeću i ukloniti je na bezbjedan način.
Odmah oprati obilnom količinom tekuće vode i eventualno sapunom dijelove tijela koji su došli u dodir s proizvodom, čak i u slučaju da samo sumnjate da je došlo do kontakta.
Oprati čitavo tijelo (istuširati se ili okupati).

U slučaju kontakta sa očima:

U slučaju kontakta sa očima, ispirati oči vodom neko vrijeme, držati otvorene kapke, a potom zatražiti pomoć oftalmologa.
Zaštititi neozlijeđeno oko.

U slučaju gutanja:

Ne poticati povraćanje, obratiti se liječniku i pokazati listić o sigurnosti i oznaku kemijskog rizika.

U slučaju udisanja:

Izloženu osobu treba iznijeti na svjež zrak, držati je na toplom, a ista mora mirovati.

4.2. Najvažniji simptomi i učinci, akutni i odgođeni

Simptomi i učinci su u skladu s očekivanjima od opasnosti kako je prikazano u 2. odjeljku.

4.3. Navod o potrebi za hitnom liječničkom pomoći i posebnom obradom

U slučaju nesreće ili slabosti smjesta se obratiti liječniku (ako je moguće, pokazati upute za uporabu ili sigurnosni list).

ODJELJAK 5.: Mjere za suzbijanje požara

5.1. Sredstva za gašenje

Prikladna sredstva za gašenje požara:

U slučaju požara, rabiti suhi prah za gašenje.
CO2, aparati za gašenje požara prahom, pjena, raspršivanje vode.

Sredstva za gašenje požara koja ne treba koristiti iz bezbjednosnih razloga:

Voda u mlazovima.

5.2. Posebne opasnosti koje proizlaze iz tvari ili smjese

Sagorijevanjem se oslobađaju teški dimovi.
Ne udisati plinove nastale eksplozijom i/ili izgaranjem (ugljikov monoksid i ugljikov dioksid, dušikove okside).
Pare mogu stvoriti eksplozivne smjese sa zrakom.

5.3. Savjeti za gasitelje požara

Koristiti prikladne dišne aparate.
Posebno pokupiti zaprljanu vodu, koja je korištena za gašenje požara. Ne bacati ovu vodu u kanalizacionu mrežu.

ODJELJAK 6.: Mjere kod slučajnog ispuštanja

6.1. Osobne mjere opreza, zaštitna oprema i postupci za izvanredna stanja

- Koristiti sredstva za osobnu zaštitu.
- Ukloniti svaki izvor plamena.
- Ukloniti osobe na sigurno mjesto.
- Konzultirati mjere zaštite opisane u točkama 7. i 8.

6.2. Mjere zaštite okoliša

- Spriječiti prodiranje u tlo/dublje slojeve zemlje. Spriječiti ulivanje u površinske vode ili u kanalizacionu mrežu.
- U slučaju izlaska plina ili prodiranja u vodene tokove, tlo ili kanalizacionu mrežu, obavijestiti nadležna tijela.

6.3. Metode i materijal za sprečavanje širenja i čišćenje

- Materijal je prikladan za skupljanje: inertni upijajući materijal (npr. pijesak, vermikulit)
- Zadržati vodu kojom ste izvršili pranje, pa je eliminirati.

6.4. Uputa na druge odjeljke

- Pogledati također i paragrafe 8. i 13.

ODJELJAK 7.: Rukovanje i skladištenje

7.1. Mjere opreza za sigurno rukovanje

- Izbjegavati dodir s kožom i očima, udisanje para i maglica.
- Ne koristite prazne spremnike prije no što ih očistite.
- Prije prijenosa proizvoda, uvjeriti se da u spremnicima nema ostataka nekompatibilnih tvari.

Savjeti o općoj higijeni na radnom mjestu:

- Kontaminirana odjeća se smjesta mora zamijeniti prije ulaska u menze.
- Ne konzumirati hranu i piće na radnom mjestu.
- Pogledati i paragraf 8. u svezi sa preporučenim napravama za zaštitu.

7.2. Uvjeti sigurnog skladištenja, uzimajući u obzir moguće inkompatibilnosti

- Čuvati spremnike dobro zatvorene na hladnom i dobro prozračenom mjestu daleko od izvora topline.
- Čuvati dalje od nezaštićenog plamena, iskrenja i izvora topline. Izbjegavati izravno izlaganje sunčevoj svjetlosti.
- Držati podalje od hrane, pića i krmiva.

Inkompatibilne tvari:

- Vidi točku 10.5

Upute za prostorije za skladištenje:

- Hladno i adekvatno prozračeno.

7.3. Posebna krajnja uporaba ili uporabe

Preporuke

- Vidi točku 1.2

Specifične otopine za industrijski sektor

- Nema posebne upotrebe

ODJELJAK 8.: Nadzor nad izloženošću/osobna zaštita

8.1. Nadzorni parametri

Spisak komponenti sa OEL vrijednošću

	OEL Tip zemlja	Dugoročno mg/m3	Dugoročno ppm	Kratkoročno mg/m3	Kratkoročno ppm	Napomen
etil-acetat CAS: 141-78-6	ACGIH		400			URT and eye irr
	UE	734	200	1468	400	
	MAK AUSTRIA	734.000	200	1468.000	400	
	VLEP BELGIUM	734.000	200	1468.000	400	
	VLEP FRANCE	734.000	200	1468.000	400	
	AGW GERMANY	730.000	200.000	1460.000	400	
	MAK GERMANY	750.000	200.000	1500.000	400.000	
	ÁK HUNGARY	1400		1400		
	VLEP ITALY	734	200.000	1468	400.000	
	NDS POLAND	734.000		1468.000		
	VLEP ROMANIA	400.000	111.000	500.000	139.000	
	VLA SPAIN	734.000	200.000	1460.000	400.000	

n-butil-acetat CAS: 123-86-4	SUVA	SWITZERLAN D	730.000	200.000	1470.000	400.000	Eye and URT irr
	WEL	U.K.	730.000	200.000	1460.000	400.000	
	VLE	PORTUGAL	734.000	200.000	1468.000	400.000	
	GVI	CROATIA	734.000	200.000	1468.000	400.000	
	MV	SLOVENIA	734.000	200.000	1468.000	400.000	
	TLV	CZECHIA	700.000	191.100	900.000	245.700	
	IPRV	LITHUANIA	500.000	150.000	1100.000	300.000	
	TLV	BULGARIA	734.000	200.000	1468.000	400.000	
	ACGIH			50		150	
	UE		241	50	723	150	
	MAK	AUSTRIA	480	100	480.000	100.000	
	VLEP	BELGIUM	238.000	50.000	712.000	150.000	
	VLEP	FRANCE	710.000	150	940.000	200	
	AGW	GERMANY	300.000	62.000	600.000	124.000	
	MAK	GERMANY	480.000	100.000	960.000	200	
	ÁK	HUNGARY	950		950		
	NDS	POLAND	240		720		
	VLEP	ROMANIA	715.000	150.000	950.000	200.000	
	VLA	SPAIN	724.000	150.000	965.000	200.000	
	SUVA	SWITZERLAN D	240.000	50.000	720.000	150.000	
	WEL	U.K.	724.000	150.000	966.000	200.000	
	GVI	CROATIA	724.000	150.000	966.000	200.000	
	MV	SLOVENIA	300.000	62.000	600.000	124.000	
	TLV	CZECHIA	241.000		723.000		
	TLV	BULGARIA	710.000		950.000		

Granične vrijednosti izloženosti PNEC

	PNEC Ograni čiti	Putevi izloženosti	Učestalost izloženosti	Primjedbe
etil-acetat CAS: 141-78-6	0.024 mg/l	Morska voda		
	0.24 mg/l	Svježa voda		
	0.115 mg/kg	Sedimenti morske vode		
	1.15 mg/kg	Sedimenti svježe vode		
	650 mg/l	Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP)		
n-butil-acetat CAS: 123-86-4	0.148 mg/kg	Tlo (poljoprivredno)		
	0.018 mg/l	Morska voda		
	0.18 mg/l	Svježa voda		
	0.098 mg/kg	Sedimenti morske vode		
	0.981 mg/kg	Sedimenti svježe vode		

35.6 mg/l Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP)

0.09 mg/kg Tlo (poljoprivredno)

Izvedena razina bez učinka. (DNEL)

	Industrijski djelatnik	Profesionalni djelatnik	Potrošač	Putevi izloženosti	Učestalost izloženosti	Primjedbe
etil-acetat CAS: 141-78-6		734 mg/m ³	367 mg/m ³	Ljudi inhalacijski	Dugotrajni, sistemski učinci	
		734 mg/m ³	367 mg/m ³	Ljudi inhalacijski	Dugotrajni, lokalni učinci	
		1468 mg/m ³	734 mg/m ³	Ljudi inhalacijski	Kratkotrajni, sistemski učinci	
		1468 mg/m ³	734 mg/m ³	Ljudi inhalacijski	Kratkotrajni, lokalni učinci	
		63 mg/kg	37 mg/kg	Ljudi dermalno	Dugotrajni, sistemski učinci	
n-butil-acetat CAS: 123-86-4			4.5 mg/kg	Ljudi oralno	Dugotrajni, sistemski učinci	
		300 mg/m ³	35.7 mg/m ³	Ljudi inhalacijski	Dugotrajni, sistemski učinci	
		600 mg/m ³	300 mg/m ³	Ljudi inhalacijski	Kratkotrajni, sistemski učinci	
		300 mg/m ³	35.7 mg/m ³	Ljudi inhalacijski	Dugotrajni, lokalni učinci	
		600 mg/m ³	300 mg/m ³	Ljudi inhalacijski	Kratkotrajni, lokalni učinci	
		11 mg/kg	6 mg/kg	Ljudi dermalno	Dugotrajni, sistemski učinci	
		11 mg/kg	6 mg/kg	Ljudi dermalno	Kratkotrajni, sistemski učinci	
			2 mg/kg	Ljudi oralno	Kratkotrajni, sistemski učinci	
			2 mg/kg	Ljudi oralno	Dugotrajni, sistemski učinci	

8.2. Nadzor nad izloženošću

Osigurati odgovarajuću ventilaciju. Kad je to razumno moguće, to se može postići upotrebom rezervne ventilacije i dobre opće aspiracije.

Zaštita očiju:

Čaše sa bočnom zaštitom (EN 166).

Zaštita kože:

Osoblje treba nositi antistatičku odjeću od prirodnih vlakana ili sintetičkih vlakana otpornih na visoke temperature.

Zaštita za ruke:

Ne postoji materijal ili kombinacija materijala za rukavice koji bi mogli jamčiti neograničenu otpornost na bilo koji kemijski proizvod ili kombinaciju proizvoda.

Ako je riječ o duljem ili ponavljanom rukovanju, koristite se rukavicama otpornim na kemijske proizvode.

Prikladne rukavice tipa (EN 374/EN 16523); FKM (fluorirana guma): debljina > = 0,4 mm; vrijeme prodiranja > = 480 min.; NBR (nitrilna guma): debljina > = 0,4 mm; vrijeme prodiranja > = 480 min.

Izbor prikladnih rukavica ne ovisi samo o materijalu, nego i o drugim karakteristikama kvalitete koje se razlikuju od proizvođača do proizvođača, i o načinima i vremenu upotrebe smjese.

Zaštita pri disanju:

Ako su radnici izloženi koncentracijama višima od granice izloženosti, moraju upotrebljavati odgovarajuće certificirane respiratore.

Kombinirana filtrirajuća naprava (EN 14387): maska s filtrom A-P2.

Kontrola izlaganja u okolišu:

Vidi točku 6.2

ODJELJAK 9.: Fizikalna i kemijska svojstva

9.1. Informacije o osnovnim fizikalnim i kemijskim svojstvima

Izgled: tekuće
Boja: bezbojno
Miris: voćno
Točka topljenja/smrzavanja: N.D.
Početna točka ključanja i vrijeme ključanja: > 77 °C (171 °F)
Zapaljivost: Proizvod je razvrstan kao Flam. Liq. 2 H225
Gornja/donja granica zapaljivosti ili eksplozije: N.D.
Plamište: < 23°C
Temperatura samozapaljenja: N.D.
Temperatura raspadanja: N.D.
pH: Ne primjenjuje se. (Ne odnosi se zbog prirode proizvoda)
Kinematička viskoznost: Ne primjenjuje se.
Gustoća: 0,9 kg/l (Interna metoda)
Gustoća para: 3,04
Tlak pare: N.D.
Topljivost u vodi: Ne primjenjuje se.
Topljivost u ulje: Ne primjenjuje se.
Koeficijent raspodjele (n-okanol/voda): Ne primjenjuje se.

Svojstva čestica:

Veličina čestica: Ne primjenjuje se.

9.2. Ostale informacije

Vodljivost: N.D.
Eksplozivne osobine: Ne primjenjuje se.
Osobine oksidiranja: Ne primjenjuje se.
Brzina isparavanja: Ne primjenjuje se.

ODJELJAK 10.: Stabilnost i reaktivnost

10.1. Reaktivnost

Stabilan u normalnim uvjetima

10.2. Kemijska stabilnost

Stabilan u normalnim uvjetima

10.3. Mogućnost opasnih reakcija

Zbog djelovanja topline ili u slučaju požara može doći do oslobađanja ugljikovih oksida i para koji mogu biti štetni za zdravlje.
Držati podalje od oksidansa, vrlo lužnatih i vrlo kiselih materijala radi sprečavanja egzotermnih reakcija.
Pare mogu stvoriti eksplozivne smjese sa zrakom.

10.4. Uvjeti koje treba izbjegavati

Čuvati odvojeno od izvora topline.

10.5. Inkompatibilni materijali

Izbjegavati dodir s oksidirajućim materijalima. Proizvod se može zapaliti.
Vidi točku 10.3

10.6. Opasni proizvodi raspadanja

Pri odgovarajućem skladištenju i rukovanju ne razvijaju se opasni proizvodi raspadanja.
Vidi točku 5.2

ODJELJAK 11.: Toksikološke informacije

11.1. Informacije o razredima opasnosti kako su definirani u Uredbi (EZ) br. 1272/2008

Podaci o toksičnosti proizvoda:

a) akutna toksičnost	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
b) kožno nagrizanje/nadraživanje	Nije kategorizirano Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
c) teške očne ozljede/teško očno nadraživanje	Proizvod je razvrstan kao: Eye Irrit. 2(H319)
d) izazivanje kožne ili dišne preosjetljivosti	Nije kategorizirano

	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
e) mutagenost zametnih stanica	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
f) kancerogenost	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
g) reproduktivna toksičnost	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
h) Specifična toksičnost za ciljne organe (STOT) jednokratno izlaganje	Proizvod je razvrstan kao: STOT SE 3(H336)
i) Specifična toksičnost za ciljne organe (STOT) opetovano izlaganje	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
j) opasnost u slučaju udisanja	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.

Podaci o toksičnosti glavnih sastojaka u proizvodu:

etil-acetat	a) akutna toksičnost	LD50 Oralno Štakor 4934 mg/kg LD50 Koža Kunić > 20000 mg/kg LC50 Udisanje pare Štakor > 22.5 mg/l 6h
n-butil-acetat	a) akutna toksičnost	LD50 Oralno Štakor 10760 mg/kg LD50 Koža Kunić 14112 mg/kg LC50 Udisanje pare Štakor > 21.1 mg/l 4h

11.2. Informacije o drugim opasnostima

Svojstva endokrine disrupcije:

Bez drugih endokrinih disruptora prisutnih u koncentraciji $\geq 0,1\%$

ODJELJAK 12.: Ekološke informacije

Primjeniti dobre radne postupke da se produkt ne oslobađa u okoliš.

12.1. Toksičnost

Eko-Toksikološke informacije:

Popis eko-toksikoloških svojstava proizvoda

Nije razvrstan kao opasan za okoliš

Nema raspoloživih podataka za proizvod

Popis sastojaka sa eko-toksikološkim svojstvima

Sastojak	Ident. Broj.	Ekotoksik. Informacije
etil-acetat	CAS: 141-78-6 - EINECS: 205- 500-4 - INDEX: 607-022-00-5	a) Akutna otrovnost na vodene organizme : LC50 Ribe 230 mg/l 96h
		a) Akutna otrovnost na vodene organizme : EC50 Daphnia 165 mg/l 48h
n-butil-acetat	CAS: 123-86-4 - EINECS: 204- 658-1 - INDEX: 607-025-00-1	a) Akutna otrovnost na vodene organizme : LC50 Ribe 18 mg/l 96h
		a) Akutna otrovnost na vodene organizme : EC50 Daphnia 44 mg/l 48h
		a) Akutna otrovnost na vodene organizme : EC50 Algae 675 mg/l 72h
		b) Hronična otrovnost na vodene organizme : NOEC Daphnia 23 mg/l - 21d

12.2. Postojanost i razgradivost

Sastojak	Postojanost/razgradivost:
etil-acetat	Brzo-biološki razgradiv
n-butil-acetat	Brzo-biološki razgradiv

12.3. Bioakumulacijski potencijal

Ne primjenjuje se.

12.4. Pokretljivost u tlu

Ne primjenjuje se.

12.5. Rezultati procjene svojstava PBT i vPvB

Prema dostupnim podacima proizvod ne sadrži
PBT/vPvB u postotku većem $\geq 0.1\%$.

12.6. Svojstva endokrine disrupcije

Bez drugih endokrinih disruptora prisutnih u koncentraciji $> = 0,1 \%$

12.7. Ostali štetni učinci

Ne primjenjuje se.

ODJELJAK 13.: Zbrinjavanje

13.1. Metode obrade otpada

Regenerirati ako je moguće. Poslati ovlaštenim postrojenjima za odlaganje ili na spaljivanje pod kontroliranim uvjetima. Pri tome se pridržavati vrijedećih lokalnih i državnih regulativa.

Ne dopustiti prodor u kanalizaciju ili vodene tokove.

Zbrinite kontejnera onečišćenih proizvoda u skladu s lokalnim ili nacionalnim zakonskim odredbama.

ODJELJAK 14.: Informacije o prijevozu



14.1. UN broj ili identifikacijski broj

1993

14.2. Ispravno otpremno ime prema UN-u

ADR-Naziv za otpremu: ZAPALJIVA TEKUĆINA, N.D.N. (etil-acetat - n-butil-acetat)

IATA-Tehnički naziv: FLAMMABLE LIQUID, N.O.S. (etil-acetat - n-butil-acetat)

IMDG-Tehnički naziv: FLAMMABLE LIQUID, N.O.S. (etil-acetat - n-butil-acetat)

14.3. Razred(i) opasnosti pri prijevozu

ADR-Razred: 3

IATA-Razred: 3

IMDG-Razred: 3

14.4. Skupina pakiranja

ADR-Grupa pakiranja: II

IATA-Grupa pakiranja: II

IMDG-Grupa pakiranja: II

14.5. Opasnosti za okoliš

Morski polutant: Ne

Zagađivači okoliša: Ne

IMDG-EMS: F-E, S-E

14.6. Posebne mjere opreza za korisnika

Ceste i Željeznica (ADR-RID):

ADR-Označavanje: 3

ADR - Identifikacijski broj opasnosti: 33

ADR-Posebne odredbe: 274 601 640D

ADR ograničenja prijevoza u tunelu:

Zrak (IATA):

IATA-Putnički zrakoplov: 353

IATA-Teretni zrakoplov: 364

IATA-Označavanje: 3

IATA-Sporedni opasnosti: -

IATA-Erg: 3H

IATA-Posebne odredbe: A3

More (IMDG):

IMDG-Šifra utovara u brod: Category B

IMDG-Napomena za utovar u brod: -

IMDG-Sporedni opasnosti -

IMDG-Posebne odredbe: 274

14.7. Prijevoz morem u razlivenom stanju u skladu s instrumentima IMO-a

Ne primjenjuje se.

ODJELJAK 15.: Informacije o propisima

15.1. Propisi u području sigurnosti, zdravlja i okoliša/posebno zakonodavstvo za tvar ili smjesu

Direktiva 98/24/EC (Rizici koji nastaju od kemijskih agenasa na radu)

Direktiva 2000/39/EC (Granična vrijednost profesionalne izloženosti)

Direktiva 2010/75/EU

Uredba (EC) br. 1907/2006 (REACH)

Uredba (EC) br. 1272/2008 (CLP)

Uredba (EC) br. 790/2009 (ATP 1 CLP) i (EZ) br. 758/2013

Uredba (EZ) br. 2020/878

Uredba (EZ) br. 286/2011 (ATP 2 CLP)

Uredba (EZ) br. 618/2012 (ATP 3 CLP)

Uredba (EZ) br. 487/2013 (ATP 4 CLP)

Uredba (EZ) br. 944/2013 (ATP 5 CLP)

Uredba (EZ) br. 605/2014 (ATP 6 CLP)

Uredba (EZ) br. 2015/1221 (ATP 7 CLP)

Uredba (EZ) br. 2016/918 (ATP 8 CLP)

Uredba (EZ) br. 2016/1179 (ATP 9 CLP)

Uredba (EZ) br. 2017/776 (ATP 10 CLP)

Uredba (EZ) br. 2018/669 (ATP 11 CLP)

Uredba (EZ) br. 2018/1480 (ATP 13 CLP)

Uredba (EZ) br. 2019/521 (ATP 12 CLP)

Uredba (EZ) br. 2020/217 (ATP 14 CLP)

Uredba (EZ) br. 2020/1182 (ATP 15 CLP)

Uredba (EZ) br. 2021/643 (ATP 16 CLP)

Uredba (EZ) br. 2021/849 (ATP 17 CLP)

Uredba (EZ) br. 2022/692 (ATP 18 CLP)

Ograničenja u vezi s produktom ili sadržajnim tvarima u skladu s Prilogom XVII Uredbe (EZ-a) 1907/2006 (REACH) i naknadne izmjene:

Ograničenja koja se odnose na proizvod: 3, 40

Ograničenja koja se odnose na sadržane tvari: 75

Odredbe prema direktivi 2012/18/EU (Seveso III)

Kategorija Seveso III prema dijelu 1. Priloga 1.

proizvod pripada kategoriji: P5c

Donje granične količine opasnih tvari (u tonama) - male količine

5000

Donje granične količine opasnih tvari (u tonama) - velike količine

50000

Uredba (EU) br. 649/2012 (Uredba PIC)

Nijedna tvar nije navedena

Njemačka klasifikacija opasnosti za vodu.

1: Low hazard to waters

SVHC tvari:

Prema dostupnim podacima proizvod ne sadrži SVHC u postotku većem $\geq 0.1\%$.

15.2. Procjena kemijske sigurnosti

Procjena kemijske sigurnosti nije provedena za smjesu

ODJELJAK 16.: Ostale informacije

Šifra	Opis
EUH066	Ponavljano izlaganje može prouzročiti sušenje ili pucanje kože.
H225	Lako zapaljiva tekućina i para.
H226	Zapaljiva tekućina i para.
H319	Uzrokuje jako nadraživanje oka.

H336 Može izazvati pospanost ili vrtoglavicu.

Šifra Razred opasnosti i kategorija opasnosti Opis

2.6/2	Flam. Liq. 2	Zapaljiva tekućina, kategorija 2
2.6/3	Flam. Liq. 3	Zapaljiva tekućina, kategorija 3
3.3/2	Eye Irrit. 2	Nadražujuće za oči, kategorija 2
3.8/3	STOT SE 3	Specifična toksičnost za ciljane organe – jednokratno izlaganje, Kategorija 3

Razvrstavanje i postupak razvrstavanja za smjese sukladno Uredbi (EZ) br. 1272/2008 (CLP):

Razvrstavanje prema Uredbi (EZ) br. 1272/2008 Postupak razvrstavanja

2.6/2	Na temelju rezultata ispitivanja
3.3/2	Računska metoda
3.8/3	Računska metoda

Ovaj dokument izradila je tehnički kompetentna osoba za SDS, te koja je prikladno za to osposobljena.

Glavni bibliografski izvori:

ECDIN – Informacijska mreža za ekološke podatke za kemikalije – Zajednički istraživački centar, Komisija Europskih zajednica
SAX's OPASNE OSOBINE INDUSTRIJSKIH TVARI- Osmo izdanje - Van Nostrand Reinold
Sigurnosno-tehnički listovi dobavljača sirovina.
CCNL - Apendiks 1

Ovdje objavljenе informacije se temelje na našem znanju u vrijeme gore navedenog datuma. Odnose se samo na navedene proizvode i ne predstavlja garanciju neke određene kvalitete.

Obaveza je korisnika da utvrdi da je ova informacija cjelovita i da odgovara specifičnoj upotrebi.

Ovaj MSDS poništava i zamjenjuje sva predhodna izdanja.

Legenda kratica i akronima upotrebljenih u sigurnosno-tehničkom listu:

ACGIH: Američka konferencija vladinih specijalista za industrijsku higijenu

ADR: Europski sporazum o međunarodnom cestovnom prijevozu opasnih tvari.

ATE: Procjena akutne toksičnosti

ATEmix: Procijenjena vrijednost akutne toksičnosti (Mješavine)

BEI: Indeks biološke izloženosti

CAS: CAS registarski broj (Američko kemijsko društvo)

CAV: Centar za otrove

CE: Europska zajednica

CLP: Razvrstavanje, označavanje, pakiranje.

CMR: Karcinogeno, Mutageno i Reprotoksično

COV: Hlapivi organski spoj

CSA: Procjena kemijske sigurnosti

CSR: Izvješće o kemijskoj sigurnosti

DNEL: Izvedena razina bez učinka.

EC50: Pulu maksimalna efektivna koncentracija

ECHA: Europska agencija za kemijske proizvode

EINECS: Europski propis postojećih trgovačkih kemijskih tvari.

ES: Scenario izloženosti

GefStoffVO: Propis o opasnim tvarima, Njemačka.

GHS: Globalno harmonizirani sustav razvrstavanja i označavanja kemikalija

IARC: Međunarodna agencija za istraživanja o karcinomu

IATA: Međunarodna udruga za zračni prijevoz.

IC50: Pulu maksimalna koncentracija inhibitora

IMDG: Međunarodni pomorski kodeks opasnog tereta.

LC50: Smrtna koncentracija u 50% slučajeva ispitivane populacije.

LD50: Smrtna doza u 50% slučajeva ispitivane populacije.

LDLo: Niska smrtonosna doza

N.A.: Nije primjenjivo

N/A: Nije primjenjivo

N/D: Nije definirano/Nije dostupno

N.D.: Nije dostupno

NIOSH: Državni institut za zaštitu na radu

NOAEL: Razina bez uočenih štetnih učinaka

OSHA: Upravljanje zaštitom na radu

PBT: Persistentno, bioakumulativno i toksično

PGK: Packaging Instruction

PNEC: Predviđena koncentracija bez učinka.

PSG: Putnici

RID: Propis o međunarodnom prijevozu opasnih tvari željeznicom

STEL: Granica kratkotrajne izloženosti.

STOT: Toksičnost za ciljani organ.

TLV: Granična vrijednost praga.

TLV-TWA: Granična vrijednost praga za vremenski ponderirani prosjek. (ACGIH standard)

vPvB: Vrlo persistentno, vrlo bioakumulativno

WGK: Njemačka klasifikacija opasnosti za vodu.

Ethyl acetate

Substance identification

Chemical Name: Ethyl acetate

CAS number: 141-78-6

ETHYL ACETATE

ES 1: Cosmetics, personal care products (PC39); User for consumers (SU21).

ES 2: Filling of drums and small packages (CS6); INDUSTRIAL USES (SU3).

ES 3: Formulation or repackaging (F); INDUSTRIAL USES (SU3).

ES 4: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4); Industrial uses (su3); Extraction agents (PC40).

ES 5: PROFESSIONAL APPLICATION OF COATINGS AND INKS; INDUSTRIAL USES (SU3).

ES 6: Use as laboratory reagent (PROC15); Industrial uses (su3); Industrial use.

ES 7: Use in cleaning products (GEST4_I, GEST4_P, GEST4_C); INDUSTRIAL USES (SU3).

ES 8: Use in lubricants (GEST6_I, GEST6_P, GEST6_C); INDUSTRIAL USES (SU3).

ES 9: Professional application of coatings and inks (14); INDUSTRIAL USES (SU3). Covers use in coatings (paints, inks, adhesives, etc.) including exposures during use (receipt of material, storage, preparation and transfer of bulk and semi-bulk products, application by spray, roller or spreader, dipping, flow, fluidized bed on production lines and film formation), the cleaning and maintenance of the equipment and the associated laboratory activities [GES3_I].

ES 10: Use as laboratory reagent (PROC15); Industrial uses (su3); Professional (G27).

ES 11: Use in agrochemical products (GEST11_P, GEST11_C); INDUSTRIAL USES (SU3).

ES 12: Use in detergent products (GEST4_I, GEST4_P, GEST4_C).

ES 13: Use in lubricants (GEST6_I, GEST6_P, GEST6_C)

ES 14: Adhesives, Sealants (PC1); Use in coatings (GEST3_I, GEST3_P, GEST3_C).

ES 5: PROFESSIONAL APPLICATION OF COATINGS AND INKS (17); INDUSTRIAL USES (SU3).

5.1. USE AT INDUSTRIAL SITES

Environment

SC 1: Use of non-reactive processing aid at industrial site (no inclusion in article) ERC4

Worker

SC 2: Generalized exposures (closed systems) PROC1

SC 3: Generalized exposures (closed systems); Use in closed systems, with sample taking PROC2

SC 4: Film formation - forced drying (50 -100°C). Stove (>100°C), Curing by UV/EB radiation PROC2

SC 5: Mixing operations, Generalized exposures PROC3

SC 6: Film formation, air drying PROC4

SC 7: Preparation of material for application, Mixing operations (open systems) PROC5

SC 8: Spraying (automatic/robotic) PROC7

SC 9: Manual spraying PROC7

SC 10: Material transfers, Non-Specialized site PROC8a

SC 11: Material transfers, Specialized site PROC8b

SC 12: Roller, diffusion, flow application PROC10

SC 13: Immersion, dipping and pouring PROC13

SC 14: Laboratory activities PROC15

SC 15: Material transfers, Drum/batch transfers, Transfer from/pour from containers PROC9

SC 16: Production or preparation of articles by tableting, compression, extrusion or pelettisation. PROC14

5.2. CONDITIONS OF USE THAT AFFECT EXPOSURE

5.2.1 Environmental exposure control: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4)

Amount used (or contained in articles), frequency and duration of use/exposure

Daily amount per site: ≤ 1 t/day

Annual amount per site: ≤ 300 t/year

Organizational and technical measures and conditions

A wastewater treatment plant is expected.

Assumed domestic sewage treatment plant flow: ≥ 2E³ m³/day.

Conditions and measures for waste treatment (including the article of waste)

Waste treatment: Dispose of waste products or used containers according to local regulations.

Other conditions affecting environmental exposure

Water flow on the receiving surface: 18,000 m³/day.

5.2.2. Worker Exposure Control: Chemical production or refinement in closed processes without likelihood of exposure or in processes with equivalent containment conditions (PROC1)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.3. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.4. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.5. Worker Exposure Control: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.6. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.7. Worker Exposure Control: Mixing or blending in batch processes (PROC5)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.8. Worker Exposure Control: Industrial spraying (PROC7)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 95%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.9. Worker Exposure Control: Industrial spraying (PROC7)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 95%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.10. Worker Exposure Control: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.11. Worker Exposure Control: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 95%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.12. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.13. Worker Exposure Control: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.14. Worker Exposure Control: Use as laboratory reagents (PROC15)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.15. Worker Exposure Control: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.16. Worker Exposure Control: Tableting, compression, extrusion, pelletising, granulation (PROC14)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

5.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4)

Route release	Release rate	Method for estimating for release
water	20 kg/day	Estimated release factor
air	980 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Estimated exposure	RCR
Fresh water	0.119 mg/l (EUSES v2.1)	0,495
freshwater sediments	0.708 mg/kg dry weight (EUSES v2.1)	0,616
Sea water	0.012 mg/l (EUSES v2.1)	0,495
Marine sediment	0.071 mg/kg dry weight (EUSES v2.1)	0,617
Sewage treatment plant	1.184 mg/l (EUSES v2.1)	< 0.01
Farmland	0.081 mg/kg dry weight (EUSES v2.1)	0,547
Prey for predators (freshwater)	1.469 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for predators (marine water)	0.148 mg/kg dry weight (EUSES v2.1)	< 0.01
Main predator prey (marine water)	0.031 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for Predators (Terrestrial)	0.028 mg/kg dry weight (EUSES v2.1)	< 0.01

5.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	0.037 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	systemic	Short term	0.147 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	local	Long-term	0.037 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	local	Short term	0.147 mg/m ³ (ECETOC TRA worker v3)	< 0.01
dermal	systemic	Long-term	0.034 mg/kg p.c./day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	< 0.01

5.3.3. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	361.7 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	361.7 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	1.37 mg/kg p.c./day (ECETOC TRA worker v3)	0.022
combined routes	systemic	Long-term	/	0.147

5.3.4. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	361.7 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	361.7 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	1.37 mg/kg p.c./day (ECETOC TRA worker v3)	0.022
combined routes	systemic	Long-term	/	0.147

5.3.5. Worker exposure: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	0.69 mg/kg p.c./day (ECETOC TRA worker v3)	0.011
combined routes	systemic	Long-term	/	0.261

5.3.6. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	36.71 mg/m ³ (ECETOC TRA worker v3)	0.05
inhalation	systemic	Short term	146.8 mg/m ³ (ECETOC TRA worker v3)	0.1
inhalation	local	Long-term	36.71 mg/m ³ (ECETOC TRA worker v3)	0.05
inhalation	local	Short term	146.8 mg/m ³ (ECETOC TRA worker v3)	0.1
dermal	systemic	Long-term	6.86 mg/kg p.c./day (ECETOC TRA worker v3)	0.109
combined routes	systemic	Long-term	/	0.159

5.3.7. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.343

5.3.8. Worker exposure: Industrial spraying (PROC7)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	42.86 mg/kg p.c./day (ECETOC TRA worker v3)	0.68
combined routes	systemic	Long-term	/	0.805

5.3.9. Worker exposure: Industrial spraying (PROC7)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	42.86 mg/kg p.c./day (ECETOC TRA worker v3)	0.68
combined routes	systemic	Long-term	/	0.805

5.3.10. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.343

5.3.11. Worker exposure: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	27.53 mg/m ³ (ECETOC TRA worker v3)	0,038
inhalation	systemic	Short term	110.1 mg/m ³ (ECETOC TRA worker v3)	0,075
inhalation	local	Long-term	27.53 mg/m ³ (ECETOC TRA worker v3)	0,038
inhalation	local	Short term	110.1 mg/m ³ (ECETOC TRA worker v3)	0,075
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.255

5.3.12. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	27.43 mg/kg p.c./day (ECETOC TRA worker v3)	0.435
combined routes	systemic	Long-term	/	0.56

5.3.13. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.343

5.3.14. Worker exposure: Use as laboratory reagents (PROC15)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	0.34 mg/kg p.c./day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	0.255

5.3.15. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	73.42 mg/m ³ (ECETOC TRA worker v3)	0.1
inhalation	systemic	Short term	293.6 mg/m ³ (ECETOC TRA worker v3)	0.2
inhalation	local	Long-term	73.42 mg/m ³ (ECETOC TRA worker v3)	0.1
inhalation	local	Short term	293.6 mg/m ³ (ECETOC TRA worker v3)	0.2
dermal	systemic	Long-term	6.86 mg/kg p.c./day (ECETOC TRA worker v3)	0.109
combined routes	systemic	Long-term	/	0.209

5.3.16. Worker exposure: Tableting, compression, extrusion, pelletising, granulation (PROC14)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	3.43 mg/kg p.c./day (ECETOC TRA worker v3)	0.054
combined routes	systemic	Long-term	/	0.179

5.4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: <https://echa.europa.eu/>

ES 9: PROFESSIONAL APPLICATION OF COATINGS AND INKS (14); INDUSTRIAL USES (SU3). COVERS USE IN COATINGS (PAINTS, INKS, ADHESIVES, ETC.) INCLUDING EXPOSURES DURING USE (RECEIPT OF MATERIAL, STORAGE, PREPARATION AND TRANSFER OF BULK AND SEMI-BULK PRODUCTS, APPLICATION BY SPRAY, ROLLER OR SPREADER, DIPPING, FLOW, FLUIDIZED BED ON PRODUCTION LINES AND FILM FORMATION), THE CLEANING AND MAINTENANCE OF THE EQUIPMENT AND THE ASSOCIATED LABORATORY ACTIVITIES [GES3_I].

9.1. WIDE DISPERSIVE USE BY PROFESSIONAL WORKERS

Environment

SC 1: Wide dispersive use of non-reactive processing aid (no inclusion into the article, outdoor) ERC8d

Worker

SC 3: Generalized exposures (closed systems) PROC1
SC 4: Filling of equipment from drums and containers PROC2
SC 5: Generalized exposures (closed systems), Use in closed systems PROC2
SC 6: Preparation of material for application, Generalized exposures PROC3
SC 7: Film formation - air drying, Indoor use PROC4
SC 8: Film formation - air drying, Outdoor use PROC4
SC 9: Preparation of material for application, Indoor use PROC5
SC 10: Preparation of material for application, Outdoor use PROC5
SC 11: Material transfers, Drum/batch transfers, Non-Specialized site PROC8a
SC 12: 12 Material Transfers, Drum/batch transfers, specialized site PROC8b
SC 13: Roller, diffusion, flow application, Indoor use PROC10
SC 14: Roller, diffusion, flow application, Outdoor use PROC10
SC 15: Manual spraying, Indoor use PROC11
SC 16: Manual spraying, Outdoor use PROC11
SC 17: Immersion, dipping and pouring, Indoor use PROC13
SC 18: Immersion, dipping and pouring, Outdoor use PROC13
SC 19: Laboratory activities PROC15
SC 20: Hand application - finger paints, crayons, stickers, Indoor use PROC19
SC 21: Hand application - finger paints, crayons, stickers, Outdoor use PROC19

9.2. CONDITIONS OF USE THAT AFFECT EXPOSURE

9.2.1 Environmental exposure control: Wide dispersive use of non-reactive processing aid (no inclusion into the article, outdoor) (ERC8d)

Organizational and technical measures and conditions

A wastewater treatment plant is expected.

Conditions and measures for waste treatment (including the article of waste)

Waste treatment: Dispose of waste products or used containers according to local regulations.

9.2.3. Worker Exposure Control: Chemical production or refinement in closed processes without likelihood of exposure or in processes with equivalent containment conditions (PROC1)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.4. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.5. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.6. Worker Exposure Control: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.7. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.8. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.9. Worker Exposure Control: Mixing or blending in batch processes (PROC5)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.10. Worker Exposure Control: Mixing or blending in batch processes (PROC5)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

9.2.11. Worker Exposure Control: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a) (PROC8b)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.12. Worker Exposure Control: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.13. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.14. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.15. Worker Exposure Control: Non-industrial spray application (PROC11)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.16. Worker Exposure Control: Non-industrial spray application (PROC11)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

9.2.17. Worker Exposure Control: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.18. Worker Exposure Control: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

9.2.19. Worker Exposure Control: Use as laboratory reagents (PROC15)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.20. Worker Exposure Control: Hand-mixing with direct contact and only PPE available (PROC19)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.21. Worker Exposure Control: Hand-mixing with direct contact and only PPE available (PROC19)

Product features (article)

Covers concentrations up to 5 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

9.3.1. Environmental release and exposure: Wide dispersive use of non-reactive processing aid (no inclusion into the article, outdoor) (ERC8d)

Route release	Release rate	Method for estimating for release
water	0.014 kg/day	Estimated release factor
air	980 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Estimated exposure	RCR
Fresh water	0.000396 mg/l (EUSES v2.1)	< 0.01
freshwater sediments	0.00236 mg/kg dry weight (EUSES v2.1)	< 0.01
Sea water	0.0000597 mg/l (EUSES v2.1)	< 0.01
Marine sediment	0.000356 mg/kg dry weight (EUSES v2.1)	< 0.01
Sewage treatment plant	0.000805 mg/l (EUSES v2.1)	< 0.01
Farmland	0.000131 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for predators (freshwater)	0.011 mg/kg wet weight (EUSES v2.1)	< 0.01
Prey for predators (marine water)	0.00167 mg/kg wet weight (EUSES v2.1)	< 0.01
Main predator prey (marine water)	0.00158 mg/kg wet weight (EUSES v2.1)	< 0.01
Prey for Predators (Terrestrial)	0.000114 mg/kg wet weight (EUSES v2.1)	< 0.01

9.3.3. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	0.367 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	systemic	Short term	1.468 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	local	Long-term	0.367 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	local	Short term	1.468 mg/m ³ (ECETOC TRA worker v3)	< 0.01
dermal	systemic	Long-term	0.034 mg/kg p.c./day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	< 0.01

9.3.4. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	1.37 mg/kg p.c./day (ECETOC TRA worker v3)	0.022
combined routes	systemic	Long-term	/	0.272

9.3.5. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	1.37 mg/kg p.c./day (ECETOC TRA worker v3)	0.022
combined routes	systemic	Long-term	/	0.272

9.3.6. Worker exposure: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	0.69 mg/kg p.c./day (ECETOC TRA worker v3)	0.011
combined routes	systemic	Long-term	/	0.361

9.3.7. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	systemic	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	local	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
dermal	systemic	Long-term	6.86 mg/kg p.c./day (ECETOC TRA worker v3)	0.109
combined routes	systemic	Long-term	/	0.284

9.3.8. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	6.86 mg/kg p.c./day (ECETOC TRA worker v3)	0.109
combined routes	systemic	Long-term	/	0.459

9.3.9. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.568

9.3.10. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	systemic	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	local	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.393

9.3.11. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.568

9.3.12. Worker exposure: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.343

9.3.13. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	27.43 mg/kg p.c./day (ECETOC TRA worker v3)	0.435
combined routes	systemic	Long-term	/	0.785

9.3.14. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	systemic	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	local	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
dermal	systemic	Long-term	27.43 mg/kg p.c./day (ECETOC TRA worker v3)	0.435
combined routes	systemic	Long-term	/	0.61

9.3.15. Worker exposure: Non-industrial spray application (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	308.3 mg/m ³ (ECETOC TRA worker v3)	0.42
inhalation	systemic	Short term	mg/m ³ (ECETOC TRA worker v3)	0.84
inhalation	local	Long-term	308.3 mg/m ³ (ECETOC TRA worker v3)	0.42
inhalation	local	Short term	mg/m ³ (ECETOC TRA worker v3)	0.84
dermal	systemic	Long-term	12.85 mg/kg p.c./day (ECETOC TRA worker v3)	0.204
combined routes	systemic	Long-term	/	0.624

9.3.16. Worker exposure: Non-industrial spray application (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.21
inhalation	systemic	Short term	616.7 mg/m ³ (ECETOC TRA worker v3)	0.42
inhalation	local	Long-term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.21
inhalation	local	Short term	616.7 mg/m ³ (ECETOC TRA worker v3)	0.42
dermal	systemic	Long-term	12.85 mg/kg p.c./day (ECETOC TRA worker v3)	0.204
combined routes	systemic	Long-term	/	0.414

9.3.17. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	systemic	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	local	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
dermal	systemic	Long-term	8.226 mg/kg p.c./day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.356

9.3.18. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	38.54 mg/m ³ (ECETOC TRA worker v3)	0.053
inhalation	systemic	Short term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.105
inhalation	local	Long-term	38.54 mg/m ³ (ECETOC TRA worker v3)	0.053
inhalation	local	Short term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.105
dermal	systemic	Long-term	8.226 mg/kg p.c./day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.183

9.3.19. Worker exposure: Use as laboratory reagents (PROC15)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	0.34 mg/kg p.c./day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	0.255

9.3.20. Worker exposure: Hand-mixing with direct contact and only PPE available (PROC19)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	330.3 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	systemic	Short term	1.32 g/m ³ (ECETOC TRA worker v3)	0.9
inhalation	local	Long-term	330.3 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Short term	1.32 g/m ³ (ECETOC TRA worker v3)	0.9
dermal	systemic	Long-term	16.97 mg/kg p.c./day (ECETOC TRA worker v3)	0.269
combined routes	systemic	Long-term	/	0.72

9.3.21. Worker exposure: Hand-mixing with direct contact and only PPE available (PROC19)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	mg/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	mg/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	5.657 mg/kg p.c./day (ECETOC TRA worker v3)	0.09
combined routes	systemic	Long-term	/	0.44

9.4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: <https://echa.europa.eu/>

ES 12: USE IN DETERGENT PRODUCTS (GEST4_I, GEST4_P, GEST4_C).

12.1. WIDE DISPERSIVE USE BY PROFESSIONAL WORKERS

Environment

SC 1: Wide dispersive use of non-reactive processing aid (no inclusion into the article, indoors) ERC8a

Worker

SC 2: Filling of equipment from drums and containers, specialised site PROC8b

SC 3: Automated process with (semi) closed systems; Use in closed systems PROC2

SC 4: Automated process with (semi) closed systems Drum/batch transfers, Use in closed systems PROC3

SC 5: Semi-automatic process (e.g: Semi-automatic application of floor care and maintenance products) PROC4

SC 6: Filling of equipment from drums and containers, Outdoor use PROC8a

SC 7: Immersion, dipping and pouring, Manual, Surfaces, Cleaning PROC13

SC 8: Cleaning with low-pressure washers, Roller application or brushing, No spraying PROC10

SC 9: Cleaning with high pressure washers, Spraying, Indoor use PROC11

SC 10: Cleaning with high pressure washers Spraying, Outdoor use PROC11

SC 11: Application of cleaning products in closed systems, Manual, Surfaces, Cleaning PROC10

SC 12: Ad hoc manual application via trigger sprays, partial dipping, etc., Roller application or brushing PROC10

SC 13: Application of cleaning products in closed systems, Outdoor use PROC4

SC 14: Cleaning of medical devices PROC4

12.2. CONDITIONS OF USE THAT AFFECT EXPOSURE

12.2.1 Environmental exposure control: Wide dispersive use of non-reactive processing aid (no inclusion into the article, indoors) (ERC8a)

Organizational and technical measures and conditions

A wastewater treatment plant is expected.

Conditions and measures for waste treatment (including the article of waste)

Waste treatment: Dispose of waste products or used containers according to local regulations.

12.2.2. Worker Exposure Control: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.3. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.4. Worker Exposure Control: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.5. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.6. Worker Exposure Control: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

12.2.7. Worker Exposure Control: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.8. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.9. Worker Exposure Control: Non-industrial spray application (PROC11)

Product features (article)

Covers concentrations up to 5 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.10. Worker Exposure Control: Non-industrial spray application (PROC11)

Product features (article)

Covers concentrations up to 1%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

12.2.11. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 5 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.12. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.13. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

12.2.14. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

12.3.1. Environmental release and exposure: Wide dispersive use of non-reactive processing aid (no inclusion into the article, indoors) (ERC8a)

Route release	Release rate	Method for estimating for release
water	0.014 kg/day	Environmental Release Category (ERC)
air	0.014 kg/day	Environmental Release Category (ERC)
Soil	0 kg/day	Environmental Release Category (ERC)

Protection target	Estimated exposure	RCR
Fresh water	0.000397 mg/l (EUSES v2.1)	< 0.01
freshwater sediments	0.00237 mg/kg dry weight (EUSES v2.1)	< 0.01
Sea water	0.0000598 mg/l (EUSES v2.1)	< 0.01
Marine sediment	0.000357 mg/kg dry weight (EUSES v2.1)	< 0.01
Sewage treatment plant	0.000811 mg/l (EUSES v2.1)	< 0.01
Farmland	0.000131 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for predators (freshwater)	0.011 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for predators (marine water)	0.00167 mg/kg dry weight (EUSES v2.1)	< 0.01
Main predator prey (marine water)	0.00158 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for Predators (Terrestrial)	0.000114 mg/kg dry weight (EUSES v2.1)	< 0.01

12.3.2. Worker exposure: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	systemic	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	local	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
dermal	systemic	Long-term	8.226 mg/kg p.c./day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.356

12.3.3. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.15
inhalation	local	Long-term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.15
inhalation	local	Short term	440.5 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	systemic	Short term	440.5 mg/m ³ (ECETOC TRA worker v3)	0.3
dermal	systemic	Long-term	0.822 mg/kg p.c./day (ECETOC TRA worker v3)	0.013
combined routes	systemic	Long-term	/	0.163

12.3.4. Worker exposure: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	systemic	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
inhalation	local	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	local	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
dermal	systemic	Long-term	0.414 mg/kg p.c./day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	0.307

12.3.5. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	systemic	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	local	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
dermal	systemic	Long-term	4.116 mg/kg p.c./day (ECETOC TRA worker v3)	0.065
combined routes	systemic	Long-term	/	0.29

12.3.6. Worker exposure: Transfer of substance or preparation (charging/discharging) at non dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	77.09 mg/m ³ (ECETOC TRA worker v3)	0.105
inhalation	systemic	Short term	308.3 mg/m ³ (ECETOC TRA worker v3)	0.21
inhalation	local	Long-term	77.09 mg/m ³ (ECETOC TRA worker v3)	0.105
inhalation	local	Short term	308.3 mg/m ³ (ECETOC TRA worker v3)	0.21
dermal	systemic	Long-term	8.226 mg/kg p.c./day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.236

12.3.7. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	systemic	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	local	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
dermal	systemic	Long-term	8.226 mg/kg p.c./day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.356

12.3.8. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	330.3 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	systemic	Short term	mg/m ³ (ECETOC TRA worker v3)	0.9
inhalation	local	Long-term	330.3 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Short term	mg/m ³ (ECETOC TRA worker v3)	0.9
dermal	systemic	Long-term	16.45 mg/kg p.c./day (ECETOC TRA worker v3)	0.261
combined routes	systemic	Long-term	/	0.711

12.3.9. Worker exposure: Non-industrial spray application (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	systemic	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
inhalation	local	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	local	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
dermal	systemic	Long-term	21.42 mg/kg p.c./day (ECETOC TRA worker v3)	0.34
combined routes	systemic	Long-term	/	0.64

12.3.10. Worker exposure: Non-industrial spray application (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	2.143 mg/kg p.c./day (ECETOC TRA worker v3)	0.034
combined routes	systemic	Long-term	/	0.384

12.3.11. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	5.486 mg/kg p.c./day (ECETOC TRA worker v3)	0.087
combined routes	systemic	Long-term	/	0.437

12.3.12. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	systemic	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
inhalation	local	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	local	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
dermal	systemic	Long-term	16.45 mg/kg p.c./day (ECETOC TRA worker v3)	0.261
combined routes	systemic	Long-term	/	0.561

12.3.13. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	38.54 mg/m ³ (ECETOC TRA worker v3)	0.053
inhalation	systemic	Short term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.105
inhalation	local	Long-term	38.54 mg/m ³ (ECETOC TRA worker v3)	0.053
inhalation	local	Short term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.105
dermal	systemic	Long-term	4.116 mg/kg p.c./day (ECETOC TRA worker v3)	0.065
combined routes	systemic	Long-term	/	0.118

12.3.14. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.15
inhalation	systemic	Short term	440.5 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	local	Long-term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.15
inhalation	local	Short term	440.5 mg/m ³ (ECETOC TRA worker v3)	0.3
dermal	systemic	Long-term	4.116 mg/kg p.c./day (ECETOC TRA worker v3)	0.065
combined routes	systemic	Long-term	/	0.215

12.4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: <https://echa.europa.eu/>

n-butyl acetate

Substance identification

Chemical Name: n-butyl acetate

CAS number: 123-86-4

Date - Version: 07/06/2017 10.0

1. USE IN COATINGS. USE IN PAINTS. USE IN PRINTING INKS. USE IN ADHESIVES.

Short title of the exposure scenario: Use in coatings. Use in paints. Use in printing inks. Use in adhesives.

SU3; ERC4; PROC7, PROC10, PROC13

EXPOSURE CONTROL AND RISK MANAGEMENT MEASURES

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: CEPE SPERC4.1a.v1

Operating conditions

Yearly amount used in EU: 5,000,000 kgs

Minimum emission days per year: 225

Emission factor to air: 0.8%

Emission factor in water: 2%

Emission factor in soil: 0%

Receiving surface water (flow rate): 18,000 m³/day

Freshwater dilution factor: 10

Marine water dilution factor: 100

Risk management measures

Suitable measures to reduce emissions to air can be: Exhaust gas treatment with thermal oxidation.

Type of treatment plant: Municipal sewage treatment plant.

Assumed sewage treatment plant flow: 2,000 m³/day

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Environment

Risk Characterization Ratio (RCR): 0.925355

Risk from environmental exposure is driven by soil.

Maximum safe use amount: 1080.7 kg/day

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC7: Industrial spray application

Area of use: Industrial

Operating conditions

Substance concentration: n-butyl acetate content: ≥0 - ≤100%

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%
Minimize manual tasks.
Daily general cleaning of equipment and work area.
Regular inspection and maintenance of equipment and machinery.
Ensure that the activity is performed outside the operator's respiratory zone (head-product distance greater than 1m).
Avoid frequent and direct contact with the substance.
Check that risk reduction measures are implemented and that the conditions of use are respected.
Avoid splashes.
Make sure the spray booth is used.
Wear suitable clothing.

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.
Exposure estimation: 4.2857 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.38961
Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.
Exposure estimation: 0.0001 mg/m³
Risk Characterization Ratio (RCR): 0.000001

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra> Please note that a revised version was used (see exposure estimates).

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC10: Application with rollers or brushes

Area of use: Industrial

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 100\%$
Physical state: liquid
Vapor pressure of the substance during use: 1120Pa
Process temperature: 20°C
Duration and frequency of application: 480 mins. 5 days a week
Indoor/Outdoor: Internal use

Risk management measures

Forced local ventilation. Effectiveness: 90%
Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.
Exposure estimation: 2.7429 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.249351
Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.
Exposure estimation: 24.1996 mg/m³
Risk Characterization Ratio (RCR): 0.080665

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC13: Treatment of articles by dipping and pouring

Area of use: Industrial

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 100\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Forced local ventilation. Effectiveness: 90%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 1.3714 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.124675

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 24.1996 mg/m³

Risk Characterization Ratio (RCR): 0.080665

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

2. USE IN COATINGS. USE IN PAINTS. USE IN PRINTING INKS. USE IN ADHESIVES.

Short title of the exposure scenario: Use in coatings. Use in paints. Use in printing inks. Use in adhesives.
SU3; ERC4; PROC7, PROC10, PROC13

EXPOSURE CONTROL AND RISK MANAGEMENT MEASURES

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: CEPE SPERC4.1a.v1

Operating conditions

Yearly amount used in EU: 43,000,000 kgs

Minimum emission days per year: 225

Emission factor to air: 0.8%

Emission factor in water: 2%

Emission factor in soil: 0%

Receiving surface water (flow rate): 18,000 m³/day

Freshwater dilution factor: 10

Marine water dilution factor: 100

Risk management measures

Suitable measures to reduce emissions to air can be: Exhaust gas treatment with thermal oxidation.

Type of treatment plant: Municipal sewage treatment plant.

Assumed sewage treatment plant flow: 2,000 m³/day

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Environment

Risk Characterization Ratio (RCR): 0.925355

Risk from environmental exposure is driven by soil.

Maximum safe use amount: 1080.7 kg/day

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC7: Industrial spray application

Area of use: Industrial

Operating conditions

Substance concentration: n-butyl acetate content: ≥0 - ≤100%

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Minimize manual tasks.

Daily general cleaning of equipment and work area.

Regular inspection and maintenance of equipment and machinery.

Ensure that the activity is performed outside the operator's respiratory zone (head-product distance greater than 1m).

Avoid frequent and direct contact with the substance.

Check that risk reduction measures are implemented and that the conditions of use are respected.

Avoid splashes.

Make sure the spray booth is used.

Wear suitable clothing.

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 4.2857 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.38961

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.
Exposure estimation: 0.0001 mg/m³
Risk Characterization Ratio (RCR): 0.000001

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra> Please note that a revised version was used (see exposure estimates).

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC10: Application with rollers or brushes

Area of use: Industrial

Operating conditions

Substance concentration: n-butyl acetate content: ≥0 - ≤100%

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Forced local ventilation. Effectiveness: 90%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 2.7429 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.249351

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 24.1996 mg/m³

Risk Characterization Ratio (RCR): 0.080665

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC13: Treatment of articles by dipping and pouring

Area of use: Industrial

Operating conditions

Substance concentration: n-butyl acetate content: ≥0 - ≤100%

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Forced local ventilation. Effectiveness: 90%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 1.3714 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.124675

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 24.1996 mg/m³

Risk Characterization Ratio (RCR): 0.080665

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

3. USE IN COATINGS. USE IN PAINTS. USE IN PRINTING INKS. USE IN ADHESIVES.

Short title of the exposure scenario: Use in coatings. Use in paints. Use in printing inks. Use in adhesives.
SU22; ERC8a, ERC8d; PROC10, PROC11, PROC13, PROC19

EXPOSURE CONTROL AND RISK MANAGEMENT MEASURES

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: CEPE SPERC 8a.2a.v1

Operating conditions

Yearly amount used in EU: 2,000,000 kgs

Minimum emission days per year: 225

Emission factor to air: 99%

Emission factor in water: 1%

Emission factor in soil: 0%

Receiving surface water (flow rate): 18,000 m³/day

Freshwater dilution factor: 10

Marine water dilution factor: 100

Risk management measures

The wastewater treatment measures considered suitable are, for example, wastewater or sewage treatment plant.

Type of treatment plant: Municipal sewage treatment plant.

Assumed sewage treatment plant flow: 2,000 m³/day

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Environment

Risk Characterization Ratio (RCR): 0.012923

Risk from environmental exposure is driven by freshwater sediment.

Maximum safe use amount: 1934.6 kg/giorno

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: CEPE SPERC 8d.3a.v1

Operating conditions

Yearly amount used in EU: 2,000,000 kgs

Minimum emission days per year: 225

Emission factor to air: 98%

Emission factor in water: 2%

Emission factor in soil: 0%

Receiving surface water (flow rate): 18,000 m³/day

Freshwater dilution factor: 10

Marine water dilution factor: 100

Risk management measures

Type of treatment plant: Municipal sewage treatment plant.

Assumed sewage treatment plant flow: 2,000 m³/day

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Environment

Risk Characterization Ratio (RCR): 0.092422

Risk from environmental exposure is driven by soil.

Maximum safe use amount: 1082 kg/day

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC10: Application with rollers or brushes

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 100\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour). Effectiveness: 70%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 2.7429 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.249351

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 145.1979 mg/m³

Risk Characterization Ratio (RCR): 0.483993

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC11: Non-industrial spray application

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 45\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Minimize manual tasks.

Daily general cleaning of equipment and work area.

Regular inspection and maintenance of equipment and machinery.

Ensure that the activity is performed outside the operator's respiratory zone (head-product distance greater than 1m).

Avoid frequent and direct contact with the substance.

Check that risk reduction measures are implemented and that the conditions of use are respected.

Avoid splashes.

Make sure the spray booth is used.

Wear suitable clothing.

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 10.7143 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.974026

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 0.0001 mg/m³

Risk Characterization Ratio (RCR): 0.000001

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra> Please note that a revised version was used (see exposure estimates).

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC11: Non-industrial spray application

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 45\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Minimize manual tasks.

Avoid frequent and direct contact with the substance.

Check that risk reduction measures are implemented and that the conditions of use are respected.

Daily general cleaning of equipment and work area.

Regular control and maintenance of equipment and machinery.

Make sure doors and windows are open (general ventilation).

Avoid splashes.

Use an adequately effective local ventilation system.

Wear suitable clothing.

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker, modified version. The concentration of the substance has been considered using a linear approach. Worker - dermal, long-term - systemic.

Exposure estimation: 4.8214 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.438312

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker, modified version. Operator - inhalation, long-term - local.

Exposure estimation: 153 mg/m³

Risk Characterization Ratio (RCR): 0.51

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra> Please note that a revised version was used (see exposure estimates).

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC11: Non-industrial spray application

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 100\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Minimize manual tasks.

Avoid frequent and direct contact with the substance.

Check that risk reduction measures are implemented and that the conditions of use are respected.

Daily general cleaning of equipment and work area.

Regular inspection and maintenance of equipment and machinery.

Avoid splashes.

Make sure doors and windows are open (general ventilation).

Wear a half face mask with a P2L filter or better.

Wear suitable clothing.

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker, modified version. The concentration of the substance has been considered using a linear approach. Worker - dermal, long-term - systemic.

Exposure estimation: 4.8214 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.438312

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker, modified version. Operator - inhalation, long-term - local.

Exposure estimation: 116 mg/m³

Risk Characterization Ratio (RCR): 0.386667

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra> Please note that a revised version was used (see exposure estimates).

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC13: Treatment of articles by dipping and pouring

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 100\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour). Effectiveness: 70%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 1.3714 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.124675

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 145.1979 mg/m³

Risk Characterization Ratio (RCR): 0.483993

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC19: Manual mixing with direct contact with the only use of personal protective equipment

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 100\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 240 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Forced local ventilation: Effectiveness: 80%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Ensure a good standard of general or controlled ventilation (no less than 3-5 air changes per hour). Effectiveness: 30%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 8.4857 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.771429

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 67.759 mg/m³

Risk Characterization Ratio (RCR): 0.225863

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC19: Manual mixing with direct contact with the only use of personal protective equipment

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 100\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 60 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour). Effectiveness: 70%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 2.8286 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.257143

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 145.1979 mg/m³

Risk Characterization Ratio (RCR): 0.483993

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>