ODJELJAK 1.: Identifikacija tvari/smjese i podaci o društvu/poduzeću

1.1. Identifikacijska oznaka proizvoda

Identifikacija preparata:

Trgovačko ime: FASSA EPOXY 100 COMP.A

Trgovački kod: 1222

UFI: 2HEW-9ARA-R00F-6AVC

1.2. Utvrđene relevantne uporabe tvari ili smjese i uporabe koje se ne preporučuju

Preporučana upotreba: Epoksidna podloga za FRP sustave; Samo za stručno upotrebljavanje

Nepreporučljiva upotreba: Nije namijenjeno potrošačima

1.3. Podaci o dobavljaču koji isporučuje sigurnosno-tehnički list

Tvrtka: FASSA Srl

Via Lazzaris, 3 - 31027 Spresiano (TV) - ITALY

Tel. +39 0422 7222

Fax +39 0422 887509

Odgovorna osoba: laboratorio.spresiano@fassabortolo.it

1.4. Broj telefona za izvanredna stanja

+3851 2348 342

ODJELJAK 2.: Identifikacija opasnosti



2.1. Razvrstavanje tvari ili smjese

Uredba (EC) br. 1272/2008 (CLP)

Skin Corr. 1C	Uzrokuje teške opekline kože i ozljede oka.
Skin Sens. 1A	Može izazvati alergijsku reakciju na koži.
Repr. 1B	Može štetno djelovati na plodnost ili naškoditi nerođenom djetetu ako dođe u dodir s kožom ili se proguta.
Aquatic Chronic 2	Otrovno za vodeni okoliš s dugotrajnim učincima.

Fizikalno-kemijski učinci štetni po ljudsko zdravlje i okoliš:

Nema ostalih rizika

2.2. Elementi označivanja

Uredba (EC) br. 1272/2008 (CLP):

Piktogrami i oznaka opasnosti



Opasnost

Oznake upozorenja

H314	Uzrokuje teške opekline kože i ozljede oka.
H317	Može izazvati alergijsku reakciju na koži.
H360	Može štetno djelovati na plodnost ili naškoditi nerođenom djetetu ako dođe u dodir s kožom ili se proguta.
H411	Otrovno za vodeni okoliš s dugotrajnim učincima.

Oznake obavijesti

P201	Prije uporabe pribaviti posebne upute.
P260	Nemojte udisati dimove/plinove/maglicu/pare/aerosole.
P280	Nositi zaštitne rukavice/zaštitno odijelo te zaštitu za oči/zaštitu za lice.
P303+P361+P353	U SLUČAJU DODIRA S KOŽOM (ili kosom): odmah skinuti svu zagađenu odjeću. Isprati kožu vodom [ili tuširanjem].
P305+P351+P338	U SLUČAJU DODIRA S OČIMA: oprezno ispirati vodom nekoliko minuta. Ukloniti kontaktne leće ako ih nosite i ako se one lako uklanjaju. Nastaviti ispirati.

P310 Odmah nazvati CENTAR ZA KONTROLU OTROVANJA/liječnika.

Posebna osiguranja:

EUH205 Sadrži epoksidne sastojke. Može izazvati alergijsku reakciju.

Sadrži:

reakcijska smjesa 2,2'-[metilenbis(4,1-fenilenoksimetilen)]dioksiran i 2-({2-[4-(oksiran-2-ilmetoksi)]fenoksi})oksiran i 2,2'-[metilenbis(2,1-fenilenoksimetilen)]dioksiran

bis[4-(2,3-epoksipropoksi)fenil]propan

1,6-heksandiol diglicidil eter

1,3-propandiol, 2-etil-2-(hidroksimetil)-, polimer s (klormetil)oksiran

Posebne odredbe prema Prilogu XVII REACH-a i naknadnih amandmana:

Niti jedan

2.3. Ostale opasnosti

Bez PBT-a, vPvB-a ili endokrinih disruptora prisutnih u koncentraciji > = 0,1 %.

Nema ostalih rizika

ODJELJAK 3.: Sastav/informacije o sastojcima

3.1. Tvari

Ne primjenjuje se.

3.2. Smjese

Identifikacija preparata: FASSA EPOXY 100 COMP.A

Opasni sastojci u smislu CLP Uredbe koja se odnosi na razvrstavanje:

Količina	Naziv	Ident. Broj.	Klasifikacija	Broj registriranih slučajeva:
≥30 - <50 %	bis[4-(2,3-epoksipropoksi)fenil]propan	CAS:1675-54-3 EC:216-823-5 Index:603-073-00-2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 Specifične granične vrijednosti koncentracije: 5% ≤ C < 100%: Skin Irrit. 2 H315 5% ≤ C < 100%: Eye Irrit. 2 H319	01-2119456619-26-xxxx
≥30 - <50 %	1,6-heksandiol diglicidil eter	CAS:933999-84-9 EC:618-939-5	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1A, H317; Repr. 1B, H360Fd; Aquatic Chronic 3, H412	01-2119463471-41-xxxx
≥10 - <20 %	reakcijska smjesa 2,2'-[metilenbis(4,1-fenilenoksimetilen)]dioksiran i 2-({2-[4-(oksiran-2-ilmetoksi)]fenoksi})oksiran i 2,2'-[metilenbis(2,1-fenilenoksimetilen)]dioksiran	EC:701-263-0	Skin Irrit. 2, H315; Skin Sens. 1A, H317; Aquatic Chronic 2, H411	01-2119454392-40-xxxx
≥5 - <10 %	1,3-propandiol, 2-etil-2-(hidroksimetil)-, polimer s (klormetil)oksiran	CAS:30499-70-8 EC:608-489-8	Skin Corr. 1C, H314; Eye Dam. 1, H318; Skin Sens. 1B, H317; Repr. 1B, H360F; Aquatic Chronic 2, H411	
≥0.005 - <0.025 %	2-metoksi-1-metiletil-acetat	CAS:108-65-6 EC:203-603-9 Index:607-195-00-7	Flam. Liq. 3, H226; STOT SE 3, H336	01-2119475791-29-xxxx

ODJELJAK 4.: Mjere prve pomoći

4.1. Opis mjera prve pomoći

U slučaju kontakta sa kožom:

Smjesta skinuti zagađenu odjeću i ukloniti je na bezbjedan način.

ODMAH NAZVATI MEDICINSKU EKIPU ZA HITNU POMOĆ

U slučaju kontakta sa očima:

U slučaju kontakta sa očima, ispirati oči vodom neko vrijeme, držati otvorene kapke, a potom zatražiti pomoć oftalmologa.

Zaštititi neozlijeđeno oko.

U slučaju gutanja:

Ne poticati povraćanje, obratiti se liječniku i pokazati listić o sigurnosti i oznaku kemijskog rizika.

U slučaju udisanja:

Izloženu osobu treba iznijeti na svježi zrak, držati je na toplom, a ista mora mirovati.

4.2. Najvažniji simptomi i učinci, akutni i odgođeni

Simptomi i ucinci su u skladu s ocekivanjima od opasnosti kako je prikazano u 2. odjeljku.

4.3. Navod o potrebi za hitnom liječničkom pomoći i posebnom obradom

U slučaju nesreće ili slabosti smjesta se obratiti liječniku (ako je moguće, pokazati upute za uporabu ili sigurnosni list).

ODJELJAK 5.: Mjere za suzbijanje požara

5.1. Sredstva za gašenje

Prikladna sredstva za gašenje požara:

CO_2, aparati za gašenje požara prahom, pjena, raspršivanje vode.

Sredstva za gašenje požara koja ne treba koristiti iz bezbijednosnih razloga:

Voda u mlazovima.

5.2. Posebne opasnosti koje proizlaze iz tvari ili smjese

Sagorijevanjem se oslobađaju teški dimovi.

Ne udisati plinove nastale eksplozijom i/ili izgaranjem (ugljikov monoksid i ugljikov dioksid, dušikove okside).

5.3. Savjeti za gasitelje požara

Koristiti prikladne dišne aparate.

Posebno pokupiti zaprljanu vodu, koja je korištena za gašenje požara. Ne bacati ovu vodu u kanalizacionu mrežu.

Neoštećene spremnike skloniti iz prostora neposredne opasnosti, ukoliko se to može izvršiti na bezbjedan način.

ODJELJAK 6.: Mjere kod slučajnog ispuštanja

6.1. Osobne mjere opreza, zaštitna oprema i postupci za izvanredna stanja

Za osobe koje se ne ubrajaju u interventno osoblje:

Koristiti sredstva za osobnu zaštitu.

Ukloniti osobe na sigurno mjesto.

Konzultirati mjere zaštite opisane u točkama 7. i 8.

Za interventno osoblje:

Koristiti sredstva za osobnu zaštitu.

6.2. Mjere zaštite okoliša

Spriječiti prodiranje u tlo/dublje slojeve zemlje. Spriječiti ulivanje u površinske vode ili u kanalizacionu mrežu.

U slučaju izlaska plina ili prodiranja u vodene tokove, tlo ili kanalizacionu mrežu, obavijestiti nadležna tijela.

6.3. Metode i materijal za sprečavanje širenja i čišćenje

Materijal je prikladan za skupljanje: inertni upijajući materijal (npr. pijesak, vermikulit)

Nakon što je proizvod sakupljen, isprati onečišćeno područje i predmete s vodom.

Zadržati vodu kojom ste izvršili pranje, pa je eliminirati.

6.4. Uputa na druge odjeljke

Pogledati također i paragrafe 8. i 13.

ODJELJAK 7.: Rukovanje i skladištenje

7.1. Mjere opreza za sigurno rukovanje

Izbjegavati dodir s kožom i očima, udisanje para i maglica.

Ne koristite prazne spremnike prije no što ih očistite.

Prije prijenosa proizvoda, uvjeriti se da u spremnicima nema ostataka nekompatibilnih tvari.

Savjeti o općoj higijeni na radnom mjestu:

Kontaminirana odjeća se smjesta mora zamijeniti prije ulaska u menze.

Ne konzumirati hranu i piće na radnom mjestu.

Pogledati i paragraf 8. u svezi sa preporučanim napravama za zaštitu.

7.2. Uvjeti sigurnog skladištenja, uzimajući u obzir moguće inkompatibilnosti

Čuvati spremnike dobro zatvorene na hladnom i dobro prozračenom mjestu daleko od izvorā topline.

Držati podalje od hrane, pića i krmiva.

Inkompatibilne tvari:

Vidi točku 10.5

Upute za prostorije za skladištenje:

Adekvatno prozračene prostorije.

7.3. Posebna krajnja uporaba ili uporabe

Preporuke

Vidi točku 1.2

Specifične otopine za industrijski sektor

Nema posebne upotrebe

ODJELJAK 8.: Nadzor nad izloženošću/osobna zaštita

8.1. Nadzorni parametri

Granične vrijednosti izloženosti na mjestu rada

2-metoksi-1-metiletil-acetat

CAS: 108-65-6	OEL Tip	UE		Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 550 mg/m3 - 100 ppm Napomene: Skin
	OEL Tip	MAK	Austrija	Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 550 mg/m3 - 100 ppm Napomene: Skin
	OEL Tip	MAK	Njemačka	Dugoročno 270 mg/m3 - 50 ppm; Kratkoročno 270 mg/m3 - 50 ppm
	OEL Tip	VLEP	Belgija	Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 550 mg/m3 - 100 ppm Napomene: Additional indication "D" means that the absorption of the agent through the skin, mucous membranes or eyes is an important part of the total exposure. It can be the result of both direct contact and its presence in the air.
	OEL Tip	VLEP	Francuska	Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 550 mg/m3 - 100 ppm Napomene: Skin
	OEL Tip	VLEP	Italija	Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 550 mg/m3 - 100 ppm Napomene: Skin
	OEL Tip	VLEP	Rumunjska	Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 550 mg/m3 - 100 ppm
	OEL Tip	TLV	Bugarska	Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 550 mg/m3 - 100 ppm Napomene: Skin
	OEL Tip	TLV	Češka	Dugoročno 270 mg/m3 - 49.14 ppm; Kratkoročno 550 mg/m3 - 10.01 ppm Napomene: Skin
	OEL Tip	VLA	Španjolska	Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 550 mg/m3 - 100 ppm Napomene: Skin
	OEL Tip	ÁK	Mađarska	Dugoročno 275 mg/m3; Kratkoročno 550 mg/m3
	OEL Tip	MAC	Nizozemska	Dugoročno 550 mg/m3 - 100 ppm
	OEL Tip	VLE	Portugal	Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 550 mg/m3 - 100 ppm Napomene: Skin
	OEL Tip	SUVA	Švicarska	Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 275 mg/m3 - 50 ppm
	OEL Tip	WEL	U.K.	Dugoročno 274 mg/m3 - 50 ppm; Kratkoročno 548 mg/m3 - 100 ppm Napomene: Skin
	OEL Tip	GVI	Hrvatska	Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 550 mg/m3 - 100 ppm Napomene: Skin
	OEL Tip	AGW	Njemačka	Dugoročno 270 mg/m3 - 50 ppm; Kratkoročno 270 mg/m3 - 50 ppm
	OEL Tip	NDS	Poljska	Dugoročno 260 mg/m3; Kratkoročno 520 mg/m3 Napomene: Skin
	OEL Tip	MV	Slovenija	Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 550 mg/m3 - 100 ppm Napomene: Skin
	OEL Tip	IPRV	Litva	Dugoročno 250 mg/m3 - 50 ppm; Kratkoročno 400 mg/m3 - 75 ppm Napomene: Skin
	OEL Tip	RV	Latvija	Dugoročno 275 mg/m3 - 50 ppm; Kratkoročno 550 mg/m3 - 100 ppm Napomene: Skin

Granične vrijednosti izloženosti PNEC

bis[4-(2,3-epoksipropoksi)fenil]propan

CAS: 1675-54-3	Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.006 mg/l
	Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.001 mg/l
	Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 0.341 mg/kg
	Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 0.034 mg/kg

Putevi izloženosti: Tlo (poljoprivredno); PNEC Ograničiti: 0.065 mg/kg

Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 10 mg/l

1,6-heksandiol diglicidil eter

CAS: 933999-84-9 Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.011 mg/l

Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.001 mg/l

Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 1 mg/l

Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 0.283 mg/kg

Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 0.028 mg/kg

Putevi izloženosti: Tlo (poljoprivredno); PNEC Ograničiti: 0.223 mg/kg

reakcijska smjesa 2,2'-[metilenbis(4,1-fenilenoksimetilen)]dioksiran i 2-({2-[4-(oksiran-2-ilmetoksi)]fenoksi})oksiran i 2,2'-[metilenbis(2,1-fenilenoksimetilen)]dioksiran

Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.003 mg/l

Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.0003 mg/l

Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 10 mg/l

Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 0.0294 mg/kg

Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 0.294 mg/kg

Putevi izloženosti: Tlo (poljoprivredno); PNEC Ograničiti: 0.237 mg/kg

2-metoksi-1-metiletil-acetat

CAS: 108-65-6 Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.635 mg/l

Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.064 mg/l

Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 100 mg/l

Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 3.29 mg/kg

Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 0.329 mg/kg

Putevi izloženosti: Tlo (poljoprivredno); PNEC Ograničiti: 0.29 mg/kg

Izvedena razina bez učinka. (DNEL)

bis[4-(2,3-epoksipropoksi)fenil]propan

CAS: 1675-54-3 Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci Profesionalni djelatnik: 0.75 mg/kg; Potrošač: 0.089 mg/kg

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci Profesionalni djelatnik: 4.93 mg/m3; Potrošač: 0.87 mg/m3

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Kratkotrajni, sistemski učinci Potrošač: 0.5 mg/kg

1,6-heksandiol diglicidil eter

CAS: 933999-84-9 Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci djelatnik: 10.57 mg/m3; Potrošač: 5.29 mg/m3

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci djelatnik: 6 mg/kg; Potrošač: 3 mg/kg

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Dugotrajni, sistemski učinci Potrošač: 1.5 mg/kg

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Kratkotrajni, sistemski učinci djelatnik: 10.57 mg/m3; Potrošač: 5.29 mg/m3

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Kratkotrajni, sistemski učinci Potrošač: 1.7 mg/kg

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Kratkotrajni, sistemski učinci Potrošač: 1.5 mg/kg

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, lokalni učinci djelatnik: 0.44 mg/m3; Potrošač: 0.27 mg/m3

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, lokalni učinci djelatnik: 0.022 mg/kg; Potrošač: 0.013 mg/kg

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Kratkotrajni, lokalni učinci

djelatnik: 0.022 mg/kg; Potrošač: 0.013 mg/kg

reakcijska smjesa 2,2'-[metilenbis(4,1-fenilenoksimetilen)]dioksiran i 2-({2-[4-(oksiran-2-ilmetoksi)]fenoksi})oksiran i 2,2'-[metilenbis(2,1-fenilenoksimetilen)]dioksiran

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 104.15 mg/kg; Potrošač: 62.5 mg/kg

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Kratkotrajni, lokalni učinci
Profesionalni djelatnik: 0.0083 mg/cm2

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 29.39 mg/m3; Potrošač: 8.7 mg/m3

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Potrošač: 6.25 mg/kg

2-metoksi-1-metiletil-acetat

CAS: 108-65-6 Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci
djelatnik: 796 mg/kg; Potrošač: 320 mg/kg

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Potrošač: 36 mg/kg

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Kratkotrajni, sistemski učinci
Potrošač: 500 mg/kg

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
djelatnik: 275 mg/m3; Potrošač: 33 mg/m3

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Kratkotrajni, lokalni učinci
djelatnik: 550 mg/m3

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, lokalni učinci
Potrošač: 33 mg/m3

8.2. Nadzor nad izloženošću

Osigurati odgovarajuću ventilaciju. Kad je to razumno moguće, to se može postići upotrebom rezervne ventilacije i dobre opće aspiracije.

Zaštita očiju:

Čaše sa bočnom zaštitom (EN 16321).

Zaštita kože:

Upotrebljavati odjeću prikladnu za potpunu zaštitu kože u skladu s aktivnošću i izloženošću (EN 14605/EN 13982), npr. radne kombinezone, pregače, sigurnosnu obuću, prikladnu odjeću.

Zaštita za ruke:

Ne postoji materijal ili kombinacija materijala za rukavice koji bi mogli jamčiti neograničenu otpornost na bilo koji kemijski proizvod ili kombinaciju proizvoda.

Ako je riječ o duljem ili ponavljanom rukovanju, koristite se rukavicama otpornim na kemijske proizvode.

Prikladne rukavice tipa (EN 374/EN 16523); FKM (fluorirana guma): debljina> = 0,4 mm; vrijeme prodiranja> = 480 min. NBR (nitrilna guma): debljina> = 0,4 mm; vrijeme prodiranja> = 480 min

Izbor prikladnih rukavica ne ovisi samo o materijalu, nego i o drugim karakteristikama kvalitete koje se razlikuju od proizvođača do proizvođača, i o načinima i vremenu upotrebe smjese.

Zaštita pri disanju:

Ako su radnici izloženi koncentracijama višima od granice izloženosti, moraju upotrebljavati odgovarajuće certificirane respiratore.

Kombinirana filtrirajuća naprava (EN 14387): maska s filtrom A-P2.

Kontrola izlaganja u okolišu:

Vidi točku 6.2

Higijenske i tehničke mjere

Vidi odlomak 7.

ODJELJAK 9.: Fizikalna i kemijska svojstva

9.1. Informacije o osnovnim fizikalnim i kemijskim svojstvima

fizičko stanje: tekuće

Izgled: tekuće

Boja: bezbojno

Miris: karakterističan

Talište/ledište: N.D.

Vrelište ili početno vrelište i raspon temperatura vrenja: N.D.

Zapaljivost: Ne primjenjuje se.

Donja i gornja granica eksplozivnosti: N.D.

Plamište: Ne primjenjuje se.

Temperatura samozapaljenja: N.D.

Temperatura raspadanja: Ne primjenjuje se.

pH: Ne primjenjuje se.

Kinematička viskoznost: Ne primjenjuje se.

Topljivost u vodi: Ne primjenjuje se.

Topljivost u ulje: Topivo

Koeficijent raspodjele n-oktanol/voda (logaritamska vrijednost): Ne primjenjuje se.

Tlak pare: N.D.

Gustoća i/ili relativna gustoća: 1.12 kg/l (Interna metoda)

Relativna gustoća pare: N.D. Ne primjenjuje se.

Svojstva čestica:

Veličina čestica: Ne primjenjuje se.

9.2. Ostale informacije

Explozivne osobine: Ne primjenjuje se. (Interna evaluacija)

Osobine oksidiranja: Ne primjenjuje se. (Interna evaluacija)

ODJELJAK 10.: Stabilnost i reaktivnost

10.1. Reaktivnost

Stabilan u normalnim uvjetima

10.2. Kemijska stabilnost

Stabilan u normalnim uvjetima

10.3. Mogućnost opasnih reakcija

Može se zapaliti u kontaktu s jakim oksidansima.

Zbog djelovanja topline ili u slučaju požara može doći do oslobađanja ugljikovih oksida i para koji mogu biti štetni za zdravlje.

10.4. Uvjeti koje treba izbjegavati

Čuvati odvojeno od izvorā topline.

10.5. Inkompatibilni materijali

Snažni oksidansi, snažna redukcijska sredstva, alifatski i aromatski amini.

Vidi točku 10.3

10.6. Opasni proizvodi raspadanja

Pri odgovarajućem skladištenju i rukovanju ne razvijaju se opasni proizvodi raspadanja.

Vidi točku 5.2

ODJELJAK 11.: Toksikološke informacije

11.1. Informacije o razredima opasnosti kako su definirani u Uredbi (EZ) br. 1272/2008

Ova tvar sadrži tekuću epoksi smolu koja uzrokuje manju iritaciju kože. Sve epoksi smole mogu uzrokovati osjetljivost kože. Učinci na kožu variraju od osobe do osobe.

Kod osoba koje dolaze u kontakt s tvari, alergijski dermatitis se može pojaviti nakon nekoliko dana ili tjedana učestalog i dugotrajnog kontakta. Zbog toga, i u slučaju da je iritacija kože slaba kontakt se treba izbjegavati.

Kad se jednom pojavi osjetljivost, izlaganje kože vrlo malim količinama može uzrokovati eritrem i edem.

Podaci o toksičnosti proizvoda:

a) akutna toksičnost	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
b) kožno nagrizanje/nadraživanje	Proizvod je razvrstan kao: Skin Corr. 1C(H314)
c) teške očne ozljede/teško očno nadraživanje	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
d) izazivanje kožne ili dišne preosjetljivosti	Proizvod je razvrstan kao: Skin Sens. 1A(H317)
e) mutagenost zametnih stanica	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
f) kancerogenost	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
g) reproduktivna toksičnost	Proizvod je razvrstan kao: Repr. 1B(H360)
h) Specifična toksičnost za ciljne organe (STOT) jednokratno izlaganje	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
i) Specifična toksičnost za ciljne	Nije kategorizirano

organe (STOT) opetovano izlaganje

Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.

j) opasnost u slučaju udisanja Nije kategorizirano

Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.

Podaci o toksičnosti glavnih sastojaka u proizvodu:

bis[4-(2,3-epoksipropoksi)fenil]propan

CAS: 1675-54-3 a) akutna toksičnost LD50 Oralno Štakor > 2000 mg/kg

LD50 Koža Štakor > 2000 mg/kg

1,6-heksandiol diglicidil eter

CAS: 933999-84-9 a) akutna toksičnost LD50 Oralno Štakor 2189 mg/kg

LD50 Koža Štakor > 2000 mg/kg

reakcijska smjesa 2,2'-[metilenbis(4,1-fenilenoksimetilen)]dioksiran i 2-({2-[4-(oksiran-2-ilmetoksi)]fenoksi})oksiran i 2,2'-[metilenbis(2,1-fenilenoksimetilen)]dioksiran

a) akutna toksičnost LD50 Koža Štakor > 2000 mg/kg

LD50 Oralno Štakor > 5000 mg/kg

1,3-propandiol, 2-etil-2-(hidroksimetil)-, polimer s (klormetil)oksiran

CAS: 30499-70-8 a) akutna toksičnost LD50 Oralno Štakor > 2000 mg/kg

LD50 Koža Štakor > 3170 mg/kg

2-metoksi-1-metiletil-acetat

CAS: 108-65-6 a) akutna toksičnost LD50 Oralno Štakor > 5000 mg/kg

LD50 Koža Kunić > 5000 mg/kg

LC0 Udisanje pare Štakor > 4345 ppm 6h

11.2. Informacije o drugim opasnostima

Svojstva endokrine disrupcije:

Bez drugih endokrinih disruptora prisutnih u koncentraciji > = 0,1 %

ODJELJAK 12.: Ekološke informacije

Primjeniti dobre radne postupke da se produkt ne oslobađa u okoliš.

12.1. Toksičnost

Eko-Toksikološke informacije:

Otrovno za vodeni okoliš s dugotrajnim učincima.

Popis eko-toksikoloških svojstava proizvoda

Proizvod je razvrstan kao: Aquatic Chronic 2(H411)

Popis sastojaka sa eko-toksikološkim svojstvima

bis[4-(2,3-epoksipropoksi)fenil]propan

CAS: 1675-54-3 a) Akutna otrovnost na vodene organizme: EC50 Daphnia 1.8 mg/l 48h

a) Akutna otrovnost na vodene organizme: LC50 Ribe 2 mg/l 96h

a) Akutna otrovnost na vodene organizme: EC50 Algae 11 mg/l 72h

b) Hronična otrovnost na vodene organizme: NOEC Daphnia 0.3 mg/l 21d

1,6-heksandiol diglicidil eter

CAS: 933999-84-9 a) Akutna otrovnost na vodene organizme: LC50 Ribe 30 mg/l 96h

a) Akutna otrovnost na vodene organizme: EC50 Daphnia 47 mg/l 48h

reakcijska smjesa 2,2'-[metilenbis(4,1-fenilenoksimetilen)]dioksiran i 2-({2-[4-(oksiran-2-ilmetoksi)]fenoksi})oksiran i 2,2'-[metilenbis(2,1-fenilenoksimetilen)]dioksiran

a) Akutna otrovnost na vodene organizme: LC50 Ribe 2.54 mg/l 96h

a) Akutna otrovnost na vodene organizme: EC50 Algae 1.8 mg/l 72h

a) Akutna otrovnost na vodene organizme: EC50 Daphnia 2.55 mg/l 48h

b) Hronična otrovnost na vodene organizme: NOEC Daphnia 0.3 mg/l - 21d

1,3-propandiol, 2-etil-2-(hidroksimetil)-, polimer s (klormetil)oksiran

CAS: 30499-70-8 a) Akutna otrovnost na vodene organizme: LC50 Ribe 75 mg/l 96h

a) Akutna otrovnost na vodene organizme: EC50 Daphnia 3.7 mg/l 48h

a) Akutna otrovnost na vodene organizme: EC50 Algae 9 mg/l 72h

2-metoksi-1-metiletil-acetat

CAS: 108-65-6 a) Akutna otrovnost na vodene organizme: LC50 Ribe 134 mg/l 96h

a) Akutna otrovnost na vodene organizme: EC50 Daphnia 408 mg/l 48h

a) Akutna otrovnost na vodene organizme: EC50 Algae > 1000 mg/l 96h

b) Hronična otrovnost na vodene organizme: NOEC Ribe 47.5 mg/l - 14 d

12.2. Postojanost i razgradivost

bis[4-(2,3-epoksipropoksi)fenil]propan

CAS: 1675-54-3 Nije brzo-biološki razgradiv

2-metoksi-1-metiletil-acetat

CAS: 108-65-6 Brzo-biološki razgradiv

12.3. Bioakumulacijski potencijal

bis[4-(2,3-epoksipropoksi)fenil]propan

CAS: 1675-54-3 Nije bioakumulativan

12.4. Pokretljivost u tlu

bis[4-(2,3-epoksipropoksi)fenil]propan

CAS: 1675-54-3 Test: Log Koc; Vrijednost: 2.650

12.5. Rezultati procjene svojstava PBT i vPvB

Prema dostupnim podacima proizvod ne sadrži PBT/vPvB u postotku većem ≥ 0.1%.

12.6. Svojstva endokrine disrupcije

Bez drugih endokrinih disruptora prisutnih u koncentraciji > = 0,1 %

12.7. Ostali štetni učinci

Ne primjenjuje se.

ODJELJAK 13.: Zbrinjavanje

13.1. Metode obrade otpada


Regenerirati ako je moguće. Poslati ovlaštenim postrojenjima za odlaganje ili na spaljivanje pod kontroliranim uvjetima. Pri tome se pridržavati vrijedećih lokalnih i državnih regulativa.

Ne dopustiti prodor u kanalizaciju ili vodene tokove.

Zbrinite kontejnera onečišćenih proizvoda u skladu s lokalnim ili nacionalnim zakonskim odredbama.

Proizvod se nakon isteka roka trajanja mora odložiti prema propisima na snazi.

ODJELJAK 14.: Informacije o prijevozu



14.1. UN broj ili identifikacijski broj

1760

14.2. Ispravno otpremno ime prema UN-u

ADR-Naziv za otpremu: KOROZIVNA TEKUĆA TVAR, N.A.S. (1,3-propandiol, 2-etil-2-(hidroksimetil)-, polimer s (klormetil)oksiran - reakcijska smjesa 2,2'-[metilenbis(4,1-fenilenoksimetilen)]dioksiran i 2-({2-[4-(oksiran-2-ilmetoksi)]fenoksi})oksiran i 2,2'-[metilenbis(2,1-fenilenoksimetilen)]dioksiran)

IATA-Naziv za otpremu: CORROSIVE LIQUID, N.O.S. (1,3-propandiol, 2-etil-2-(hidroksimetil)-, polimer s (klormetil)oksiran - reakcijska smjesa 2,2'-[metilenbis(4,1-fenilenoksimetilen)]dioksiran i 2-({2-[4-(oksiran-2-ilmetoksi)]fenoksi})oksiran i 2,2'-[metilenbis(2,1-fenilenoksimetilen)]dioksiran)

IMDG-Naziv za otpremu: CORROSIVE LIQUID, N.O.S. (1,3-propandiol, 2-etil-2-(hidroksimetil)-, polimer s (klormetil)oksiran - reakcijska smjesa 2,2'-[metilenbis(4,1-fenilenoksimetilen)]dioksiran i 2-({2-[4-(oksiran-2-ilmetoksi)]fenoksi})oksiran i 2,2'-[metilenbis(2,1-fenilenoksimetilen)]dioksiran)

14.3. Razred(i) opasnosti pri prijevozu

ADR-Razred: 8

IATA-Razred: 8

IMDG-Razred: 8

14.4. Skupina pakiranja

ADR-Grupa pakiranja: III

IATA-Grupa pakiranja: III

IMDG-Grupa pakiranja: III

14.5. Opasnosti za okoliš

Morski polutant: Da

Zagađivači okoliša: Da

IMDG-EMS: F-A, S-B

14.6. Posebne mjere opreza za korisnika

Ceste i Željeznica (ADR-RID):

ADR-Označavanje: 8

ADR - Identifikacijski broj opasnosti: 80

ADR-Posebne odredbe: 274

ADR ograničenja prijevoza u tunelu:

Zrak (IATA):

IATA-Putnički zrakoplov: 852

IATA-Teretni zrakoplov: 856

IATA-Označavanje: 8

IATA-Sporedni opasnosti: -

IATA-Erg: 8L

IATA-Posebne odredbe: A3 A803

More (IMDG):

IMDG-Skladištenje i rukovanje: Category A SW2

IMDG-Segregacija: -

IMDG-Sporedni opasnosti -

IMDG-Posebne odredbe: 223 274

14.7. Prijevoz morem u razlivenom stanju u skladu s instrumentima IMO-a

Ne primjenjuje se.

ODJELJAK 15.: Informacije o propisima

15.1. Propisi u području sigurnosti, zdravlja i okoliša/posebno zakonodavstvo za tvar ili smjesu

Direktiva 98/24/EC (Rizici koji nastaju od kemijskih agenasa na radu)
Direktiva 2000/39/EC (Granična vrijednost profesionalne izloženosti)
Direktiva 2010/75/EU
Uredba (EC) br. 1907/2006 (REACH)
Uredba (EC) br. 1272/2008 (CLP)
Uredba (EC) br. 790/2009 (ATP 1 CLP) i (EZ) br. 758/2013
Uredba (EZ) br. 2020/878
Uredba (EZ) br. 286/2011 (ATP 2 CLP)
Uredba (EZ) br. 618/2012 (ATP 3 CLP)
Uredba (EZ) br. 487/2013 (ATP 4 CLP)
Uredba (EZ) br. 944/2013 (ATP 5 CLP)
Uredba (EZ) br. 605/2014 (ATP 6 CLP)
Uredba (EZ) br. 2015/1221 (ATP 7 CLP)
Uredba (EZ) br. 2016/918 (ATP 8 CLP)
Uredba (EZ) br. 2016/1179 (ATP 9 CLP)
Uredba (EZ) br. 2017/776 (ATP 10 CLP)
Uredba (EZ) br. 2018/669 (ATP 11 CLP)
Uredba (EZ) br. 2018/1480 (ATP 13 CLP)
Uredba (EZ) br. 2019/521 (ATP 12 CLP)
Uredba (EZ) br. 2020/217 (ATP 14 CLP)
Uredba (EZ) br. 2020/1182 (ATP 15 CLP)
Uredba (EZ) br. 2021/643 (ATP 16 CLP)
Uredba (EZ) br. 2021/849 (ATP 17 CLP)
Uredba (EZ) br. 2022/692 (ATP 18 CLP)
Uredba (EU) no. 2023/707
Uredba (EZ) br. 2023/1434 (ATP 19 CLP)
Uredba (EZ) br. 2023/1435 (ATP 20 CLP)
Uredba (EZ) br. 2024/197 (ATP 21 CLP)
Uredba (EZ) br. 2024/2564 (ATP 22 CLP)
Uredba (EZ) br. 2024/2865
Uredba (EZ) br. 2025/1222 (ATP 23 CLP)

Ograničenja u vezi s produktom ili sadržajnim tvarima u skladu s Prilogom XVII Uredbe (EZ-a) 1907/2006 (REACH) i naknadne izmjene:

Ograničenja koja se odnose na proizvod: 3

Ograničenja koja se odnose na sadržane tvari: 40, 75

Odredbe prema direktivi 2012/18/EU (Seveso III)

Kategorija Seveso III prema dijelu 1. Priloga 1.	Donje granične količine opasnih tvari (u tonama) - male količine	Donje granične količine opasnih tvari (u tonama) - velike količine
proizvod pripada kategoriji: E2	200	500

Uredba (EU) br. 649/2012 (Uredba PIC)

Nijedna tvar nije navedena

Njemačka klasifikacija opasnosti za vodu.

Klasa 3: iznimno opasni.

SVHC tvari:

Prema dostupnim podacima proizvod ne sadrži SVHC u postotku većem ≥ 0.1%.

15.2. Procjena kemijske sigurnosti

Procjena kemijske sigurnosti nije provedena za smjesu. Pogledajte scenarije izloženosti tvari priložene ovom sigurnosnom listu. Kad budete proučavali scenarije, razmotrite i eventualna ograničenja upotrebe navedena u odjeljku 1.2.

ODJELJAK 16.: Ostale informacije

Šifra	Opis
H226	Zapaljiva tekućina i para.
H314	Uzrokuje teške opekline kože i ozljede oka.
H315	Nadražuje kožu.
H317	Može izazvati alergijsku reakciju na koži.
H318	Uzrokuje teške ozljede oka.
H319	Uzrokuje jako nadraživanje oka.
H336	Može izazvati pospanost ili vrtoglavicu.
H360	Može štetno djelovati na plodnost ili naškoditi nerođenom djetetu ako dođe u dodir s kožom ili se proguta.
H360F	Može štetno djelovati na plodnost.
H360Fd	Može štetno djelovati na plodnost. Sumnja se da šteti nerođenom djetetu.
H411	Otrovno za vodeni okoliš s dugotrajnim učincima.
H412	Štetno za vodeni okoliš s dugotrajnim učincima.

Šifra	Razred opasnosti i kategorija opasnosti	Opis
2.6/3	Flam. Liq. 3	Zapaljiva tekućina, kategorija 3
3.2/1C	Skin Corr. 1C	Nagrizajuće za kožu, kategorija 1C
3.2/2	Skin Irrit. 2	Nadražujuće za kožu, kategorija 2
3.3/1	Eye Dam. 1	Teška ozljeda oka, kategorija 1
3.3/2	Eye Irrit. 2	Nadražujuće za oči, kategorija 2
3.4.2/1	Skin Sens. 1	Izazivanje preosjetljivosti kože, kategorija 1
3.4.2/1A	Skin Sens. 1A	Izazivanje preosjetljivosti kože, kategorija 1A
3.4.2/1B	Skin Sens. 1B	Izazivanje preosjetljivosti kože, kategorija 1B
3.7/1B	Repr. 1B	Reproduktivna toksičnost, Kategorija 1B
3.8/3	STOT SE 3	Specifična toksičnost za ciljane organe – jednokratno izlaganje, Kategorija 3
4.1/C2	Aquatic Chronic 2	Kroničnu (dugoročnu) opasnost za organizme koji žive u vodi, kategorija 2
4.1/C3	Aquatic Chronic 3	Kroničnu (dugoročnu) opasnost za organizme koji žive u vodi, kategorija 3

Razvrstavanje i postupak razvrstavanja za smjese sukladno Uredbi (EZ) br. 1272/2008 (CLP):

Razvrstavanje prema Uredbi (EZ) br. 1272/2008	Postupak razvrstavanja
Skin Corr. 1C, H314	Računska metoda
Skin Sens. 1A, H317	Računska metoda
Repr. 1B, H360	Računska metoda
Aquatic Chronic 2, H411	Računska metoda

Ovaj dokument izradila je tehnički kompetentna osoba za SDS, te koja je prikladno za to osposobljena.

Glavni bibliografski izvori:

ECDIN – Informacijska mreža za ekološke podatke za kemikalije – Zajednički istraživački centar, Komisija Europskih zajednica

SAX's OPASNE OSOBINE INDUSTRIJSKIH TVARI- Osmo izdanje - Van Nostrand Reinold

Sigurnosno-tehnički listovi dobavljača sirovina.

Ovdje objavljne informacije se temelje na našem znanju u vrijeme gore navedenog datuma. Odnose se samo na navedene proizvode i ne predstavlja garanciju neke određene kvalitete.

Obaveza je korisnika da utvrdi da je ova informacija cjelovita i da odgovara specifičnoj upotrebi.

Ovaj MSDS poništava i zamjenjuje sva predhodna izdanja.

Legenda kratica i akronima upotrebljenih u sigurnosno-tehničkom listu:

ACGIH: Američka konferencija vladinih specijalista za industrijsku higijenu

ADR: Europski sporazum o međunarodnom cestovnom prijevozu opasnih tvari.

ATE: Procjena akutne toksičnosti

ATEmix: Procijenjena vrijednost akutne toksičnosti (Mješavine)

BEI: Indeks biološke izloženosti

CAS: CAS registarski broj (Američko kemijsko društvo)

CAV: Centar za otrove

CE: Europska zajednica

CLP: Razvrstavanje, označavanje, pakiranje.

CMR: Karcinogeno, Mutageno i Reprotoksično

COV: Hlapivi organski spoj

CSA: Procjena kemijske sigurnosti

CSR: Izvješće o kemijskoj sigurnosti

DNEL: Izvedena razina bez učinka.

EC50: Pulu maksimalna efektivna koncentracija

ECHA: Europska agencija za kemijske proizvode

EINECS: Europski propis postojećih trgovačkih kemijskih tvari.

ES: Scenario izloženosti

GefStoffVO: Propis o opasnim tvarima, Njemačka.

GHS: Globalno harmonizirani sustav razvrstavanja i označavanja kemikalija

IARC: Međunarodna agencija za istraživanja o karcinomu

IATA: Međunarodna udruga za zračni prijevoz.

IC50: Pulu maksimalna koncentracija inhibitora

IMDG: Međunarodni pomorski kodeks opasnog tereta.

LC50: Smrtna koncentracija u 50% slučajeva ispitivane populacije.

LD50: Smrtna doza u 50% slučajeva ispitivane populacije.

LDLo: Niska smrtonosna doza

N.A.: Nije primjenjivo

N/A: Nije primjenjivo

N/D: Nije definirano/Nije dostupno

N.D.: Nije dostupno

NIOSH: Državni institut za zaštitu na radu

NOAEL: Razina bez uočenih štetnih učinaka

OSHA: Upravljanje zaštitom na radu

PBT: Persistentno, bioakumulativno i toksično

PGK: Upute za pakiranje

PNEC: Predviđena koncentracija bez učinka.

PSG: Putnici

RID: Propis o međunarodnom prijevozu opasnih tvari željeznicom

STEL: Granica kratkotrajne izloženosti.

STOT: Toksičnost za ciljani organ.

TLV: Granična vrijednost praga.

TLV-TWA: Granična vrijednost praga za vremenski ponderirani prosjek. (ACGIH standard)

vPvB: Vrlo persistentno, vrlo bioakumulativno

WGK: Njemačka klasifikacija opasnosti za vodu.

Odlomci promijenjeni u odnosu na prethodnu reviziju:

- ODJELJAK 1.: Identifikacija tvari/smjese i podaci o društvu/poduzeću
- ODJELJAK 2.: Identifikacija opasnosti
- ODJELJAK 3.: Sastav/informacije o sastojcima
- ODJELJAK 8.: Nadzor nad izloženošću/osobna zaštita
- ODJELJAK 9.: Fizikalna i kemijska svojstva
- ODJELJAK 11.: Toksikološke informacije
- ODJELJAK 12.: Ekološke informacije

- ODJELJAK 15.: Informacije o propisima
- ODJELJAK 16.: Ostale informacije

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Identifikacija tvari
Kemijski naziv: bis-[4-(2,3-epoxipropoxi)phenyl]propane
CAS broj: 1675-54-3
Datum - verzija: 29/12/2021 - 1.3

INDUSTRIJSKA UPORABA - PROFESIONALNA UPOTREBA: JAVNI SEKTOR (UPRAVA, OBRAZOVANJE, ZABAVA, USLUGE, OBRTNIŠTVO) (SU22).

1. NASLOVNI ODJELJAK

Naziv scenarija izloženosti: industrijska upotreba.
Strukturirani kratki naslov: profesionalna upotreba: javni sektor (uprava, obrazovanje, zabava, usluge, obrtništvo) (SU22).
Tvar: 2,2'-[(1-metiletiliden)bis(4,1-fenilenossimetilen)]bisossirano
EC broj: 216-823-5
Registracijski broj: 01-2119456619-26

OKOLIŠ

SC 1: upotreba nereaktivnih tehnoloških pomoćnih sredstava za obradu na industrijskoj lokaciji (bez uključivanja u artikl) ERC4

RADNIK

SC 2: upotreba kao laboratorijski reagensi PROC15
SC 3: obrada artikala umakanjem i prelijevanjem PROC13
SC 4: sažimanje u pastile, kompresija, ekstruzija, peletizacija, granulacija PROC14
SC 5: mašćenje / opće podmazivanje u uvjetima visoke kinetičke energije PROC18
SC 6 prijenos tvari ili pripravka (punjenje/pražnjenje) iz posuda / velikih spremnika i u njih, u nenamjenskim objektima PROC8a

2. UVJETI UPOTREBE KOJI UTJEČU NA IZLOŽENOST

2.1. NADZOR NAD OKOLIŠNOM IZLOŽENOŠĆU: upotreba nereaktivnih tehnoloških pomoćnih sredstava za obradu na industrijskoj lokaciji (bez uključivanja u artikl) (ERC4)

Obilježja proizvoda (artikla)
Fizički oblik proizvoda: Tekućina

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Dnevna količina po lokaciji: 0,6 tona/dan
Godišnja količina po lokaciji: 20 tona godišnje

Uvjeti i mjere povezani s uređajem za pročišćavanje otpadnih voda
Vrsta STP-a: uređaj za obradu komunalnog otpada.
Ostale informacije o STP-u: biološka eliminacija.
Pročišćavanje mulja u STP-u: može se odložiti na odlagališta ako je to dopušteno lokalnim zakonodavstvom.
Izlazna voda STP-a: 2.000 m³/giorno

Ostali uvjeti koji utječu na okolišnu izloženost
Protok vode na dolaznoj površini: 18.000 m³/dan
otvoreni/zatvoreni prostor: upotreba u zatvorenom prostoru.

2.2. NADZOR NAD IZLOŽENOŠĆU RADNIKA: upotreba kao laboratorijski reagensi (PROC15)

Obilježja proizvoda (artikla)
Obuhvaća udio tvari u proizvodu do 100 %.
Fizički oblik proizvoda: Tekućina.
Temperatura: < 40°C

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Trajanje: obuhvaća dnevna izlaganja do 8 sati.

Tehnički i organizacijski uvjeti i mjere
Pretpostavlja se da se primjenjuju dobri osnovni standardi higijene na radnom mjestu.
Osigurajte dobru razinu opće ventilacije (ne manje od 3 do 5 varijacija zraka na sat).
Kožno: minimalna učinkovitost od 0 %.
Udisanje: minimalni prinos od 30 %.

Uvjeti i mjere koje se odnose na osobnu zaštitu, procjenu higijene i zdravlja
Nosite rukavice otporne na kemikalije (testirane u skladu s normom EN374); trebate biti i odgovarajuće osposobljeni.
Upotrebljavajte odgovarajuću zaštitu za oči.
Kožno: minimalna učinkovitost od 95 %.
Udisanje: minimalni prinos od 0 %.

Ostali uvjeti koji utječu na izloženost radnikā
otvoreni/zatvoreni prostor: na prekrivenom prostoru.
Temperatura: < 40°C

2.3. NADZOR NAD IZLOŽENOŠĆU RADNIKA: obrada artikala umakanjem i prelijevanjem (PROC13)

Obilježja proizvoda (artikla)
Obuhvaća udio tvari u proizvodu do 25 %.
Fizički oblik proizvoda: Tekućina.
Tlak pare: 0,00741 Pa
Temperatura: < 70°C

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Trajanje: obuhvaća dnevna izlaganja do 8 sati.

Tehnički i organizacijski uvjeti i mjere
Pretpostavlja se da se primjenjuju dobri osnovni standardi higijene na radnom mjestu.
Osigurajte dobru razinu opće ventilacije (ne manje od 1 do 3 varijacija zraka na sat).
Kožno: minimalna učinkovitost od 0 %.
Udisanje: minimalni prinos od 0 %.

Uvjeti i mjere koje se odnose na osobnu zaštitu, procjenu higijene i zdravlja
Nosite rukavice otporne na kemikalije (testirane u skladu s normom EN374); trebate biti i odgovarajuće osposobljeni.
Upotrebljavajte odgovarajuću zaštitu za oči.
Kožno: minimalna učinkovitost od 95 %.
Udisanje: minimalni prinos od 0 %.
Nosite odgovarajući respirator.
Udisanje: minimalni prinos od 90 %.

Ostali uvjeti koji utječu na izloženost radnikā
otvoreni/zatvoreni prostor: na prekrivenom prostoru.
Temperatura: < 40°C

2.4. NADZOR NAD IZLOŽENOŠĆU RADNIKA: sažimanje u pastile, kompresija, ekstruzija, peletizacija, granulacija (PROC14)

Obilježja proizvoda (artikla)
Obuhvaća udio tvari u proizvodu do 100 %.
Fizički oblik proizvoda: Tekućina.
Temperatura: < 40°C

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Trajanje: obuhvaća dnevna izlaganja do 8 sati.

Tehnički i organizacijski uvjeti i mjere
Pretpostavlja se da se primjenjuju dobri osnovni standardi higijene na radnom mjestu.
Osigurajte dobru razinu opće ventilacije (ne manje od 3 do 5 varijacija zraka na sat).
Kožno: minimalna učinkovitost od 0 %.
Udisanje: minimalni prinos od 30 %.

Uvjeti i mjere koje se odnose na osobnu zaštitu, procjenu higijene i zdravlja
Nosite rukavice otporne na kemikalije (testirane u skladu s normom EN374); trebate biti i odgovarajuće osposobljeni.
Upotrebljavajte odgovarajuću zaštitu za oči.
Kožno: minimalna učinkovitost od 95 %.
Udisanje: minimalni prinos od 0 %.

Ostali uvjeti koji utječu na izloženost radnikā
otvoreni/zatvoreni prostor: na prekrivenom prostoru.
Temperatura: < 40°C

2.5. NADZOR NAD IZLOŽENOŠĆU RADNIKA: mašćenje / opće podmazivanje u uvjetima visoke kinetičke energije (PROC18)

Obilježja proizvoda (artikla)
Obuhvaća koncentracije do 20 %.
Fizički oblik proizvoda: Tekućina.
Temperatura: ≤ 800°C

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Trajanje: obuhvaća dnevna izlaganja do 8 sati.

Uvjeti i mjere koje se odnose na osobnu zaštitu, procjenu higijene i zdravlja
Nosite rukavice otporne na kemikalije (testirane u skladu s normom EN374); trebate biti i odgovarajuće osposobljeni.
Upotrebljavajte odgovarajuću zaštitu za oči.
Kožno: minimalna učinkovitost od 95 %.
Udisanje: minimalni prinos od 0 %.
Nosite odgovarajući respirator.
Udisanje: minimalni prinos od 90 %.

Ostali uvjeti koji utječu na izloženost radnikā
otvoreni/zatvoreni prostor: na otvorenom.
Industrijska ili profesionalna okruženja: profesionalna upotreba.
Temperatura: ≤ 800°C

2.6. NADZOR NAD IZLOŽENOŠĆU RADNIKA: prijenos tvari ili pripravka (punjenje/pražnjenje) iz posuda / velikih spremnika i u njih, u nenamjenskim objektima (PROC8a)

Obilježja proizvoda (artikla)
Obuhvaća udio tvari u proizvodu do 25 %.
Fizički oblik proizvoda: Tekućina.

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Trajanje: obuhvaća dnevna izlaganja do 8 sati.

Uvjeti i mjere koje se odnose na osobnu zaštitu, procjenu higijene i zdravlja
Nosite rukavice otporne na kemikalije (testirane u skladu s normom EN374); trebate biti i odgovarajuće osposobljeni.
Upotrebljavajte odgovarajuću zaštitu za oči.
Kožno: minimalna učinkovitost od 95 %.
Udisanje: minimalni prinos od 0 %.

Ostali uvjeti koji utječu na izloženost radnikā
otvoreni/zatvoreni prostor: na otvorenom.
Industrijska ili profesionalna okruženja: profesionalna upotreba.
Temperatura: Pretpostavlja se temperatura obrade do < 40 °C.

3. PROCJENA IZLOŽENOSTI I REFERENCA NA NJEZIN IZVOR

3.1. Ispuštanje u okoliš i izloženost: upotreba nereaktivnih tehnoloških pomoćnih sredstava za obradu na industrijskoj lokaciji (bez uključivanja u artikl) (ERC4)

Put ispuštanja	Brzina ispuštanja	Metoda procjene za ispuštanje
slap	1.2E-10kg/giorno	FEICA SPERC 5.1 a.v1
zrak	3E-4kg/dan	FEICA SPERC 5.1 a.v1
Tlo	0%	FEICA SPERC 5.1 a.v1

Cilj zaštite	Procijenjena izloženost (EUSES v2.1)	RCR
Svježa voda	3.76E-4mg/l	0.063
Sedimenti u slatkoj vodi	0.018mg/l	0.053
Morska voda	2.95E-5mg/kg suha težina	0.049
Morski sediment	1.42E-3mg/kg suha težina	0.042
Postrojenje za pročišćavanje otpadnih voda	5.68E-11 mg/l	< 0.01
Poljoprivredno zemljište	2.88E-6mg/kg suha težina	< 0.01
Plijen za grabežljivce (slatka voda)	mg/kg mokre mase (EUSES v2.1)	< 0.01
Plijen za grabežljivce (morska voda)	9.13E-4mg/kg mokro težo	< 0.01
Glavni plijen grabežljivaca (morska voda)	9.13E-4mg/kg mokro težo	< 0.01
Plijen za grabežljivce (na kopnu)	1.68E-4mg/kg mokro težo	< 0.01
Čovjek kroz okoliš – udisanje	7.65E-9mg/m³	< 0.01
Čovjek kroz okoliš – oralni put	3E-5mg/kg tt/dan	< 0.01
Stanovništvo izloženo putem okoliša	-	< 0.01

3.2. Izloženost radnika: upotreba kao laboratorijski reagensi (PROC15)

Putovi izlaganja	Utjecaj na zdravlje	Pokazatelj izloženosti	Procijenjena izloženost (ECETOC TRA radnik v3)	RCR
udisanjem	sustavan	dugoročan	0.993mg/m³	0.201
udisanjem	lokalan	dugoročan	0.993mg/m³	-
udisanjem	lokalan	kratkoročan	0.993mg/m³	-
dermalno	sustavan	dugoročan	0.172mg/kg tt/dan	0.045
dermalno	lokalan	kratkoročan	9.92E-3 mg/cm²	-
kombinirani putovi	-	-	-	0.247

3.3. Izloženost radnika: obrada artikala umakanjem i prelijevanjem (PROC13)

Putovi izlaganja	Utjecaj na zdravlje	Pokazatelj izloženosti	Procijenjena izloženost (ECETOC TRA radnik v3)	RCR
udisanjem	sustavan	dugoročan	0.085mg/m³	0.017
udisanjem	lokalan	dugoročan	0.085mg/m³	-
udisanjem	lokalan	kratkoročan	0.085mg/m³	-
dermalno	sustavan	dugoročan	0.411mg/kg tt/dan	0.548
dermalno	lokalan	kratkoročan	0.06 mg/cm²	-
kombinirani putovi	-	-	-	0.566

3.4. Izloženost radnika: sažimanje u pastile, kompresija, ekstruzija, peletizacija, granulacija (PROC14)

Putovi izlaganja	Utjecaj na zdravlje	Pokazatelj izloženosti	Procijenjena izloženost (ECETOC TRA radnik v3)	RCR
udisanjem	sustavan	dugoročan	0.993mg/m³	0.201
udisanjem	lokalan	dugoročan	0.993mg/m³	-
udisanjem	lokalan	kratkoročan	0.993mg/m³	-
dermalno	sustavan	dugoročan	0.172mg/kg tt/dan	0.229
dermalno	lokalan	kratkoročan	0.0025mg/cm²	-
kombinirani putovi	-	-	-	0.43

3.5. Izloženost radnika: mašćenje / opće podmazivanje u uvjetima visoke kinetičke energije (PROC18)

Putovi izlaganja	Utjecaj na zdravlje	Pokazatelj izloženosti	Procijenjena izloženost (ECETOC TRA radnik v3)	RCR
udisanjem	sustavan	dugoročan	0.596mg/m³	0.121
udisanjem	lokalan	dugoročan	0.596mg/m³	-
udisanjem	lokalan	kratkoročan	0.596mg/m³	-
dermalno	sustavan	dugoročan	0.411mg/kg tt/dan	0.548
dermalno	lokalan	kratkoročan	0.03mg/cm²	-
kombinirani putovi	-	-	-	0.669

3.6. Izloženost radnika: prijenos tvari ili pripravka (punjenje/pražnjenje) u nenamjenskim objektima (PROC8a)

Putovi izlaganja	Utjecaj na zdravlje	Pokazatelj izloženosti	Procijenjena izloženost (ECETOC TRA radnik v3)	RCR
udisanjem	sustavan	dugoročan	0.596mg/m³	0.121
udisanjem	lokalan	dugoročan	0.596mg/m³	-
udisanjem	lokalan	kratkoročan	0.596mg/m³	-
dermalno	sustavan	dugoročan	0.411mg/kg tt/dan	0.548
dermalno	lokalan	kratkoročan	0.03mg/cm²	-
kombinirani putovi	-	-	-	0.669

4. VODIČ ZA DALJNJE KORISNIKE ZA PROCJENU RADE LI U GRANICAMA NAMETNUTIM SCENARIJEM IZLOŽENOSTI

Predviđena izlaganja ne bi smjela prelaziti primjenjive granice izlaganja (navedene u odjeljku 8. sigurnosnog lista) kad su provedeni mjere upravljanja rizikom / radni uvjeti navedeni u odjeljku 2.
Ako se primjenjuju druge mjere upravljanja rizicima / drugi radni uvjeti, korisnici su dužni osigurati da se rizicima upravlja barem na jednakim razinama.
Vodič se temelji na pretpostavljenim radnim uvjetima koji možda nisu primjenjivi na sve lokacije, stoga bi skaliranje moglo biti potrebno za definiranje mjera upravljanja za točan rizik specifičan za lokaciju.

PROFESIONALNA UPOTREBA - PROFESIONALNA UPOTREBA: JAVNI SEKTOR (UPRAVA, OBRAZOVANJE, ZABAVA, USLUGE, OBRTNIŠTVO) (SU22).

1. NASLOVNI ODJELJAK

Naziv scenarija izloženosti: profesionalni.
Strukturirani kratki naslov: profesionalna upotreba: javni sektor (uprava, obrazovanje, zabava, usluge, obrtništvo) (SU22).
Tvar: 2,2'-[(1-metiletiliden)bis(4,1-fenilenossimetilen)]bisossirano
EC broj: 216-823-5
Registracijski broj: 01-2119456619-26

OKOLIŠ

SC 1: upotreba na industrijskoj lokaciji zbog čega dolazi do uključivanja u artikl ERC5

RADNIK

SC 2: industrijsko prskanje PROC7
SC 3 prijenos tvari ili pripravka (punjenje/pražnjenje) iz posuda / velikih spremnika i u njih, u nenamjenskim objektima PROC8a
SC 4: prijenos tvari ili smjese (punjenje/pražnjenje) iz posuda / velikih spremnika i u njih, u namjenskim objektima PROC8b
SC 5: prijenos tvari ili smjese u male spremnike (namjensko punjenje, uključujući vaganje) PROC9
SC 6: nanošenje valjcima ili kistovima PROC10
SC 7: neindustrijsko prskanje PROC11

2. UVJETI UPOTREBE KOJI UTJEČU NA IZLOŽENOST

2.1. NADZOR NAD OKOLIŠNOM IZLOŽENOŠĆU: upotreba na industrijskoj lokaciji zbog čega dolazi do uključivanja u artikl (ERC5)

Obilježja proizvoda (artikla)
Obuhvaća udio tvari u proizvodu do 100 %.
Fizički oblik proizvoda: Tekućina

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Godišnja količina po lokaciji: 30.000 tona godišnje
Dnevna količina po lokaciji: 100 tona/dan

Uvjeti i mjere povezani s uređajem za pročišćavanje otpadnih voda
Vrsta STP-a: uređaj za obradu komunalnog otpada.
Ostale informacije o STP-u: biološka eliminacija.
Pročišćavanje mulja u STP-u: može se odložiti na odlagališta ako je to dopušteno lokalnim zakonodavstvom.
Izlazna voda STP-a: 2.000 m^3/giorno

Ostali uvjeti koji utječu na okolišnu izloženost
Protok vode na dolaznoj površini: 18.000 m^3/dan

2.2. NADZOR NAD IZLOŽENOŠĆU RADNIKA: industrijsko prskanje (PROC7)

Obilježja proizvoda (artikla)
Obuhvaća udio tvari u proizvodu do 25 %.
Fizički oblik proizvoda: Tekućina.
Tlak pare: 0,00741 Pa

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Trajanje: obuhvaća dnevna izlaganja do 8 sati.

Tehnički i organizacijski uvjeti i mjere
Osigurajte dobru razinu opće ventilacije (ne manje od 3 do 5 varijacija zraka na sat).

Uvjeti i mjere koje se odnose na osobnu zaštitu, procjenu higijene i zdravlja
Nosite rukavice otporne na kemikalije (testirane u skladu s normom EN374); trebate biti i odgovarajuće osposobljeni.
Upotrebljavajte odgovarajuću zaštitu za oči.
Ako se očekuje da će se kontaminacija kože proširiti i na druge dijelove tijela, i ti bi dijelovi trebali biti zaštićeni vodootpornom odjećom na način jednak onome opisan za ruke.
Nosite odgovarajući respirator.
Kožno: minimalna učinkovitost od 99 %.
Udisanje: minimalni prinos od 90 %.

Ostali uvjeti koji utječu na izloženost radnikā
otvoreni/zatvoreni prostor: na prekrivenom prostoru.
Industrijska ili profesionalna okruženja profesionalna upotreba.
Temperatura: pretpostavlja se temperatura obrade do 70 °C.

2.3. NADZOR NAD IZLOŽENOŠĆU RADNIKA: prijenos tvari ili pripravka (punjenje/pražnjenje) iz posuda / velikih spremnika i u njih, u nenamjenskim objektima (PROC8a)

Obilježja proizvoda (artikla)
Obuhvaća udio tvari u proizvodu do 25 %.
Fizički oblik proizvoda: Tekućina.
Tlak pare: 0,00741 Pa
Temperatura: 70°C

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Trajanje: obuhvaća dnevna izlaganja do 8 sati.

Tehnički i organizacijski uvjeti i mjere
Osigurajte dobru razinu opće ventilacije (ne manje od 1 do 3 varijacija zraka na sat).
Kožno: minimalna učinkovitost od 0 %.
Udisanje: minimalni prinos od 0 %.

Uvjeti i mjere koje se odnose na osobnu zaštitu, procjenu higijene i zdravlja
Nosite rukavice otporne na kemikalije (testirane u skladu s normom EN374); trebate biti i odgovarajuće osposobljeni.
Upotrebljavajte odgovarajuću zaštitu za oči.
Kožno: minimalna učinkovitost od 95 %.
Udisanje: minimalni prinos od 0 %.

Ostali uvjeti koji utječu na izloženost radnikā
otvoreni/zatvoreni prostor: na prekrivenom prostoru.
Industrijska ili profesionalna okruženja profesionalna upotreba.
Temperatura: 70°C

2.4. NADZOR NAD IZLOŽENOŠĆU RADNIKA: prijenos tvari ili smjese (punjenje/pražnjenje) iz posuda / velikih spremnika i u njih, u namjenskim objektima (PROC8b)

Obilježja proizvoda (artikla)
Obuhvaća udio tvari u proizvodu do 100 %.
Fizički oblik proizvoda: Tekućina.
Tlak pare: 0,00741 Pa
Temperatura: 70°C

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Trajanje: obuhvaća dnevna izlaganja do 8 sati.

Tehnički i organizacijski uvjeti i mjere
Pretpostavlja se da se primjenjuju dobri osnovni standardi higijene na radnom mjestu.
Osigurajte dobru razinu opće ventilacije (ne manje od 1 do 3 varijacija zraka na sat).

Uvjeti i mjere koje se odnose na osobnu zaštitu, procjenu higijene i zdravlja
Nosite rukavice otporne na kemikalije (testirane u skladu s normom EN374); trebate biti i odgovarajuće osposobljeni.
Upotrebljavajte odgovarajuću zaštitu za oči.
Kožno: minimalna učinkovitost od 95 %.
Udisanje: minimalni prinos od 0 %.
Nosite odgovarajući respirator.
Udisanje: minimalni prinos od 90 %.

Ostali uvjeti koji utječu na izloženost radnikā
otvoreni/zatvoreni prostor: na prekrivenom prostoru.
Temperatura: 70°C

2.5. NADZOR NAD IZLOŽENOŠĆU RADNIKA: prijenos tvari ili smjese u male spremnike (namjensko punjenje, uključujući vaganje) (PROC9)

Obilježja proizvoda (artikla)
Obuhvaća koncentracije do 100 %.
Fizički oblik proizvoda: Tekućina.
Tlak pare: 0,00741 Pa
Temperatura: < 50°C

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Trajanje: obuhvaća dnevna izlaganja do 8 sati.

Tehnički i organizacijski uvjeti i mjere
Pretpostavlja se da se primjenjuju dobri osnovni standardi higijene na radnom mjestu.
Osigurajte dobru razinu opće ventilacije (ne manje od 3 do 5 varijacija zraka na sat).
Kožno: minimalna učinkovitost od 0 %.
Udisanje: minimalni prinos od 30 %.

Uvjeti i mjere koje se odnose na osobnu zaštitu, procjenu higijene i zdravlja
Nosite rukavice otporne na kemikalije (testirane u skladu s normom EN374); trebate biti i odgovarajuće osposobljeni.
Upotrebljavajte odgovarajuću zaštitu za oči.
Kožno: minimalna učinkovitost od 95 %.
Udisanje: minimalni prinos od 0 %.
Nosite odgovarajući respirator.
Udisanje: minimalni prinos od 90 %.

Ostali uvjeti koji utječu na izloženost radnikā
otvoreni/zatvoreni prostor: na prekrivenom prostoru.
Temperatura: < 50°C

2.6. NADZOR NAD IZLOŽENOŠĆU RADNIKA: nanošenje valjcima ili kistovima (PROC10)

Obilježja proizvoda (artikla)
Obuhvaća udio tvari u proizvodu do 25 %.
Fizički oblik proizvoda: Tekućina.
Tlak pare: 0,00741 Pa
Temperatura: < 70°C

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Trajanje: obuhvaća dnevna izlaganja do 8 sati.

Tehnički i organizacijski uvjeti i mjere
Pretpostavlja se da se primjenjuju dobri osnovni standardi higijene na radnom mjestu.
Osigurajte dobru razinu opće ventilacije (ne manje od 1 do 3 varijacija zraka na sat).
Lokalna ispušna ventilacija.
Kožno: minimalna učinkovitost od 0 %.
Udisanje: minimalni prinos od 90 %.

Uvjeti i mjere koje se odnose na osobnu zaštitu, procjenu higijene i zdravlja
Nosite rukavice otporne na kemikalije (testirane u skladu s normom EN374); trebate biti i odgovarajuće osposobljeni.
Upotrebljavajte odgovarajuću zaštitu za oči.
Kožno: minimalna učinkovitost od 99 %.
Udisanje: minimalni prinos od 0 %.

Ostali uvjeti koji utječu na izloženost radnikā
otvoreni/zatvoreni prostor: na prekrivenom prostoru.
Temperatura: < 70°C.

2.7. NADZOR NAD IZLOŽENOŠĆU RADNIKA: neindustrijsko prskanje (PROC11)

Obilježja proizvoda (artikla)
Obuhvaća udio tvari u proizvodu do 25 %.
Fizički oblik proizvoda: Tekućina.
Temperatura: < 40°C

Upotrijebljene količine (ili sadržane u artiklu), učestalost i trajanje upotrebe/izlaganja
Trajanje: obuhvaća dnevna izlaganja do 8 sati.

Tehnički i organizacijski uvjeti i mjere
Osigurajte dobru razinu opće ventilacije (ne manje od 3 do 5 varijacija zraka na sat).

Uvjeti i mjere koje se odnose na osobnu zaštitu, procjenu higijene i zdravlja
Nosite rukavice otporne na kemikalije (testirane u skladu s normom EN374); trebate biti i odgovarajuće osposobljeni.
Upotrebljavajte odgovarajuću zaštitu za oči.
Ako se očekuje da će se kontaminacija kože proširiti i na druge dijelove tijela, i ti bi dijelovi trebali biti zaštićeni vodootpornom odjećom na način jednak onome opisan za ruke.
Nosite odgovarajući respirator.
Kožno: minimalna učinkovitost od 99 %.
Udisanje: minimalni prinos od 90 %.

Ostali uvjeti koji utječu na izloženost radnikā
otvoreni/zatvoreni prostor: na prekrivenom prostoru.
Temperatura: < 40°C.

3. PROCJENA IZLOŽENOSTI I REFERENCA NA NJEZIN IZVOR

3.1. Ispuštanje u okoliš i izloženost: upotreba na industrijskoj lokaciji zbog čega dolazi do uključivanja u artikl (ERC5)

Put ispuštanja	Brzina ispuštanja	Metoda procjene za ispuštanje
slap	0,06 kg/dan	FEICA SPERC 8c.1 b.v1
zrak	0 kg/dan	FEICA SPERC 8c.1 b.v1
Tlo	0%	FEICA SPERC 8c.1 b.v1

Cilj zaštite	Procijenjena izloženost (EUSES v2.1)	RCR
Svježa voda	3.22E-3mg/l	0,536
Sedimenti u slatkoj vodi	0.155mg/l	0,454
Morska voda	3.14E-4mg/l	0,523
Morski sediment	0.015mg/kg suha težina	0,442
Postrojenje za pročišćavanje otpadnih voda	0.028mg/l	< 0,01
Poljoprivredno zemljište	0.05mg/kg suha težina	0,779
Plijen za grabežljivce (slatka voda)	0.048mg/kg mokro težo	< 0,01
Plijen za grabežljivce (morska voda)	4.53E-3mg/kg mokro težo	< 0,01
Glavni plijen grabežljivaca (morska voda)	1.64E-3mg/kg mokro težo	< 0,01
Plijen za grabežljivce (na kopnu)	0.056mg/kg mokro težo	< 0,01
Čovjek kroz okoliš – udisanje	Koncentracija u zraku: 3.45E-11 mg/m³	< 0,01
Čovjek kroz okoliš – oralni put	1.47E-3mg/kg tt/dan	< 0,01
Stanovništvo izloženo putem okoliša	-	< 0,01

3.2. Izloženost radnika: industrijsko prskanje (PROC7)

Putovi izlaganja	Utjecaj na zdravlje	Pokazatelj izloženosti	Procijenjena izloženost	RCR
udisanjem	sustavan	dugoročan	0.34mg/m³ (ART v1.5)	0.069
udisanjem	lokalan	dugoročan	0.34mg/m³ (ART v1.5)	-
udisanjem	lokalan	kratkoročan	0.78mg/m³ (ART v1.5)	-
dermalno	sustavan	dugoročan	0.257mg/kg tt/dan (ECETOC TRA radnika v3)	0.343
dermalno	lokalan	kratkoročan	0.012mg/cm² (ECETOC TRA worker v3)	-
kombinirani putovi	-	-	-	0.412

3.3. Izloženost radnika: prijenos tvari ili pripravka (punjenje/pražnjenje) u nenamjenskim objektima (PROC8a)

Putovi izlaganja	Utjecaj na zdravlje	Pokazatelj izloženosti	Procijenjena izloženost (ECETOC TRA radnik v3)	RCR
udisanjem	sustavan	dugoročan	0.851mg/m³	0.173
udisanjem	lokalan	dugoročan	0.851mg/m³	-
udisanjem	lokalan	kratkoročan	0.851mg/m³	-
dermalno	sustavan	dugoročan	0.411mg/kg tt/dan	0.548
dermalno	lokalan	kratkoročan	0.03mg/cm²	-
kombinirani putovi	-	-	-	0.721

3.4. Izloženost radnika: prijenos tvari ili smjese (punjenje/pražnjenje) u namjenskim objektima (PROC8b)

Putovi izlaganja	Utjecaj na zdravlje	Pokazatelj izloženosti	Procijenjena izloženost (ECETOC TRA radnik v3)	RCR
udisanjem	sustavan	dugoročan	0.085mg/m³	0.017
udisanjem	lokalan	dugoročan	0.085mg/m³	-
udisanjem	lokalan	kratkoročan	0.0851mg/m³	-
dermalno	sustavan	dugoročan	0.411mg/kg tt/dan	0.548
dermalno	lokalan	kratkoročan	0.03mg/cm²	-
kombinirani putovi	-	-	-	0.566

3.5. Izloženost radnika: prijenos tvari ili smjese u male spremnike (namjensko punjenje, uključujući vaganje) (PROC9)

Putovi izlaganja	Utjecaj na zdravlje	Pokazatelj izloženosti	Procijenjena izloženost (ECETOC TRA radnik v3)	RCR
udisanjem	sustavan	dugoročan	0.099mg/m³	0.02
udisanjem	lokalan	dugoročan	0.099mg/m³	-
udisanjem	lokalan	kratkoročan	0.993mg/m³	-
dermalno	sustavan	dugoročan	0.343mg/kg tt/dan	0.457
dermalno	lokalan	kratkoročan	0.05mg/cm²	-
kombinirani putovi	-	-	-	0.659

3.6. Izloženost radnika: nanošenje valjcima ili kistovima (PROC10)

Putovi izlaganja	Utjecaj na zdravlje	Pokazatelj izloženosti	Procijenjena izloženost (ECETOC TRA radnik v3)	RCR
udisanjem	sustavan	dugoročan	0.085mg/m³	0.017
udisanjem	lokalan	dugoročan	0.085mg/m³	-
udisanjem	lokalan	kratkoročan	0.085mg/m³	-
dermalno	sustavan	dugoročan	0.165mg/kg tt/dan	0.219
dermalno	lokalan	kratkoročan	0.012mg/cm²	-
kombinirani putovi	-	-	-	0.237

3.7. Izloženost radnika: neindustrijsko prskanje (PROC11)

Putovi izlaganja	Utjecaj na zdravlje	Pokazatelj izloženosti	Procijenjena izloženost	RCR
udisanjem	sustavan	dugoročan	0.34mg/m³ (ART v1 .5)	0.069
udisanjem	lokalan	dugoročan	0.34mg/m³ (ART v1 .5)	-
udisanjem	lokalan	kratkoročan	0.78mg/m³ (ART v1 .5)	-
dermalno	sustavan	dugoročan	0.643mg/kg tt/dan (ECETOC TRA radnika v3)	0.857
dermalno	lokalan	kratkoročan	0.03mg/cm² (ECETOC TRA worker v3)	-
kombinirani putovi	-	-	-	0.926

4. VODIČ ZA DALJNJE KORISNIKE ZA PROCJENU RADE LI U GRANICAMA NAMETNUTIM SCENARIJEM IZLOŽENOSTI

Predviđena izlaganja ne bi smjela prelaziti primjenjive granice izlaganja (navedene u odjeljku 8. sigurnosnog lista) kad su provedeni mjere upravljanja rizikom / radni uvjeti navedeni u odjeljku 2.
Ako se primjenjuju druge mjere upravljanja rizicima / drugi radni uvjeti, korisnici su dužni osigurati da se rizicima upravlja barem na jednakim razinama.
Vodič se temelji na pretpostavljenim radnim uvjetima koji možda nisu primjenjivi na sve lokacije, stoga bi skaliranje moglo biti potrebno za definiranje mjera upravljanja za točan rizik specifičan za lokaciju.

bis-[4-(2,3-epoxipropoxi)phenyl]propane

2-methoxy-1-methylethyl acetate

Substance identification
Chemical Name: 2-methoxy-1-methylethyl acetate
CAS number: 108-65-6
Date - Version: 02/08/2021 18.0

4. USE IN COATINGS. - USE IN INDUSTRIAL PLANTS

Short title of the exposure scenario: Use in coatings. - Use in industrial plants
SU3; ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15

EXPOSURE CONTROL AND RISK MANAGEMENT MEASURES

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: ERC4: Industrial use of processing aids not becoming part of articles.

Operating conditions

Yearly amount used in EU: 63,050,000 kg
Daily amount per site: 105.087 kg
Minimum continuous emission days per year: 300
Emission factor to air: 27%
Emission factor in water: 2%
Emission factor in soil: 0.1%
Releases based on A&B tables from TGD 2003
Freshwater dilution factor: 10
Marine water dilution factor: 100

Risk management measures

Treat air emissions to provide a typical removal efficiency of 70%.
Prevent discharge of undissolved substance, or recover from wastewater.
Type of treatment plant: Municipal sewage treatment plant.
Total removal efficiency of the substance from the wastewater after Risk Management Measures and treatment in the treatment plant (5): 87.3%
Assumed treatment plant flow: 2,000 m³/day

Measures relative to the waste

Dispose of waste cans and containers according to local regulations.

Exposure estimation and reference to its source

Risk Characterization Ratio (RCR): 0.1338
Risk from environmental exposure is driven by freshwater and marine water.
Maximum safe use amount: 79,180 kg/day

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC1: Use in closed process, no likelihood of exposure.

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 0.04 mg/m³
Risk Characterization Ratio (RCR): 0.0001
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 0.34 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.01

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC2: Use in closed, continuous process with occasional controlled exposure. General exposure. Continuous process (closed system) with sample collection.

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 1.37 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.03

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC2: Use in closed, continuous process with occasional controlled exposure. Film formation - Fast drying.

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Operation is carried out at elevated temperature (> 20°C above ambient temperature).

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 187.71 mg/m³
Risk Characterization Ratio (RCR): 0.5
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 1.37 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.03

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC3: Use in batch process (synthesis or formulation). Mixing operations. General exposure (closed system).

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 93.85 mg/m³
Risk Characterization Ratio (RCR): 0.25
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 0.34 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.01

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC4: Use in batch process (synthesis) where opportunity for exposure arises. Film formation - Air drying.

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 75.08 mg/m³
Risk Characterization Ratio (RCR): 0.2
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 6.86 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.14

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC5: Mixing in batch processes for formulation of preparations and articles (multistage and/or significant contact). Preparation of material for application. Mixing operations (open systems).

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 187.71 mg/m³
Risk Characterization Ratio (RCR): 0.51
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 13.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.27

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC7: Industrial spray application. Spraying (automatic/robotic).

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures
Carry out in a vented booth or extracted enclosure. Effectiveness: 95%.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 46.93 mg/m³
Risk Characterization Ratio (RCR): 0.13
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 2.14 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.04

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC7: Industrial spray application. Spraying (manual).

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures
Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Effectiveness: 70%.
Wear suitable gloves compliant with EN ISO 374-1. Effectiveness: 80%.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 281.56 mg/m³
Risk Characterization Ratio (RCR): 0.76
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 8.57 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.17

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities. Material transfers. Non-dedicated system.

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 187.71 mg/m³
Risk Characterization Ratio (RCR): 0.51
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 13.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.27

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. Material transfers. Dedicated plant.

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 187.71 mg/m³
Risk Characterization Ratio (RCR): 0.51
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 6.86 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.14

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Material transfers. Drum/batch transfers. Transfer from containers. Dedicated plant.

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 187.71 mg/m³
Risk Characterization Ratio (RCR): 0.51
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 6.86 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.14

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC10: Application with rollers or brushes. Roller, spatula, jet application.

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures
Wear suitable gloves compliant with EN ISO 374-1. Effectiveness: 80%

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 187.71 mg/m³
Risk Characterization Ratio (RCR): 0.51
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 5.49 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.11

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC13: Treatment of articles by dipping, pouring, enamelling.

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 187.71 mg/m³
Risk Characterization Ratio (RCR): 0.51
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 13.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.27

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC14: Production of preparations or articles by tableting, compression, extrusion or pelletising. Production or preparation of articles by tableting, compression, extrusion.

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 187.71 mg/m³
Risk Characterization Ratio (RCR): 0.51
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 3.43 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.07

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC15: Use as laboratory reagent. Laboratory activities.

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 0.34 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.01

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

5. USE IN COATINGS. - USE IN INDUSTRIAL PLANTS

Short title of the exposure scenario: Use in coatings. - Use in industrial plants
SU3; ERC4; PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15

EXPOSURE CONTROL AND RISK MANAGEMENT MEASURES

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: ERC4: Industrial use of processing aids not becoming part of articles.

Operating conditions

Yearly amount used in EU: 2,600,000 kgs
Daily amount per site: 430kg
Minimum continuous emission days per year: 300
Emission factor to air: 80%
Emission factor in water: 10%
Emission factor in soil: 0.1%
Releases based on A&B tables from TGD 2003
Freshwater dilution factor: 10
Marine water dilution factor: 100

Risk management measures

Prevent discharge of undissolved substance, or recover from wastewater.
Type of treatment plant: Municipal sewage treatment plant.
Total removal efficiency of the substance from the wastewater after Risk Management Measures and treatment in the treatment plant (5): 87.3%
Assumed treatment plant flow: 2,000 m³/day

Measures relative to the waste

Dispose of waste cans and containers according to local regulations.

Exposure estimation and reference to its source

Risk Characterization Ratio (RCR): 0.029
Risk from environmental exposure is driven by freshwater and marine water.
Maximum safe use amount: 140.104 kg/day

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC1: Use in closed process, no likelihood of exposure (closed system). General exposure.

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure.
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC2: Use in closed, continuous process with occasional controlled exposure. General exposure. Continuous process (closed system) with sample collection.

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 7.51 mg/m³
Risk Characterization Ratio (RCR): 0.02
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 1.37 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.03

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC2: Use in closed, continuous process with occasional controlled exposure. Film formation - Fast drying.

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Operation is carried out at elevated temperature (> 20°C above ambient temperature).

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 1.37 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.03

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC3: Use in batch process (synthesis or formulation). Mixing operations. General exposure (closed system).

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 18.77 mg/m³
Risk Characterization Ratio (RCR): 0.05
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 0.34 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.01

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC4: Use in batch process (synthesis) where opportunity for exposure arises. Film formation - Air drying.

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 15.02 mg/m³
Risk Characterization Ratio (RCR): 0.04
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 6.86 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.14

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC5: Mixing in batch processes for formulation of preparations and articles (multistage and/or significant contact). Preparation of material for application. Mixing operations (open systems).

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 13.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.27

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC7: Industrial spray application. Spraying (automatic/robotic). Spraying (manual)

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures

Wear suitable gloves compliant with EN ISO 374-1. Effectiveness: 80%.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 187.71 mg/m³
Risk Characterization Ratio (RCR): 0.51
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 8.57 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.17

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC7: Industrial spray application. Spraying (manual).

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures
Wear suitable gloves compliant with EN ISO 374-1.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities. Material transfers. Non-dedicated system.

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 13.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.27

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. Material transfers. Dedicated plant.

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 6.86 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.14

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Material transfers. Drum/batch transfers. Transfer from containers. Dedicated plant.

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 6.86 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.14

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC10: Application with rollers or brushes. Roller, spatula, jet application.

Area of use: Industrial

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 27.43 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.54

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC13: Treatment of articles by dipping, pouring, enamelling.

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 13.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.27

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC14: Production of preparations or articles by tableting, compression, extrusion or pelletising. Production or preparation of articles by tableting, compression, extrusion.

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 3.43 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.07

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC15: Use as laboratory reagent. Laboratory activities.

Area of use: Industrial

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 7.51 mg/m³
Risk Characterization Ratio (RCR): 0.02
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 0.34 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.01

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

7 USE IN COATINGS. - USE IN INDUSTRIAL PLANTS

Short title of the exposure scenario: Use in coatings. - Use in professional installations
SU22; ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19

EXPOSURE CONTROL AND RISK MANAGEMENT MEASURES

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: ERC8a: Wide dispersive indoor use of processing aids in open systems.

Operating conditions

Yearly amount used in EU: 2,600,000 kgs
Daily amount per site: 433 kg
Minimum continuous emission days per year: 300
Emission factor to air: 80%
Emission factor in water: 10%
Emission factor in soil: 0.1%
Releases based on A&B tables from TGD 2003
Freshwater dilution factor: 10
Marine water dilution factor: 100

Risk management measures

Prevent discharge of undissolved substance, or recover from wastewater.
Type of treatment plant: Municipal sewage treatment plant.
Total removal efficiency of the substance from the wastewater after Risk Management Measures and treatment in the treatment plant (5): 87.3%
Assumed treatment plant flow: 2,000 m³/day

Measures relative to the waste

Dispose of waste cans and containers according to local regulations.

Exposure estimation and reference to its source

Risk Characterization Ratio (RCR): 0.029
Risk from environmental exposure is driven by freshwater and marine water.
Maximum safe use amount: 15,141 kg/day

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: ERC8d: Wide dispersive outdoor use of processing aids in open systems.

Operating conditions

Yearly amount used in EU: 2,600,000 kgs
Daily amount per site: 433 kg
Minimum continuous emission days per year: 300
Emission factor to air: 80%
Emission factor in water: 10%
Emission factor in soil: 0.1%
Releases based on A&B tables from TGD 2003
Freshwater dilution factor: 10
Marine water dilution factor: 100

Risk management measures

Prevent discharge of undissolved substance, or recover from wastewater.
Type of treatment plant: Municipal sewage treatment plant.
Total removal efficiency of the substance from the wastewater after Risk Management Measures and treatment in the treatment plant (5): 87.3%
Assumed treatment plant flow: 2,000 m³/day

Measures relative to the waste
Dispose of waste cans and containers according to local regulations.

Exposure estimation and reference to its source
Risk Characterization Ratio (RCR): 0.029
Risk from environmental exposure is driven by freshwater and marine water.
Maximum safe use amount: 15,141 kg/day

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC1: Use in closed process, no likelihood of exposure.

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 0.04 mg/m³
Risk Characterization Ratio (RCR): 0.0001
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 0.34 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.01

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC2: Use in closed, continuous process with occasional controlled exposure. Filling/Preparation of equipment required for drums and containers.

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure.
The use has been assessed as safe.

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC2: Use in closed, continuous process with occasional controlled exposure. General exposure. Use in confined systems (closed system). Filling/Preparation of equipment required for drums and containers.

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Operation is carried out at elevated temperature (> 20°C above ambient temperature).

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 75.08 mg/m³
Risk Characterization Ratio (RCR): 0.2
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 1.37 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.03

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC3: Use in batch process (synthesis or formulation). Preparation of material for application

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 93.85 mg/m³
Risk Characterization Ratio (RCR): 0.25
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 0.34 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.01

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC4: Use in batch process (synthesis) where opportunity for exposure arises. Film formation - Air drying.

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 187.71 mg/m³
Risk Characterization Ratio (RCR): 0.51
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 6.86 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.14

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC4: Use in batch and other processes (synthesis) where opportunity for exposure arises. Film formation - Air drying.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure.
The use has been assessed as safe.

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC5: Mixing in batch processes for formulation of preparations and articles (multistage and/or significant contact). Preparation of material for application.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Effectiveness: 30%.
Alternatively: Ensure that operations are carried out externally.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 269.79 mg/m³
Risk Characterization Ratio (RCR): 0.71
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 13.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.27

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC5: Mixing in batch processes for formulation of preparations and articles (multistage and/or significant contact). Preparation of material for application.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures
Ensure that operations are carried out externally.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities. Material transfers. Drum/batch transfers. Non-dedicated system.

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Effectiveness: 30%.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 262.79 mg/m³
Risk Characterization Ratio (RCR): 0.71
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 13.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.27

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. Material transfers. Drum/batch transfers Dedicated plant.

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 187.71 mg/m³
Risk Characterization Ratio (RCR): 0.51
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 6.86 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.14

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC10: Application with rollers or brushes. Roller, spatula, jet application.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Effectiveness: 30%.
Wear suitable gloves compliant with EN ISO 374-1. Effectiveness: 80%
If there is no general ventilation, ensure that operations are carried out outdoors.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 262.79 mg/m³
Risk Characterization Ratio (RCR): 0.71
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 5.49 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.11

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC10: Application with rollers or brushes. Roller, spatula, jet application.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures

Ensure that operations are carried out externally.
Wear suitable gloves compliant with EN ISO 374-1.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC11: Non-industrial spray application. Spraying (manual).

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures

Carry out in a vented booth or extracted enclosure. Effectiveness: 80%.
Wear a respirator conforming to EN140 with type A filter or better. Effectiveness: 90%.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 2.14 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.04

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC11: Non-industrial spray application. Spraying (manual).

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures
Ensure that operations are carried out externally. Effectiveness: 30%.
Wear a respirator conforming to EN140 with type A filter or better. Effectiveness: 90%.
Wear suitable gloves compliant with EN ISO 374-1. Effectiveness: 80%.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 131.4 mg/m³
Risk Characterization Ratio (RCR): 0.36
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 21.43 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.42

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC13: Treatment of articles by dipping, pouring, enamelling.

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Effectiveness: 30%.
Alternatively: Ensure that operations are carried out externally.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 262.79 mg/m³
Risk Characterization Ratio (RCR): 0.71
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 13.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.27

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC13: Treatment of articles by dipping, pouring, enamelling.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures

Ensure that operations are carried out externally.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC15: Use as laboratory reagent. Laboratory activities.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 0.34 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.01

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC19: Manual mixing with direct contact using only personal protective equipment. Hand application - fingerpaints, pastels, adhesives.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Effectiveness: 30%.
Wear chemically resistant gloves in combination with “basic” employee training. Effectiveness: 90%.
If there is no general ventilation, ensure that operations are carried out outdoors.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 262.79 mg/m³
Risk Characterization Ratio (RCR): 0.71
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 14.14 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.28

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC19: Manual mixing with direct contact using only personal protective equipment. Hand application - fingerpaints, pastels, adhesives.

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤100%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures
Ensure that operations are carried out externally.
Wear chemically resistant gloves in combination with “basic” employee training.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

8. USE IN COATINGS. - USE IN INDUSTRIAL PLANTS

Short title of the exposure scenario: Use in coatings. - Use in professional installations
SU22; ERC8a, ERC8d; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19

EXPOSURE CONTROL AND RISK MANAGEMENT MEASURES

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: ERC8a: Wide dispersive indoor use of processing aids in open systems.

Operating conditions

Yearly amount used in EU: 2,600,000 kgs
Daily amount per site: 433 kg
Minimum continuous emission days per year: 300
Emission factor to air: 80%
Emission factor in water: 10%
Emission factor in soil: 0.1%
Releases based on A&B tables from TGD 2003
Freshwater dilution factor: 10
Marine water dilution factor: 100

Risk management measures

Prevent discharge of undissolved substance, or recover from wastewater.
Type of treatment plant: Municipal sewage treatment plant.
Total removal efficiency of the substance from the wastewater after Risk Management Measures and treatment in the treatment plant (5): 87.3%
Assumed treatment plant flow: 2,000 m³/day

Measures relative to the waste

Dispose of waste cans and containers according to local regulations.

Exposure estimation and reference to its source

Risk Characterization Ratio (RCR): 0.029
Risk from environmental exposure is driven by freshwater and marine water.
Maximum safe use amount: 15,141 kg/day

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: ERC8d: Wide dispersive outdoor use of processing aids in open systems.

Operating conditions

Yearly amount used in EU: 2,600,000 kgs
Daily amount per site: 433 kg
Minimum continuous emission days per year: 300
Emission factor to air: 80%
Emission factor in water: 10%
Emission factor in soil: 0.1%
Releases based on A&B tables from TGD 2003
Freshwater dilution factor: 10
Marine water dilution factor: 100

Risk management measures

Prevent discharge of undissolved substance, or recover from wastewater.
Type of treatment plant: Municipal sewage treatment plant.
Total removal efficiency of the substance from the wastewater after Risk Management Measures and treatment in the treatment plant (5): 87.3%
Assumed treatment plant flow: 2,000 m³/day

Measures relative to the waste
Dispose of waste cans and containers according to local regulations.

Exposure estimation and reference to its source
Risk Characterization Ratio (RCR): 0.029
Risk from environmental exposure is driven by freshwater and marine water.
Maximum safe use amount: 15,141 kg/day

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC1: Use in closed process, no likelihood of exposure. General exposure (closed system).

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC2: Use in closed, continuous process with occasional controlled exposure. Filling/Preparation of equipment required for drums and containers.

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC2: Use in closed, continuous process with occasional controlled exposure. General exposure. Use in confined systems (closed system). Filling/Preparation of equipment required for drums and containers.

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Operation is carried out at elevated temperature (> 20°C above ambient temperature).

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 15.02 mg/m³
Risk Characterization Ratio (RCR): 0.4
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 1.37 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.03

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC3: Use in batch process (synthesis or formulation). Preparation of material for application

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 18.77 mg/m³
Risk Characterization Ratio (RCR): 0.05
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 0.34 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.01

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC4: Use in batch and other processes (synthesis) where opportunity for exposure arises. Film formation - Air drying.

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 6.86 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.14

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC4: Use in batch and other processes (synthesis) where opportunity for exposure arises. Film formation - Air drying.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Indoor/Outdoor: Indoor use.
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC5: Mixing in batch processes for formulation of preparations and articles (multistage and/or significant contact). Preparation of material for application.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 75.08 mg/m³
Risk Characterization Ratio (RCR): 0.2
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 13.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.27

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC5: Mixing in batch processes for formulation of preparations and articles (multistage and/or significant contact). Preparation of material for application.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures

Ensure that operations are carried out externally.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities. Material transfers. Drum/batch transfers. Non-dedicated system.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 75.08 mg/m³
Risk Characterization Ratio (RCR): 0.2
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 13.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.27

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities. Material transfers. Drum/batch transfers Dedicated plant.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 37.54 mg/m³
Risk Characterization Ratio (RCR): 0.1
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 6.86 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.14

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC10: Application with rollers or brushes. Roller, spatula, jet application.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 75.08 mg/m³
Risk Characterization Ratio (RCR): 0.2
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 27.43 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.54

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC10: Application with rollers or brushes. Roller, spatula, jet application.

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Indoor/Outdoor: Outdoor use.
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC11: Non-industrial spray application. Spraying (manual).

Area of use: Professional

Operating conditions
Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Effectiveness: 30%.
Wear chemically resistant gloves in combination with “basic” employee training. Effectiveness: 90%.
If there is no general ventilation, ensure that operations are carried out outdoors.

Exposure estimation and reference to its source
Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 262.79 mg/m³
Risk Characterization Ratio (RCR): 0.71
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 10.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.21

Guidance for downstream users
http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC11: Non-industrial spray application. Spraying (manual).

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures

Ensure that operations are carried out externally.
Wear chemically resistant gloves in combination with “basic” employee training.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC13: Treatment of articles by dipping, pouring, enamelling.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 75.08 mg/m³
Risk Characterization Ratio (RCR): 0.2
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 13.71 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.27

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC13: Treatment of articles by dipping, pouring, enamelling.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Indoor/Outdoor: Indoor use.
Assumes use at not more than 20°C above ambient temperature.

Risk management measures

Ensure that operations are carried out externally.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC15: Use as laboratory reagent. Laboratory activities.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 7.51 mg/m³
Risk Characterization Ratio (RCR): 0.02
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 0.34 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.01

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC19: Manual mixing with direct contact using only personal protective equipment. Hand application - fingerpaints, pastels, adhesives.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Assumes use at not more than 20°C above ambient temperature.

Risk management measures

Wear suitable gloves compliant with EN ISO 374-1. Effectiveness: 80%.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Worker - inhalation, long-term - systemic.
Exposure estimation: 75.08 mg/m³
Risk Characterization Ratio (RCR): 0.2
Evaluation method: ESIG GES tool, Operator. Worker - dermal, long-term - systemic.
Exposure estimation: 28.29 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.56

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC19: Manual mixing with direct contact using only personal protective equipment. Hand application - fingerpaints, pastels, adhesives.

Area of use: Professional

Operating conditions

Substance concentration: 1-methoxy-2-propanol content: ≥0 - ≤5%
Physical state: liquid, medium volatility
Duration and frequency of application: 480 mins. 5 days a week
Indoor/Outdoor: Outdoor use.
Assumes use at not more than 20°C above ambient temperature.

Risk management measures

Wear suitable gloves compliant with EN ISO 374-1.

Exposure estimation and reference to its source

Evaluation method: ESIG GES tool, Operator. Workers - all relevant routes of exposure
If the operating conditions identified and risk management measures are applied, the use has been assessed as safe.

Guidance for downstream users

http://www.esig.org/en/regulatory-information/reach/ges-library/ges-library-3

ODJELJAK 1.: Identifikacija tvari/smjese i podaci o društvu/poduzeću

1.1. Identifikacijska oznaka proizvoda

Identifikacija preparata:

Trgovačko ime: FASSA EPOXY 100 COMP.B

Trgovački kod: 1222.B

UFI: 75U2-X13E-100Q-171T

1.2. Utvrđene relevantne uporabe tvari ili smjese i uporabe koje se ne preporučuju

Preporučana upotreba: Epoksidna podloga za FRP sustave; Samo za stručno upotrebljavanje

Nepreporučljiva upotreba: Nije namijenjeno potrošačima

1.3. Podaci o dobavljaču koji isporučuje sigurnosno-tehnički list

Tvrtka: FASSA Srl

Via Lazzaris, 3 - 31027 Spresiano (TV) - ITALY

Tel. +39 0422 7222

Fax +39 0422 887509

Odgovorna osoba: laboratorio.spresiano@fassabortolo.it

1.4. Broj telefona za izvanredna stanja

+3851 2348 342

ODJELJAK 2.: Identifikacija opasnosti



2.1. Razvrstavanje tvari ili smjese

Uredba (EC) br. 1272/2008 (CLP)

Acute Tox. 4	Štetno ako se proguta.
Acute Tox. 4	Štetno ako se udiše.
Skin Corr. 1C	Uzrokuje teške opekline kože i ozljede oka.
Skin Sens. 1	Može izazvati alergijsku reakciju na koži.
Repr. 2	Sumnja na moguće štetno djelovanje na plodnost. Sumnja na mogućnost štetnog djelovanje na nerođeno dijete.
STOT RE 2	Može uzrokovati oštećenje organa tijekom produljene ili ponavljane izloženosti.
Aquatic Chronic 3	Štetno za vodeni okoliš s dugotrajnim učincima.

Fizikalno-kemijski učinci štetni po ljudsko zdravlje i okoliš:

Nema ostalih rizika

2.2. Elementi označivanja

Uredba (EC) br. 1272/2008 (CLP):

Piktogrami i oznaka opasnosti



Opasnost

Oznake upozorenja

H302	Štetno ako se proguta.
H314	Uzrokuje teške opekline kože i ozljede oka.
H317	Može izazvati alergijsku reakciju na koži.
H332	Štetno ako se udiše.
H361fd	Sumnja na moguće štetno djelovanje na plodnost. Sumnja na mogućnost štetnog djelovanje na nerođeno dijete.
H373	Može uzrokovati oštećenje organa tijekom produljene ili ponavljane izloženosti.
H412	Štetno za vodeni okoliš s dugotrajnim učincima.

Oznake obavijesti

P260	Nemojte udisati dimove/plinove/maglicu/pare/aerosole.
P264	Temeljito oprati vodom nakon rukovanja.
P280	Nositi zaštitne rukavice/zaštitno odijelo te zaštitu za oči/zaštitu za lice.
P303+P361+P353	U SLUČAJU DODIRA S KOŽOM (ili kosom): odmah skinuti svu zagađenu odjeću. Isprati kožu vodom [ili tuširanjem].
P305+P351+P338	U SLUČAJU DODIRA S OČIMA: oprezno ispirati vodom nekoliko minuta. Ukloniti kontaktne leće ako ih nosite i ako se one lako uklanjaju. Nastaviti ispirati.
P310	Odmah nazvati CENTAR ZA KONTROLU OTROVANJA/liječnika.

Sadrži:

3-aminometil-3,5,5-trimetilcikloheksilamin

m-fenilenbis(metilamin)

benzil-alkohol

produkti reakcije formaldehid i 4-nonilfenol
i trietilentetramin i 2-piperazin-1-iletilamin

2-piperazin-1-iletilamin

3-aminopropiltrietoksisilan

Posebne odredbe prema Prilogu XVII REACH-a i naknadnih amandmana:

Niti jedan

2.3. Ostale opasnosti

Bez PBT-a, vPvB-a ili endokrinih disruptora prisutnih
u koncentraciji > = 0,1 %.

Nema ostalih rizika

ODJELJAK 3.: Sastav/informacije o sastojcima

3.1. Tvari

Ne primjenjuje se.

3.2. Smjese

Identifikacija preparata: FASSA EPOXY 100 COMP.B

Opasni sastojci u smislu CLP Uredbe koja se odnosi na razvrstavanje:

Količina	Naziv	Ident. Broj.	Klasifikacija	Broj registriranih slučajeva:
≥30 - <50 %	m-fenilenbis(metilamin)	CAS:1477-55-0 EC:216-032-5	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412, EUH071 Procjena akutne toksičnosti: ATE - Oralno: 500mg/kg t.m. ATE - Udisanje (Prašina/maglica): 1.5mg/l	01-2119480150-50-xxxx
≥20 - <30 %	benzil-alkohol	CAS:100-51-6 EC:202-859-9 Index:603-057-00-5	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Procjena akutne toksičnosti: ATE - Oralno: 1200mg/kg t.m.	01-2119492630-38-xxxx
≥10 - <20 %	produkti reakcije formaldehid i 4-nonilfenol i trietilentetramin i 2-piperazin-1-iletilamin	EC:922-006-0	Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1B, H314	
≥10 - <20 %	3-aminometil-3,5,5-trimetilcikloheksilamin	CAS:2855-13-2 EC:220-666-8 Index:612-067-00-9	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Specifične granične vrijednosti koncentracije: C ≥ 0.001%: Skin Sens. 1A H317 Procjena akutne toksičnosti: ATE - Oralno: 1030mg/kg t.m.	01-2119514687-32-xxxx

≥3 - <5 %	2-piperazin-1-iletilamin	CAS:140-31-8 EC:205-411-0 Index:612-105-00-4	Acute Tox. 3, H311 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361fd STOT RE 1, H372 Aquatic Chronic 3, H412 Procjena akutne toksičnosti: ATE - Oralno: 500mg/kg t.m. ATE - Dermalno: 866mg/kg t.m.	01-2119471486-30-xxxx
≥0.5 - <1 %	3-aminopropiltrietoksisilan	CAS:919-30-2 EC:213-048-4 Index:612-108-00-0	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Procjena akutne toksičnosti: ATE - Oralno: 500mg/kg t.m.	01-2119480479-24-xxxx

ODJELJAK 4.: Mjere prve pomoći

4.1. Opis mjera prve pomoći

U slučaju kontakta sa kožom:

Smjesta skinuti zagađenu odjeću i ukloniti je na bezbjedan način.

ODMAH NAZVATI MEDICINSKU EKIPU ZA HITNU POMOĆ

U slučaju kontakta sa očima:

U slučaju kontakta sa očima, ispirati oči vodom neko vrijeme, držati otvorene kapke, a potom zatražiti pomoć oftalmologa.

Zaštititi neozlijeđeno oko.

U slučaju gutanja:

Ne davati hranu niti piće.

Ne poticati povraćanje, obratiti se liječniku i pokazati listić o sigurnosti i oznaku kemijskog rizika.

U slučaju udisanja:

Izloženu osobu treba iznijeti na svježi zrak, držati je na toplom, a ista mora mirovati.

Ukoliko osoba nepravilno diše ili uopće ne diše, dati umjetno disanje.

Ukoliko se proguta, hitno zatražiti savjet liječnika i pokazati posudu ili naljepnicu.

4.2. Najvažniji simptomi i učinci, akutni i odgođeni

Simptomi i ucinci su u skladu s ocekivanjima od opasnosti kako je prikazano u 2. odjeljku.

4.3. Navod o potrebi za hitnom liječničkom pomoći i posebnom obradom

U slučaju nesreće ili slabosti smjesta se obratiti liječniku (ako je moguće, pokazati upute za uporabu ili sigurnosni list).

ODJELJAK 5.: Mjere za suzbijanje požara

5.1. Sredstva za gašenje

Prikladna sredstva za gašenje požara:

CO2, aparati za gašenje požara prahom, pjena, raspršivanje vode.

Sredstva za gašenje požara koja ne treba koristiti iz bezbijednosnih razloga:

Voda u mlazovima.

5.2. Posebne opasnosti koje proizlaze iz tvari ili smjese

Sagorijevanjem se oslobađaju teški dimovi.

Ne udisati plinove nastale eksplozijom i/ili izgaranjem (ugljikov monoksid i ugljikov dioksid, dušikove okside).

5.3. Savjeti za gasitelje požara

Koristiti prikladne dišne aparate.

Posebno pokupiti zaprljanu vodu, koja je korištena za gašenje požara. Ne bacati ovu vodu u kanalizacionu mrežu.

Neoštećene spremnike skloniti iz prostora neposredne opasnosti, ukoliko se to može izvršiti na bezbjedan način.

ODJELJAK 6.: Mjere kod slučajnog ispuštanja

6.1. Osobne mjere opreza, zaštitna oprema i postupci za izvanredna stanja

Za osobe koje se ne ubrajaju u interventno osoblje:

Koristiti sredstva za osobnu zaštitu.

Ukoliko ste izloženi pari/prašini/aerosoli nosite dišne aparate.

Obezbjediti prikladno prozračivanje.

Koristiti prikladnu zaštitu dišnih organa.

Konzultirati mjere zaštite opisane u točkama 7. i 8.

Za interventno osoblje:

Koristiti sredstva za osobnu zaštitu.

6.2. Mjere zaštite okoliša

Spriječiti prodiranje u tlo/dublje slojeve zemlje. Spriječiti ulivanje u površinske vode ili u kanalizacionu mrežu.

U slučaju izlaska plina ili prodiranja u vodene tokove, tlo ili kanalizacionu mrežu, obavijestiti nadležna tijela.

6.3. Metode i materijal za sprečavanje širenja i čišćenje

Materijal je prikladan za skupljanje: inertni upijajući materijal (npr. pijesak, vermikulit)

Nakon što je proizvod sakupljen, isprati onečišćeno područje i predmete s vodom.

Zadržati vodu kojom ste izvršili pranje, pa je eliminirati.

6.4. Uputa na druge odjeljke

Pogledati također i paragrafe 8. i 13.

ODJELJAK 7.: Rukovanje i skladištenje

7.1. Mjere opreza za sigurno rukovanje

Izbjegavati dodir s kožom i očima, udisanje para i maglica.

Koristiti lokaliziranu ventilaciju.

Ne koristite prazne spremnike prije no što ih očistite.

Prije prijenosa proizvoda, uvjeriti se da u spremnicima nema ostataka nekompatibilnih tvari.

Savjeti o općoj higijeni na radnom mjestu:

Kontaminirana odjeća se smjesta mora zamijeniti prije ulaska u menze.

Ne konzumirati hranu i piće na radnom mjestu.

Pogledati i paragraf 8. u svezi sa preporučanim napravama za zaštitu.

7.2. Uvjeti sigurnog skladištenja, uzimajući u obzir moguće inkompatibilnosti

Čuvati spremnike dobro zatvorene na hladnom i dobro prozračenom mjestu daleko od izvorā topline.

Držati podalje od hrane, pića i krmiva.

Inkompatibilne tvari:

Vidi točku 10.5

Upute za prostorije za skladištenje:

Adekvatno prozračene prostorije.

7.3. Posebna krajnja uporaba ili uporabe

Preporuke

Vidi točku 1.2

Specifične otopine za industrijski sektor

Nema posebne upotrebe

ODJELJAK 8.: Nadzor nad izloženošću/osobna zaštita

8.1. Nadzorni parametri

Granične vrijednosti izloženosti na mjestu rada

m-fenilenbis(metilamin)

CAS: 1477-55-0	OEL Tip	ACGIH		Kratkoročno Ceiling - 0.018 ppm Napomene: Skin - Eye, skin, and GI irr
	OEL Tip	MAK	Austrija	Dugoročno 0.1 mg/m3
	OEL Tip	VLEP	Belgija	Kratkoročno 0.1 mg/m3
	OEL Tip	VLEP	Francuska	Kratkoročno 0.1 mg/m3
	OEL Tip	SUVA	Švicarska	Dugoročno 0.1 mg/m3

benzil-alkohol

CAS: 100-51-6	OEL Tip	MAK	Njemačka	Dugoročno 22 mg/m3 - 5 ppm; Kratkoročno 44 mg/m3 - 10 ppm Napomene: Inhalable fraction and vapour, Skin
	OEL Tip	TLV	Bugarska	Dugoročno 5 mg/m3
	OEL Tip	TLV	Češka	Dugoročno 40 mg/m3 - 8.88 ppm; Kratkoročno 80 mg/m3 - 17.76 ppm
	OEL Tip	SUVA	Švicarska	Dugoročno 22 mg/m3 - 5 ppm
	OEL Tip	AGW	Njemačka	Dugoročno 22 mg/m3 - 5 ppm; Kratkoročno 44 mg/m3 - 10 ppm Napomene: Inhalable fraction and vapour
	OEL Tip	NDS	Poljska	Dugoročno 240 mg/m3
	OEL Tip	MV	Slovenija	Dugoročno 22 mg/m3 - 5 ppm; Kratkoročno 44 mg/m3 - 10 ppm Napomene: Skin
	OEL Tip	IPRV	Litva	Dugoročno 5 mg/m3 Napomene: Skin

Granične vrijednosti izloženosti PNEC

m-fenilenbis(metilamin)

CAS: 1477-55-0 Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.009 mg/l

Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.094 mg/l

Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.043 mg/kg

Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.43 mg/kg

Putevi izloženosti: Tlo (poljoprivredno); PNEC Ograničiti: 0.045 mg/kg

Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 10 mg/l

benzil-alkohol

CAS: 100-51-6 Putevi izloženosti: Svježa voda; PNEC Ograničiti: 1 mg/l

Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.1 mg/l

Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 39 mg/l

Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 5.27 mg/kg

Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 0.527 mg/kg

Putevi izloženosti: Tlo (poljoprivredno); PNEC Ograničiti: 0.456 mg/kg

3-aminometil-3,5,5-trimetilcikloheksilamin

CAS: 2855-13-2 Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.06 mg/l

Putevi izloženosti: Morska voda; PNEC Ograničiti: 0.006 mg/l

Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 3.18 mg/l

Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 5.784 mg/kg

Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 0.578 mg/kg

Putevi izloženosti: Tlo (poljoprivredno); PNEC Ograničiti: 1.121 mg/kg

2-piperazin-1-iletilamin

CAS: 140-31-8 Putevi izloženosti: Svježa voda; PNEC Ograničiti: 0.058 mg/l

Putevi izloženosti: Morska voda; PNEC Ograničiti: 5.8 µg/l

Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 250 mg/l

Putevi izloženosti: Sedimenti svježe vode; PNEC Ograničiti: 215 mg/kg

Putevi izloženosti: Sedimenti morske vode; PNEC Ograničiti: 21.5 mg/kg

Putevi izloženosti: Zemlja; PNEC Ograničiti: 1 mg/kg

3-aminopropiltrietoksisilan

CAS: 919-30-2 Putevi izloženosti: Mikroorganizmi u postrojenjima za obradu otpadnih voda (STP); PNEC Ograničiti: 1.3 mg/l

Izvedena razina bez učinka. (DNEL)

m-fenilenbis(metilamin)

CAS: 1477-55-0 Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 0.33 mg/kg

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, lokalni učinci
Profesionalni djelatnik: 0.2 mg/m3

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 1.2 mg/m3

benzil-alkohol

CAS: 100-51-6 Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Kratkotrajni, sistemski učinci
Profesionalni djelatnik: 110 mg/m3; Potrošač: 27 mg/m3

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 22 mg/m3; Potrošač: 5.4 mg/m3

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Kratkotrajni, sistemski učinci
Profesionalni djelatnik: 40 mg/kg; Potrošač: 20 mg/kg

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci

Profesionalni djelatnik: 8 mg/kg; Potrošač: 4 mg/kg

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Kratkotrajni, sistemski učinci
Potrošač: 20 mg/kg

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Potrošač: 4 mg/kg

3-aminometil-3,5,5-trimetilcikloheksilamin

CAS: 2855-13-2 Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, lokalni učinci
Profesionalni djelatnik: 0.073 mg/m3

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Kratkotrajni, lokalni učinci
Profesionalni djelatnik: 0.073 mg/m3

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Potrošač: 0.3 mg/kg/day

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Kratkotrajni, sistemski učinci
Potrošač: 0.3 mg/kg/day

2-piperazin-1-iletilamin

CAS: 140-31-8 Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Kratkotrajni, sistemski učinci
djelatnik: 10.6 mg/m3

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
djelatnik: 10.6 mg/m3

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, lokalni učinci
djelatnik: 0.015 mg/m3

Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Kratkotrajni, lokalni učinci
djelatnik: 0.08 mg/m3

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci
djelatnik: 3.33 mg/kg

3-aminopropiltrietoksisilan

CAS: 919-30-2 Putevi izloženosti: Ljudi inhalacijski; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 14 mg/m3; Potrošač: 3.5 mg/m3

Putevi izloženosti: Ljudi dermalno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Profesionalni djelatnik: 2 mg/kg; Potrošač: 1 mg/kg

Putevi izloženosti: Ljudi oralno; Učestalost izloženosti: Dugotrajni, sistemski učinci
Potrošač: 1 mg/kg

8.2. Nadzor nad izloženošću

Osigurati odgovarajuću ventilaciju. Kad je to razumno moguće, to se može postići upotrebom rezervne ventilacije i dobre opće aspiracije.

Zaštita očiju:

Čaše sa bočnom zaštitom (EN 16321).

Zaštita kože:

Upotrebljavati odjeću prikladnu za potpunu zaštitu kože u skladu s aktivnošću i izloženošću (EN 14605/EN 13982), npr. radne kombinezone, pregače, sigurnosnu obuću, prikladnu odjeću.

Zaštita za ruke:

Ne postoji materijal ili kombinacija materijala za rukavice koji bi mogli jamčiti neograničenu otpornost na bilo koji kemijski proizvod ili kombinaciju proizvoda.

Ako je riječ o duljem ili ponavljanom rukovanju, koristite se rukavicama otpornim na kemijske proizvode.

Prikladne rukavice tipa (EN 374/EN 16523); FKM (fluorirana guma): debljina> = 0,4 mm; vrijeme prodiranja> = 480 min. NBR (nitrilna guma): debljina> = 0,4 mm; vrijeme prodiranja> = 480 min

Izbor prikladnih rukavica ne ovisi samo o materijalu, nego i o drugim karakteristikama kvalitete koje se razlikuju od proizvođača do proizvođača, i o načinima i vremenu upotrebe smjese.

Zaštita pri disanju:

Ako su radnici izloženi koncentracijama višima od granice izloženosti, moraju upotrebljavati odgovarajuće certificirane respiratore.

Kombinirana filtrirajuća naprava (EN 14387): maska s filtrom A-P2.

Kontrola izlaganja u okolišu:

Vidi točku 6.2

Higijenske i tehničke mjere

Vidi odlomak 7.

ODJELJAK 9.: Fizikalna i kemijska svojstva

9.1. Informacije o osnovnim fizikalnim i kemijskim svojstvima

fizičko stanje: tekuće
Izgled: tekuće
Boja: ćilibar
Miris: amin
Talište/ledište: N.D.
Vrelište ili početno vrelište i raspon temperatura vrenja: N.D.
Zapaljivost: Ne primjenjuje se.
Donja i gornja granica eksplozivnosti: N.D.
Plamište: Ne primjenjuje se.
Temperatura samozapaljenja: N.D.
Temperatura raspadanja: Ne primjenjuje se.
pH: Ne primjenjuje se.
Kinematička viskoznost: Ne primjenjuje se.
Topljivost u vodi: Ne primjenjuje se.
Topljivost u ulje: Topivo
Koeficijent raspodjele n-oktanol/voda (logaritamska vrijednost): Ne primjenjuje se.
Tlak pare: N.D.
Gustoća i/ili relativna gustoća: 0.991 kg/l (Interna metoda)
Relativna gustoća pare: N.D. Ne primjenjuje se.

Svojstva čestica:

Veličina čestica: Ne primjenjuje se.

9.2. Ostale informacije

Explozivne osobine: Ne primjenjuje se. (Interna evaluacija)
Osobine oksidiranja: Ne primjenjuje se. (Interna evaluacija)

ODJELJAK 10.: Stabilnost i reaktivnost

10.1. Reaktivnost

Stabilan u normalnim uvjetima

10.2. Kemijska stabilnost

Stabilan u normalnim uvjetima

10.3. Mogućnost opasnih reakcija

Može se zapaliti u kontaktu s jakim oksidansima.
Zbog djelovanja topline ili u slučaju požara može doći do oslobađanja ugljikovih oksida i para koji mogu biti štetni za zdravlje.

10.4. Uvjeti koje treba izbjegavati

Čuvati odvojeno od izvorā topline.

10.5. Inkompatibilni materijali

Snažni oksidansi, snažna redukcijska sredstva, alifatski i aromatski amini.
Vidi točku 10.3

10.6. Opasni proizvodi raspadanja

Pri odgovarajućem skladištenju i rukovanju ne razvijaju se opasni proizvodi raspadanja.
Vidi točku 5.2

ODJELJAK 11.: Toksikološke informacije

11.1. Informacije o razredima opasnosti kako su definirani u Uredbi (EZ) br. 1272/2008

Podaci o toksičnosti proizvoda:

a) akutna toksičnost	Proizvod je razvrstan kao: Acute Tox. 4(H302), Acute Tox. 4(H332)
b) kožno nagrizanje/nadraživanje	Proizvod je razvrstan kao: Skin Corr. 1C(H314)
c) teške očne ozljede/teško očno nadraživanje	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
d) izazivanje kožne ili dišne preosjetljivosti	Proizvod je razvrstan kao: Skin Sens. 1(H317)
e) mutagenost zametnih stanica	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
f) kancerogenost	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
g) reproduktivna toksičnost	Proizvod je razvrstan kao: Repr. 2(H361)
h) Specifična toksičnost za ciljne	Nije kategorizirano

organe (STOT) jednokratno izlaganje	
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.
i) Specifična toksičnost za ciljne organe (STOT) opetovano izlaganje	Proizvod je razvrstan kao: STOT RE 2(H373)
j) opasnost u slučaju udisanja	Nije kategorizirano
	Na temelju dostupnih podataka kriteriji za razvrstavanje nisu ispunjeni.

Podaci o toksičnosti glavnih sastojaka u proizvodu:

m-fenilenbis(metilamin)

CAS: 1477-55-0	a) akutna toksičnost	ATE - Oralno: 500 mg/kg t.m.
		ATE - Udisanje (Prašina/maglica): 1.5 mg/l
		LD50 Koža Štakor > 3100 mg/kg
		LD50 Oralno Štakor 930 mg/kg
		LC50 Inhalacija aerosola Štakor 1.34 mg/l 4h

benzil-alkohol

CAS: 100-51-6	a) akutna toksičnost	ATE - Oralno: 1200 mg/kg t.m.
		LD50 Oralno Štakor 1620 mg/kg

3-aminometil-3,5,5-trimetilcikloheksilamin

CAS: 2855-13-2	a) akutna toksičnost	ATE - Oralno: 1030 mg/kg t.m.
		LC50 Inhalacija aerosola Štakor > 5.01 mg/l 4h
		LD50 Koža Štakor > 2000 mg/kg t.m.

2-piperazin-1-iletilamin

CAS: 140-31-8	a) akutna toksičnost	ATE - Oralno: 500 mg/kg t.m.
		ATE - Dermalno: 866 mg/kg t.m.

3-aminopropiltrietoksisilan

CAS: 919-30-2	a) akutna toksičnost	ATE - Oralno: 500 mg/kg t.m.
		LD50 Oralno Štakor 1490 mg/kg
		LD50 Koža Kunić 4075 mg/kg

11.2. Informacije o drugim opasnostima

Svojstva endokrine disrupcije:

Bez drugih endokrinih disruptora prisutnih u koncentraciji > = 0,1 %

ODJELJAK 12.: Ekološke informacije

Primjeniti dobre radne postupke da se produkt ne oslobađa u okoliš.

12.1. Toksičnost

Eko-Toksikološke informacije:

Štetno za vodeni okoliš s dugotrajnim učincima.

Popis eko-toksikoloških svojstava proizvoda

Proizvod je razvrstan kao: Aquatic Chronic 3(H412)

Popis sastojaka sa eko-toksikološkim svojstvima

m-fenilenbis(metilamin)

CAS: 1477-55-0	a) Akutna otrovnost na vodene organizme: LC50 Ribe 87.6 mg/l 96h
	a) Akutna otrovnost na vodene organizme: EC50 Algae 20.3 mg/l 72h
	a) Akutna otrovnost na vodene organizme: EC50 Daphnia 15.2 mg/l 48h
	b) Hronična otrovnost na vodene organizme: NOEC Daphnia 4.7 mg/l 21d
	b) Hronična otrovnost na vodene organizme: NOEC Algae 10.5 mg/l 72h

benzil-alkohol

CAS: 100-51-6	a) Akutna otrovnost na vodene organizme: LC50 Ribe 460 mg/l 96h
	a) Akutna otrovnost na vodene organizme: EC50 Daphnia 230 mg/l 48h
	a) Akutna otrovnost na vodene organizme: EC50 Algae 770 mg/l 72h
	b) Hronična otrovnost na vodene organizme: NOEC Daphnia 51 mg/l 21d
	b) Hronična otrovnost na vodene organizme: NOEC Algae 310 mg/l 72h

3-aminometil-3,5,5-trimetilcikloheksilamin

CAS: 2855-13-2 a) Akutna otrovnost na vodene organizme: LC50 Ribe 110 mg/l 96h

a) Akutna otrovnost na vodene organizme: EC50 Daphnia 23 mg/l 48h

a) Akutna otrovnost na vodene organizme: EC50 Algae > 50 mg/l 72h

b) Hronična otrovnost na vodene organizme: NOEC Daphnia 3 mg/l 21d

2-piperazin-1-iletilamin

CAS: 140-31-8 a) Akutna otrovnost na vodene organizme: LC50 Ribe 2190 mg/l 96h

a) Akutna otrovnost na vodene organizme: EC50 Daphnia 58 mg/l 48h

a) Akutna otrovnost na vodene organizme: EC50 Algae > 1000 mg/l 72h

3-aminopropiltrietoksisilan

CAS: 919-30-2 a) Akutna otrovnost na vodene organizme: LC50 Ribe > 934 mg/l 96h

a) Akutna otrovnost na vodene organizme: EC50 Daphnia 331 mg/l 48h

a) Akutna otrovnost na vodene organizme: EC50 Algae 603 mg/l 72h

12.2. Postojanost i razgradivost

m-fenilenbis(metilamin)

CAS: 1477-55-0 Nije brzo-biološki razgradiv

benzil-alkohol

CAS: 100-51-6 Brzo-biološki razgradiv

3-aminometil-3,5,5-trimetilcikloheksilamin

CAS: 2855-13-2 Nije brzo-biološki razgradiv

3-aminopropiltrietoksisilan

CAS: 919-30-2 Nije brzo-biološki razgradiv

12.3. Bioakumulacijski potencijal

3-aminometil-3,5,5-trimetilcikloheksilamin

CAS: 2855-13-2 Nije bioakumulativan

3-aminopropiltrietoksisilan

CAS: 919-30-2 Nije bioakumulativan

12.4. Pokretljivost u tlu

3-aminometil-3,5,5-trimetilcikloheksilamin

CAS: 2855-13-2 Test: Log Koc; Vrijednost: 2.970

2-piperazin-1-iletilamin

CAS: 140-31-8 Test: Log Koc

3-aminopropiltrietoksisilan

CAS: 919-30-2 Test: Log Koc; Vrijednost: -0.600

12.5. Rezultati procjene svojstava PBT i vPvB

Prema dostupnim podacima proizvod ne sadrži PBT/vPvB u postotku većem ≥ 0.1%.

12.6. Svojstva endokrine disrupcije

Bez drugih endokrinih disruptora prisutnih u koncentraciji > = 0,1 %

12.7. Ostali štetni učinci

Ne primjenjuje se.

ODJELJAK 13.: Zbrinjavanje

13.1. Metode obrade otpada


Regenerirati ako je moguće. Poslati ovlaštenim postrojenjima za odlaganje ili na spaljivanje pod kontroliranim uvjetima. Pri tome se pridržavati vrijedećih lokalnih i državnih regulativa.

Ne dopustiti prodor u kanalizaciju ili vodene tokove.

Zbrinite kontejnera onečišćenih proizvoda u skladu s lokalnim ili nacionalnim zakonskim odredbama.

Proizvod se nakon isteka roka trajanja mora odložiti prema propisima na snazi.

ODJELJAK 14.: Informacije o prijevozu



14.1. UN broj ili identifikacijski broj

2735

14.2. Ispravno otpremno ime prema UN-u

ADR-Naziv za otpremu: AMINI, TEKUĆI, KOROZIVNI, N.D.N. (m-fenilenbis(metilamin) - produkti reakcije formaldehid i 4-nonilfenol i trietilentetramin i 2-piperazin-1-iletilamin)

IATA-Naziv za otpremu: AMINES, LIQUID, CORROSIVE, N.O.S. POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-fenilenbis(metilamin) - produkti reakcije formaldehid i 4-nonilfenol i trietilentetramin i 2-piperazin-1-iletilamin)

IMDG-Naziv za otpremu: AMINES, LIQUID, CORROSIVE, N.O.S. POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-fenilenbis(metilamin) - produkti reakcije formaldehid i 4-nonilfenol i trietilentetramin i 2-piperazin-1-iletilamin)

14.3. Razred(i) opasnosti pri prijevozu

ADR-Razred: 8

IATA-Razred: 8

IMDG-Razred: 8

14.4. Skupina pakiranja

ADR-Grupa pakiranja: III

IATA-Grupa pakiranja: III

IMDG-Grupa pakiranja: III

14.5. Opasnosti za okoliš

Morski polutant: Ne

Zagađivači okoliša: Ne

IMDG-EMS: F-A, S-B

14.6. Posebne mjere opreza za korisnika

Ceste i Željeznica (ADR-RID):

ADR-Označavanje: 8

ADR - Identifikacijski broj opasnosti: 80

ADR-Posebne odredbe: 274

ADR ograničenja prijevoza u tunelu:

Zrak (IATA):

IATA-Putnički zrakoplov: 852

IATA-Teretni zrakoplov: 856

IATA-Označavanje: 8

IATA-Sporedni opasnosti: -

IATA-Erg: 8L

IATA-Posebne odredbe: A3 A803

More (IMDG):

IMDG-Skladištenje i rukovanje: Category A

IMDG-Segregacija: SG35 SGG18

IMDG-Sporedni opasnosti -

IMDG-Posebne odredbe: 223 274

14.7. Prijevoz morem u razlivenom stanju u skladu s instrumentima IMO-a

Ne primjenjuje se.

ODJELJAK 15.: Informacije o propisima

15.1. Propisi u području sigurnosti, zdravlja i okoliša/posebno zakonodavstvo za tvar ili smjesu

Direktiva 98/24/EC (Rizici koji nastaju od kemijskih agenasa na radu)

Direktiva 2000/39/EC (Granična vrijednost profesionalne izloženosti)

Direktiva 2010/75/EU

Uredba (EC) br. 1907/2006 (REACH)

Uredba (EC) br. 1272/2008 (CLP)

Uredba (EC) br. 790/2009 (ATP 1 CLP) i (EZ) br. 758/2013

Uredba (EZ) br. 2020/878

Uredba (EZ) br. 286/2011 (ATP 2 CLP)

Uredba (EZ) br. 618/2012 (ATP 3 CLP)

Uredba (EZ) br. 487/2013 (ATP 4 CLP)

Uredba (EZ) br. 944/2013 (ATP 5 CLP)

Uredba (EZ) br. 605/2014 (ATP 6 CLP)

Uredba (EZ) br. 2015/1221 (ATP 7 CLP)
Uredba (EZ) br. 2016/918 (ATP 8 CLP)
Uredba (EZ) br. 2016/1179 (ATP 9 CLP)
Uredba (EZ) br. 2017/776 (ATP 10 CLP)
Uredba (EZ) br. 2018/669 (ATP 11 CLP)
Uredba (EZ) br. 2018/1480 (ATP 13 CLP)
Uredba (EZ) br. 2019/521 (ATP 12 CLP)
Uredba (EZ) br. 2020/217 (ATP 14 CLP)
Uredba (EZ) br. 2020/1182 (ATP 15 CLP)
Uredba (EZ) br. 2021/643 (ATP 16 CLP)
Uredba (EZ) br. 2021/849 (ATP 17 CLP)
Uredba (EZ) br. 2022/692 (ATP 18 CLP)
Uredba (EU) no. 2023/707
Uredba (EZ) br. 2023/1434 (ATP 19 CLP)
Uredba (EZ) br. 2023/1435 (ATP 20 CLP)
Uredba (EZ) br. 2024/197 (ATP 21 CLP)
Uredba (EZ) br. 2024/2564 (ATP 22 CLP)
Uredba (EZ) br. 2024/2865
Uredba (EZ) br. 2025/1222 (ATP 23 CLP)

Ograničenja u vezi s produktom ili sadržajnim tvarima u skladu s Prilogom XVII Uredbe (EZ-a) 1907/2006 (REACH) i naknadne izmjene:

Ograničenja koja se odnose na proizvod: 3

Ograničenja koja se odnose na sadržane tvari: 75

Odredbe prema direktivi 2012/18/EU (Seveso III)

Niti jedan

Uredba (EU) br. 649/2012 (Uredba PIC)

Nijedna tvar nije navedena

Njemačka klasifikacija opasnosti za vodu.

Klasa 3: iznimno opasni.

SVHC tvari:

Prema dostupnim podacima proizvod ne sadrži SVHC u postotku većem ≥ 0.1%.

15.2. Procjena kemijske sigurnosti

Procjena kemijske sigurnosti nije provedena za smjesu. Pogledajte scenarije izloženosti tvari priložene ovom sigurnosnom listu. Kad budete proučavali scenarije, razmotrite i eventualna ograničenja upotrebe navedena u odjeljku 1.2.

ODJELJAK 16.: Ostale informacije

Šifra	Opis
EUH071	Nagrizajuće za dišni sustav.
H302	Štetno ako se proguta.
H311	Otrovno u dodiru s kožom.
H314	Uzrokuje teške opekline kože i ozljede oka.
H317	Može izazvati alergijsku reakciju na koži.
H318	Uzrokuje teške ozljede oka.
H319	Uzrokuje jako nadraživanje oka.
H332	Štetno ako se udiše.
H361fd	Sumnja na moguće štetno djelovanje na plodnost. Sumnja na mogućnost štetnog djelovanja na nerođeno dijete.
H372	Uzrokuje oštećenje organa tijekom produljene ili ponavljane izloženosti ako se udiše.
H373	Može uzrokovati oštećenje organa tijekom produljene ili ponavljane izloženosti.
H412	Štetno za vodeni okoliš s dugotrajnim učincima.

Šifra	Razred opasnosti i kategorija opasnosti	Opis
3.1/3/Dermal	Acute Tox. 3	Akutna toksičnost (preko kože), kategorija 3
3.1/4/Inhal	Acute Tox. 4	Akutna toksičnost (udisanje), kategorija 4
3.1/4/Oral	Acute Tox. 4	Akutna toksičnost (gutanje), kategorija 4
3.2/1B	Skin Corr. 1B	Nagrizajuće za kožu, kategorija 1B
3.2/1C	Skin Corr. 1C	Nagrizajuće za kožu, kategorija 1C

3.3/1	Eye Dam. 1	Teška ozljeda oka, kategorija 1
3.3/2	Eye Irrit. 2	Nadražujuće za oči, kategorija 2
3.4.2/1	Skin Sens. 1	Izazivanje preosjetljivosti kože, kategorija 1
3.4.2/1A	Skin Sens. 1A	Izazivanje preosjetljivosti kože, kategorija 1A
3.4.2/1B	Skin Sens. 1B	Izazivanje preosjetljivosti kože, kategorija 1B
3.7/2	Repr. 2	Reproduktivna toksičnost, Kategorija 2
3.9/1	STOT RE 1	Specifična toksičnost za ciljane organe – ponavljano izlaganje, Kategorija 1
3.9/2	STOT RE 2	Specifična toksičnost za ciljane organe – ponavljano izlaganje, Kategorija 2
4.1/C3	Aquatic Chronic 3	Kroničnu (dugoročnu) opasnost za organizme koji žive u vodi, kategorija 3

Razvrstavanje i postupak razvrstavanja za smjese sukladno Uredbi (EZ) br. 1272/2008 (CLP):

Razvrstavanje prema Uredbi (EZ) br. 1272/2008	**Postupak razvrstavanja**
Acute Tox. 4, H302	Računska metoda
Acute Tox. 4, H332	Računska metoda
Skin Corr. 1C, H314	Računska metoda
Skin Sens. 1, H317	Računska metoda
Repr. 2, H361fd	Računska metoda
STOT RE 2, H373	Računska metoda
Aquatic Chronic 3, H412	Računska metoda

Ovaj dokument izradila je tehnički kompetentna osoba za SDS, te koja je prikladno za to osposobljena.

Glavni bibliografski izvori:

ECDIN – Informacijska mreža za ekološke podatke za kemikalije – Zajednički istraživački centar, Komisija Europskih zajednica

SAX's OPASNE OSOBINE INDUSTRIJSKIH TVARI- Osmo izdanje - Van Nostrand Reinold

Sigurnosno-tehnički listovi dobavljača sirovina.

Ovdje objavljne informacije se temelje na našem znanju u vrijeme gore navedenog datuma. Odnose se samo na navedene proizvode i ne predstavlja garanciju neke određene kvalitete.

Obaveza je korisnika da utvrdi da je ova informacija cjelovita i da odgovara specifičnoj upotrebi.

Ovaj MSDS poništava i zamjenjuje sva predhodna izdanja.

Legenda kratica i akronima upotrebljenih u sigurnosno-tehničkom listu:

ACGIH: Američka konferencija vladinih specijalista za industrijsku higijenu

ADR: Europski sporazum o međunarodnom cestovnom prijevozu opasnih tvari.

ATE: Procjena akutne toksičnosti

ATEmix: Procijenjena vrijednost akutne toksičnosti (Mješavine)

BEI: Indeks biološke izloženosti

CAS: CAS registarski broj (Američko kemijsko društvo)

CAV: Centar za otrove

CE: Europska zajednica

CLP: Razvrstavanje, označavanje, pakiranje.

CMR: Karcinogeno, Mutageno i Reprotoksično

COV: Hlapivi organski spoj

CSA: Procjena kemijske sigurnosti

CSR: Izvješće o kemijskoj sigurnosti

DNEL: Izvedena razina bez učinka.

EC50: Pulu maksimalna efektivna koncentracija

ECHA: Europska agencija za kemijske proizvode

EINECS: Europski propis postojećih trgovačkih kemijskih tvari.

ES: Scenario izloženosti

GefStoffVO: Propis o opasnim tvarima, Njemačka.

GHS: Globalno harmonizirani sustav razvrstavanja i označavanja kemikalija

IARC: Međunarodna agencija za istraživanja o karcinomu

IATA: Međunarodna udruga za zračni prijevoz.

IC50: Pulu maksimalna koncentracija inhibitora

IMDG: Međunarodni pomorski kodeks opasnog tereta.

LC50: Smrtna koncentracija u 50% slučajeva ispitivane populacije.

LD50: Smrtna doza u 50% slučajeva ispitivane populacije.

LDLo: Niska smrtonosna doza

N.A.: Nije primjenjivo
N/A: Nije primjenjivo
N/D: Nije definirano/Nije dostupno
N.D.: Nije dostupno
NIOSH: Državni institut za zaštitu na radu
NOAEL: Razina bez uočenih štetnih učinaka
OSHA: Upravljanje zaštitom na radu
PBT: Persistentno, bioakumulativno i toksično
PGK: Upute za pakiranje
PNEC: Predviđena koncentracija bez učinka.
PSG: Putnici
RID: Propis o međunarodnom prijevozu opasnih tvari željeznicom
STEL: Granica kratkotrajne izloženosti.
STOT: Toksičnost za ciljani organ.
TLV: Granična vrijednost praga.
TLV-TWA: Granična vrijednost praga za vremenski ponderirani prosjek. (ACGIH standard)
vPvB: Vrlo persistentno, vrlo bioakumulativno
WGK: Njemačka klasifikacija opasnosti za vodu.

Odlomci promijenjeni u odnosu na prethodnu reviziju:

- ODJELJAK 1.: Identifikacija tvari/smjese i podaci o društvu/poduzeću
- ODJELJAK 2.: Identifikacija opasnosti
- ODJELJAK 3.: Sastav/informacije o sastojcima
- ODJELJAK 8.: Nadzor nad izloženošću/osobna zaštita
- ODJELJAK 9.: Fizikalna i kemijska svojstva
- ODJELJAK 11.: Toksikološke informacije
- ODJELJAK 12.: Ekološke informacije
- ODJELJAK 15.: Informacije o propisima

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Substance identification
Chemical Name: 3-aminomethyl-3,5,5-trimethylcyclohexylamine
CAS number: 2855-13-2
EU index number: 612-067-00-9
EINECS number: 220-666-8

ES1 Formulation or repackaging - INDUSTRIAL USES

1. TITLE SECTION

Exposure scenario name: Preparation and repackaging of substances and mixtures
Date - Version: 15/07/2020 - 1.0
Life cycle stage: Formulation or repackaging
Main user group: Industrial uses
Sector(s) of use: Industrial uses (SU3) - Large-scale production of basic chemicals (including petroleum products) (SU8) - Formulation [blending] of preparations and/or repackaging (SU10)

Contributing scenario - Environment
CS1 Wet formulation: ERC2

Contributing scenario - Worker
CS2 Use in closed systems: PROC3
CS3 Material Transfers: PROC8a
CS4 Material Transfers: PROC8b
CS5 Material Transfers: PROC9
CS6 Blend Operations: PROC5

2. CONDITIONS OF USE AFFECTING EXPOSURE

2.1. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Environmental release categories: Formulation of mixtures (ERC2)

Product features (article)
Physical form of the product: Liquid
Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use
Amounts used: Annual amount per site 2500 t
Release Type: Continuous release
Issue days: 300 days/year
Further environmental conditions:
Wet formulation
Air - minimum efficiency of: 0.25 %
Ground - minimum efficiency of: 0.01 %
Water - minimum efficiency of: 0.5 %

Measures and technical-organizational conditions
Control measures to prevent releases:
Air - minimum efficiency of: 0.25 %
Ground - minimum efficiency of: 0.01 %
Water - minimum efficiency of: 0.5 %

Conditions and measures for the municipal sewage treatment plant
Type of sewage treatment plant (STP): Municipal STP
STP effluent (m^3/day): 8640

Conditions and measures for waste treatment (including the product waste)
Waste treatment: Do not spread industrial sludge on natural soils.

Other operational conditions affecting environmental exposure
Local seawater dilution factor: 100
Local fresh water dilution factor: 11
Flow rate of receiving surface water: 86400
Indoor use

2.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Process categories: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)
Physical form of the product: Liquid
Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure
Duration: 480 min
Frequency: 5 days/week

Measures and technical-organizational conditions
Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification
Personal protective equipment:
Wear suitable gloves, tested according to EN347.
Dermal - minimum efficiency of: 95 %

Other operational conditions affecting worker exposure
Indoor use
Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%
Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.
Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

2.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Process categories: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Product features (article)
Physical form of the product: Liquid
Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure
Duration: 240 min
Frequency: 5 days/week

Measures and technical-organizational conditions
Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification
Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure
Indoor use
Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%
Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

2.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Process categories: Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

Product features (article)

Physical form of the product: Liquid
Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min
Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347.
Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use
Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 97%
Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

2.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Process categories: Transfer of a substance or preparation (filling/emptying) (dedicated filling line, including weighing) (PROC9)

Product features (article)

Physical form of the product: Liquid
Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min
Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347.
Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use
Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%
Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

2.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Process categories: Mixing or Blending in Batch Processes (PROC5)

Product features (article)

Physical form of the product: Liquid
Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min
Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use
Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%
Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
sea water	1,025 kg/day	ECETOC TRA environment v2.0	0.81

3.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	4,258 mg/m³	ECETOC TRA worker v2.0	0.212

3.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m³	ECETOC TRA worker v2.0	0.706
by inhalation, systemic, short-term	14,192 mg/m³	ECETOC TRA worker v2.0	0.706

3.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	2,129 mg/m³	ECETOC TRA worker v2.0	0.106
by inhalation, systemic, short-term	2,129 mg/m³	ECETOC TRA worker v2.0	0.106

3.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	7,096 mg/m³	ECETOC TRA worker v2.0	0.353
by inhalation, systemic, short-term	7,096 mg/m³	ECETOC TRA worker v2.0	0.353

3.6.CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	7,096 mg/m³	ECETOC TRA worker v2.0	0.353
by inhalation, systemic, short-term	7,096 mg/m³	ECETOC TRA worker v2.0	0.353

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ES2 Formulation or repackaging - PROFESSIONAL USES

1. TITLE SECTION

Exposure scenario name: Preparation and repackaging of substances and mixtures
Date - Version: 10/03/2020 - 1.0
Life cycle stage: Formulation or repackaging
Main user group: Professional uses
Sector(s) of use: Manufacture of bulk, large scale chemicals (including petroleum products) (SU8) - Formulation [mixing] of preparations and/or re-packaging (SU10) - Professional uses (SU22)

Contributing scenario - Environment

CS1 Wet formulation: ERC2

Contributing scenario - Worker

CS2 Use in closed systems: PROC3
CS3 Material Transfers: PROC8a
CS3 Material Transfers: PROC8b
CS3 Material Transfers: PROC9
CS6 Blend Operations: PROC5

2. CONDITIONS OF USE AFFECTING EXPOSURE

2.2. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Environmental release categories: Formulation of mixtures (ERC2)

Product features (article)

Physical form of the product: Liquid
Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use

Amounts used: Annual amount per site 2500 t
Release Type: Continuous release
Issue days: 300 days/year
Further environmental conditions:
Wet formulation
Air - minimum efficiency of: 0.25 %
Ground - minimum efficiency of: 0.01 %
Water - minimum efficiency of: 0.5 %

Measures and technical-organizational conditions

Control measures to prevent releases:
Air - minimum efficiency of: 0.25 %
Ground - minimum efficiency of: 0.01 %
Water - minimum efficiency of: 0.5 %

Conditions and measures for the municipal sewage treatment plant

Type of sewage treatment plant (STP): Municipal STP
STP effluent (m^3/day): 8640

Conditions and measures for waste treatment (including the product waste)

Waste treatment: Do not spread industrial sludge on natural soils.

Other operational conditions affecting environmental exposure

Local seawater dilution factor: 100
Local fresh water dilution factor: 11
Flow rate of receiving surface water: 86400
Indoor use

2.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Process categories: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Physical form of the product: Liquid
Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min
Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 95 %

Other operational conditions affecting worker exposure

Indoor use
Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%
Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

2.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Process categories: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Product features (article)

Physical form of the product: Liquid
Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 240 min
Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use
Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%
Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

2.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Process categories: Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

Product features (article)

Physical form of the product: Liquid
Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 240 min
Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use
Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%
Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

2.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Process categories: Transfer of a substance or preparation (filling/emptying) (dedicated filling line, including weighing) (PROC9)

Product features (article)

Physical form of the product: Liquid
Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 240 min
Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use
Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%
Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

2.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Process categories: Mixing or Blending in Batch Processes (PROC5)

Product features (article)

Physical form of the product: Liquid
Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 60 min
Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use
Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%
Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
sea water	1,025 kg/day	ECETOC TRA environment v2.0	0.81

3.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	8,515 mg/m³	ECETOC TRA worker v2.0	0.424

3.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	7,096 mg/m³	ECETOC TRA worker v2.0	0.353
by inhalation, systemic, short-term	7,096 mg/m³	ECETOC TRA worker v2.0	0.353

3.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m³	ECETOC TRA worker v2.0	0.706
by inhalation, systemic, short-term	14,192 mg/m³	ECETOC TRA worker v2.0	0.706

3.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m³	ECETOC TRA worker v2.0	0.706
by inhalation, systemic, short-term	14,192 mg/m³	ECETOC TRA worker v2.0	0.706

3.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m³	ECETOC TRA worker v2.0	0.706

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Benzyl alcohol

Substance identification
Chemical Name: Benzyl alcohol
CAS number: 100-51-6
Date: 07/12/2012

INDUSTRIAL USE

Exposure scenario for industrial use in adhesives, sealants, coatings and paints, fillers, finger paints, metallic and non-metallic surface treatment products, inks and toners (PC1, PC9a, PC9b, PC9c, PC14, PC15 , PC18)

1. TITLE

Systematic title based on the use descriptor: SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

Processes, activities covered:

Mixing or dilution in batch processes
Processing by compression/pelletisation, calendering or use during foam production
Transfer operations from/to large or small containers
Treatment of objects by brush/roller application, spraying or immersion/pouring
Lubrication at high energy conditions
Use as a laboratory agent
Handling of substances bound in materials/articles

Evaluation method:

ECETOC TRA (April 2010), EUSES (v.2.1)

2. OPERATING CONDITIONS AND RISK MANAGEMENT MEASURES

Process categories for human health and environmental release categories for exposure assessment:
PC1: PROC5, 7, 8a, 8b, 9, 10, 12, 13, 14 spERC ESVOC 5 (related to ERC4)
PC9a/b/c: PROC5, 7, 8a, 8b, 9, 10, 13 spERC ESVOC 5 (related to ERC4)
PC14: PROC5, 8a, 8b, 9, 15, 23, 24, 25 spERC ESVOC 5 (related to ERC4)
PC15: PROC5, 8a, 8b, 9, 15 spERC ESVOC 5 (related to ERC4)
PC18: PROC7, 8a, 8b, 9, 10, 13 spERC ESVOC 5 (related to ERC4)

2.1 EXPOSURE SCENARIO CONTROLLING WORKER EXPOSURE FOR PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC12, PROC13, PROC14, PROC15

Product features

Concentration ≤ 40%
Physical state: liquid

Quantity used

Not applicable

Frequency and duration of use/exposure

Duration of exposure per day: 8h (full shift, indoors)
Duration of exposure per year: 230 days

Human factors not influenced by risk management

Breathing volume in the conditions of use: 10 m³/8h-day (light activity)
Body weight: 70kg (worker)

Other operational conditions affecting worker exposure

Internal use
Use at room temperature

Technical conditions and measures to control dispersion from source to the worker
Local vapor ventilation (efficiency > 90 %) or other adequate ventilation required

Organizational measures to prevent/limit releases, dispersion and exposure
Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures related to personal protection, hygiene and health evaluation
PROC7:
Respiratory protection recommended (95% efficiency) as described in section 8.
Wear safety goggles as described in section 8.
Wear protective clothing as described in section 8.

2.2 EXPOSURE SCENARIO CONTROLLING WORKER EXPOSURE FOR PROC23, PROC24, PROC25

Product features
Concentration ≤ 40%
Physical state: liquid

Quantity used
Not applicable

Frequency and duration of use/exposure
Duration of exposure per day: 8h (full shift, indoors and outdoors)
Duration of exposure per year: 230 days

Human factors not influenced by risk management
Breathing volume in the conditions of use: 10 m³/8h-day (light activity)
Body weight: 70kg (worker)

Other operational conditions affecting worker exposure
Indoor use.
Use at room temperature

Technical conditions and measures to control dispersion from source to the worker
Local vapor ventilation (efficiency > 90 %) or other adequate ventilation required.

Organizational measures to prevent/limit releases, dispersion and exposure
Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures related to personal protection, hygiene and health evaluation
Wear safety goggles as described in section 8.
Wear protective clothing as described in section 8.

2.3 EXPOSURE SCENARIO CONTROLLING ENVIRONMENTAL EXPOSURE FOR SPERC ESVOC 5 - RELATED TO ERC4

Product features
Not relevant

Quantity used
Number of sites: > 1
Yearly amount used in the region: PC 1, 9a, 9b, 9c, 14, 15, 18: 412 to: 570 to (10 % rule applies)

Frequency and duration of use
spERC ESVOC 5 (related to ERC4): 300 days/year

Environmental factors not influenced by risk management
Local fresh water dilution factor: 10
Receiving surface water flow: 18,000 m³/d
Local seawater dilution factor 100

Other operational conditions affecting environmental exposure
Indoor and outdoor use

Technical conditions and measures at process level (source) to prevent release
spERC ESVOC 5 (related to ERC4):
Fraction of tonnage released to air: 9,8 %
Fraction of tonnage released to wastewater: 2 %
Fraction of tonnage released into industrial ground: 0 %

Local technical conditions and measures to reduce and limit discharges, atmospheric emissions and soil release
Waste water must be sent to a dedicated treatment plant or treated with other suitable techniques. Floors should be waterproof and resistant to liquids.

Organizational measures to prevent/limit release from site
Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures for the domestic sewage treatment plant
Dimensions of wastewater treatment plant: 2000 m^3/d (removal rate: 87.4 %)

Conditions and measures for external treatment of waste for disposal
No specific measures. For general conditions and measures, see section 13.

Conditions and measures for external recovery of waste
No specific measures. For general conditions and measures, see section 13.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

Workers

Exposure assessment (human):
ECETOC TRA model (April 2010 version). Dermal exposure estimates of ECETOC TRA have been corrected for concentration.

Exposure estimation:
Individual and combined (skin and inhalation) exposure values are below the DNELs (RCR ratios < 1).

Environment

Exposure assessment (environment):
EUSES 2.1: ERC4 modified with ESVOC 5 (ESVOC SPERC 4.3a.v1)

Exposure estimation:
The predicted exposure concentrations for air, water and soil are lower than the derived PNECs, giving an RCR < 1.

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Environment:
Under the conditions listed above the process is considered safe. Direct release to water and soil should be avoided, air emissions should be minimised. Other conditions should be considered only when adequate measurements or calculations demonstrate that the RCR remains < 1.

Health:
Under the conditions listed above the process is considered safe. Other conditions should be considered only when adequate measurements or calculations demonstrate that the RCR remains < 1.

Further good practice advice beyond the REACH CSA
Environment: Not applicable
Health: On possible contact with the product (sampling, use, spills, product leaks, cleaning): wear protective clothing. Wear protective gloves and safety goggles. See section 8 for information on appropriate personal protective equipment.

PROFESSIONAL USE

Exposure scenario for professional uses of benzyl alcohol consisting of mixing/ loading and charging/discharging, roller, brush, spray or dip application (PC0, PC1, PC09a, 9b, 9c, PC14, PC15, PC18, PC21, PC26, PC31, PC32).

1. TITLE

Systematic title based on the use descriptor: SU22 - Professional uses: Generalized use

Processes, activities covered:

Mixing or dilution in batch processes BY HAND
Transfer operations from/to large or small containers
Treatment of objects by brush/roller application, spraying or immersion/pouring
Hand mixing with intimate contact and only PSD available
Handling of substances bound in materials/articles

Evaluation method:

ECETOC TRA (April 2010), EUSES (v.2.1)

2. OPERATING CONDITIONS AND RISK MANAGEMENT MEASURES

Process categories for human health and environmental release categories for exposure assessment:
PC0: PROC5, 8a, 8b, 9, 10, 11, 13, 19 - ERC8a, 8d
PC1: PROC5, 8a, 8b, 9, 10, 11, 13, 19 - ERC8a, 8d
PC9a, 9b, 9c: PROC5, 8a, 8b, 9, 10, 11, 13, 19 - ERC8a, 8d
PC14: PROC8a, 8b, 9, 10, 11, 13, 19, 23, 24, 25 - ERC8a, 8d
PC15: PROC8a, 8b, 9, 10, 11, 13, 19 - ERC8a, 8d
PC18: PROC5, 8a, 8b, 10, 11, 13, 19 - ERC8a, 8d
PC21: PROC8a, 8b, 15 - ERC8a, 8d
PC26: PROC5, 6, 8a, 8b, 11, 13, 14, 19, 21 - ERC8a, 8d
PC30: PROC8a, 8b - ERC8a, 8d
PC31: PROC8b, 10, 11 - ERC8a, 8d
PC32: PROC8a, 8b, 9, 10, 11 - ERC8a, 8d

Number of sites: > 1

2.1 EXPOSURE SCENARIO CONTROLLING WORKER EXPOSURE FOR PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC12, PROC13, PROC14, PROC15

Product features

Concentration ≤ 40%
Physical state: liquid

Quantity used

Not applicable

Frequency and duration of use/exposure

Duration of exposure per day: 8h (full shift, indoors and outdoors)
Duration of exposure per year: 230 days

Human factors not influenced by risk management

Breathing volume in the conditions of use: 10 m^3/8h-day (light activity)
Body weight: 70kg (worker)

Other operational conditions affecting worker exposure

Internal use
Use at room temperature

Technical conditions and measures to control dispersion from source to the worker

No special measures are required.

Organizational measures to prevent/limit releases, dispersion and exposure
Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures related to personal protection, hygiene and health evaluation
Personal protection:
PROC8b, PROC9, PROC14, PROC15: concentration ≤ 40 %: no RMM required.
PROC5, PROC8a, PROC13: > 25 % - ≤ 40 %: gloves (90 % efficiency) are required as described in section 8.
PROC6: > 5 % - ≤ 40 %: gloves (90 % efficiency) are required as described in section 8.
PROC10: < 5 % (indoor and outdoor environment): No RMMs required.
> 5 - ≤ 40 % (indoor and outdoor environment): gloves (90 % efficiency) are required as described in point 8.

Wear safety goggles as described in section 8.
Wear protective clothing as described in section 8.

2.2 EXPOSURE SCENARIO CONTROLLING WORKER EXPOSURE FOR PROC11

Product features
Concentration ≤ 40%
Physical state: liquid

Quantity used
Not applicable

Frequency and duration of use/exposure
Duration of exposure per day: 8h (full shift, indoors and outdoors)
Duration of exposure per year: 230 days

Human factors not influenced by risk management
Breathing volume in the conditions of use: 10 m³/8h-day (light activity)
Body weight: 70kg (worker)

Other operational conditions affecting worker exposure
Indoor and outdoor use
Use at room temperature

Technical conditions and measures to control dispersion from source to the worker
No special measures are required.

Organizational measures to prevent/limit releases, dispersion and exposure
Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures related to personal protection, hygiene and health evaluation
Personal protection:
≤ 5 % (indoor and outdoor environment): Respiratory protection (95 % efficiency) required as described in section 8.
> 5 % ≤ 40 % (indoor and outdoor environment): Respiratory protection (95 % efficiency) and gloves (90 % efficiency) required as described in section 8.
Wear safety goggles as described in section 8.
Wear protective clothing as described in section 8.

2.3 EXPOSURE SCENARIO CONTROLLING WORKER EXPOSURE FOR PROC19

Product features
Concentration ≤ 40%
Physical state: liquid

Quantity used
Not applicable

Frequency and duration of use/exposure
Duration of exposure per day (concentration ≤ 25 %): 8 hours (indoors and outdoors)
Duration of exposure per day (concentration >25% ≤40%): 4 hours (indoors and outdoors)
Duration of exposure per year: 230 days

Human factors not influenced by risk management
Breathing volume in the conditions of use: 10 m³/8h-day (light activity)
Body weight: 70kg (worker)

Other operational conditions affecting worker exposure
Indoor and outdoor use
Use at room temperature

Technical conditions and measures to control dispersion from source to the worker
No special measures are required.

Organizational measures to prevent/limit releases, dispersion and exposure
Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures related to personal protection, hygiene and health evaluation
Personal protection:
> 1 % (indoor): gloves (90 % efficiency) are required as described in section 8.
> 5% - 40% (outdoors): gloves (90 % efficiency) are required as described in section 8.
Wear safety goggles as described in section 8.
Wear protective clothing as described in section 8.

2.4 EXPOSURE SCENARIO CONTROLLING ENVIRONMENTAL EXPOSURE FOR ERC8a, ERC8d

Product features
Not relevant

Quantity used
Yearly amount used in the region: the 10% rule applies
ERC8a PC0, 1, 9a, 9b, 9c, 14, 15, 18, 21, 26, 30, 31, 32, 34, 35: 1,785t
ERC8d PC0, 1, 9a, 9b, 9c, 14, 15, 18, 21, 26, 31, 32, 34, 35: 1,775t
Fraction of main local source: 0.002 (default)
Issue days per site: 365 days/year (default)

Frequency and duration of use
Continuous release: 365 days/year

Environmental factors not influenced by risk management
Local fresh water dilution factor: 10
Receiving surface water flow: 18,000 m³/d
Local seawater dilution factor local: 100

Other operational conditions affecting environmental exposure
Indoor / outdoor environment

Technical conditions and measures at process level (source) to prevent release
No special measures are required.

Local technical conditions and measures to reduce and limit discharges, atmospheric emissions and soil release
Waste water must be sent to a dedicated treatment plant or treated with other suitable techniques.

Organizational measures to prevent release from site
Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures for the domestic sewage treatment plant
Dimensions of wastewater treatment plant: 2000 m³/d (removal rate: 87.4 %)

Conditions and measures for external treatment of waste for disposal
No specific measures. For general conditions and measures, see section 13.

Conditions and measures for external recovery of waste
No specific measures. For general conditions and measures, see section 13.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

Workers

PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC15, PROC19

Exposure assessment (human):

PROC5, PROC6, PROC8b, PROC9, PROC11, PROC13, PROC14, PROC15

ECETOC TRA model (April 2010 version). Dermal exposure estimates of ECETOC TRA have been linearly corrected for concentration.

PROC8a, PROC10

ECETOC TRA model (April 2010 version). Dermal exposure estimates of ECETOC TRA have been linearly corrected for concentration. Local and systemic exposure via inhalation of ECETOC TRA has been linearly scaled based on the concentration.

PROC19

ECETOC TRA model (April 2010 version). The dermal exposure estimates of ECETOC TRA have been linearly corrected for the concentration and according to the EMFs of CEFIC for the duration of exposure. Local exposure via inhalation of ECETOC TRA has been linearly scaled based on the concentration and in accordance with the CEFIC EMFs for the duration of exposure. Systemic exposure via inhalation has been linearly scaled for the duration of exposure.

Exposure estimation:

Individual and combined (skin and inhalation) exposure values are below the DNELs (RCR ratios < 1).

Environment

ERC8a, ERC8d

Exposure assessment (environment):

EUSES 2.1.

Exposure estimation:

The predicted exposure concentrations for air, water and soil are lower than the derived PNECs, giving an RCR < 1.

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Environment:

Under the conditions listed above the process is considered safe. Direct release to water and soil should be avoided, air emissions should be minimised. Other conditions should be considered only when adequate measurements or calculations demonstrate that the RCR remains < 1.

Health:

Under the conditions listed above the process is considered safe. Other conditions should be considered only when adequate measurements or calculations demonstrate that the RCR remains < 1.

Further good practice advice beyond the REACH CSA

Environment: Not applicable

Health: On possible contact with the product (sampling, use, spills, product leaks, cleaning): wear protective clothing. Wear protective gloves and safety goggles. See section 8 for information on appropriate personal protective equipment.

PROFESSIONAL USE

Exposure scenario for professional use in photochemicals (PC30)

1. TITLE

Systematic title based on the use descriptor: SU22 - Professional uses: Generalized use

Processes, activities covered:

Transfer operations from/to large or small containers

Evaluation method:

ECETOC TRA (April 2010), EUSES (v.2.1)

2. OPERATING CONDITIONS AND RISK MANAGEMENT MEASURES

Human Health Exposure/Environmental Exposure:
PC30: PROC8a, 8b - ERC8a, 8d

Number of sites: > 1

2.1 EXPOSURE SCENARIO CONTROLLING WORKER EXPOSURE FOR PROC8a E PROC8b

Product features

Concentration ≤ 40%
Physical state: liquid

Quantity used

Not applicable

Frequency and duration of use/exposure

Duration of exposure per day: 8h (full shift, indoors and outdoors)
Duration of exposure per year: 230 days

Human factors not influenced by risk management

Breathing volume in the conditions of use: 10 m^3/8h-day (light activity)
Body weight: 70kg (worker)

Other operational conditions affecting worker exposure

Internal use
Use at room temperature

Technical conditions and measures to control dispersion from source to the worker

No special measures are required.

Organizational measures to prevent/limit releases, dispersion and exposure

Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection:
PROC8b: concentration ≤ 40 %: no RMM required.
PROC8a: > 25 % - ≤ 40 %: gloves (90 % efficiency) are required as described in section 8.

Wear safety goggles as described in section 8.
Wear protective clothing as described in section 8.

2.2 EXPOSURE SCENARIO CONTROLLING ENVIRONMENTAL EXPOSURE FOR ERC8a, ERC8b

Product features
Not relevant

Quantity used
Yearly amount used in the region: the 10% rule applies
ERC8a PC30: 1.785 t
ERC8d PC30: 190 t
Fraction of main local source: 0.002 (default)
Issue days per site: 365 days/year (default)

Frequency and duration of use
Continuous release: 365 days/year

Environmental factors not influenced by risk management
Local fresh water dilution factor: 10
Receiving surface water flow: 18,000 m³/d
Local seawater dilution factor local: 100

Other operational conditions affecting environmental exposure
No special measures are required.

Technical conditions and measures at process level (source) to prevent release
No special measures are required.

Local technical conditions and measures to reduce and limit discharges, atmospheric emissions and soil release
Waste water must be sent to a dedicated treatment plant or treated with other suitable techniques.

Organizational measures to prevent release from site
Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures for the domestic sewage treatment plant
Dimensions of wastewater treatment plant: 2000 m³/d (removal rate: 87.4 %)

Conditions and measures for external treatment of waste for disposal
No specific measures. For general conditions and measures, see section 13.

Conditions and measures for external recovery of waste
No specific measures. For general conditions and measures, see section 13.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

Workers
PROC8a, PROC8b

Exposure assessment (human):
PROC8a
ECETOC TRA model (April 2010 version). Dermal exposure estimates of ECETOC TRA have been linearly corrected for concentration. Local and systemic exposure via inhalation of ECETOC TRA has been linearly scaled based on the concentration.

PROC8b
ECETOC TRA model (April 2010 version). Dermal exposure estimates of ECETOC TRA have been linearly corrected for concentration.

Exposure estimation:
Individual and combined (skin and inhalation) exposure values are below the DNELs (RCR ratios < 1).

Environment
ERC8a, ERC8b

Exposure assessment (environment):
EUSES 2.1.

Exposure estimation:
The predicted exposure concentrations for air, water and soil are lower than the derived PNECs, giving an RCR < 1.

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Environment:
Under the conditions listed above the process is considered safe. Direct release to water and soil should be avoided, air emissions should be minimised. Other conditions should be considered only when adequate measurements or calculations demonstrate that the RCR remains < 1.

Health:
Under the conditions listed above the process is considered safe. Other conditions should be considered only when adequate measurements or calculations demonstrate that the RCR remains < 1.

Further good practice advice beyond the REACH CSA
Environment: Not applicable
Health: On possible contact with the product (sampling, use, spills, product leaks, cleaning): wear protective clothing. Wear protective gloves and safety goggles. See section 8 for information on appropriate personal protective equipment.

PROFESSIONAL USE

Exposure scenario for professional use in washing and cleaning products, cosmetics and personal care products (PC35, PC39)

1. TITLE

Systematic title based on the use descriptor: SU22 - Professional uses: Generalized use

Processes, activities covered:

Transfer operations from/to large or small containers
Treatment of objects by roller/brush, spray or dip/pour application
Mixing or dilution in batch processes or by hand

Evaluation method:

ECETOC TRA (April 2010), EUSES (v.2.1)

2. OPERATING CONDITIONS AND RISK MANAGEMENT MEASURES

Human Health Exposure/Environmental Exposure:
PC35: PROC8a, 8b, 9, 10, 11, 13, 19 - ERC8a, 8b, 8d, 8e
PC39: PROC13 - ERC8a, 8b, 8d, 8e

Number of sites: > 1

2.1 EXPOSURE SCENARIO CONTROLLING WORKER EXPOSURE FOR PROC8a, PROC8b, PROC9, PROC10, PROC13

Product features

Concentration ≤ 40%
Physical state: liquid

Quantity used

Not applicable

Frequency and duration of use/exposure

Duration of exposure per day: 8h (full shift, indoors and outdoors)
Duration of exposure per year: 230 days

Human factors not influenced by risk management

Breathing volume in the conditions of use: 10 m³/8h-day (light activity)
Body weight: 70kg (worker)

Other operational conditions affecting worker exposure

Internal use
Use at room temperature

Technical conditions and measures to control dispersion from source to the worker

No special measures are required.

Organizational measures to prevent/limit releases, dispersion and exposure

Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection:
PROC8b, PROC9: concentration ≤ 40 %: no RMM required.
PROC8a, PROC13: > 25 % - ≤ 40 %: gloves (90 % efficiency) are required as described in section 8.
PROC10: < 5 % (indoor and outdoor environment): No RMMs required
> 5 - ≤ 40 % (indoor and outdoor environment): gloves (90 % efficiency) are required as described in section 8.

Wear safety goggles as described in section 8.
Wear protective clothing as described in section 8.

2.2 EXPOSURE SCENARIO CONTROLLING WORKER EXPOSURE FOR PROC11

Product features
Concentration ≤ 40%
Physical state: liquid

Quantity used
Not applicable

Frequency and duration of use/exposure
Duration of exposure per day: 8h (full shift, indoors and outdoors)
Duration of exposure per year: 230 days

Human factors not influenced by risk management
Breathing volume in the conditions of use: 10 m³/8h-day (light activity)
Body weight: 70kg (worker)

Other operational conditions affecting worker exposure
Internal use
Use at room temperature

Technical conditions and measures to control dispersion from source to the worker
No special measures are required.

Organizational measures to prevent/limit releases, dispersion and exposure
Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures related to personal protection, hygiene and health evaluation
Personal protection:
≤ 5 % (indoor and outdoor environment): Respiratory protection (95 % efficiency) required as described in section 8.
> 5 % - ≤ 40 % (indoor and outdoor environment): Respiratory protection (95 % efficiency) and gloves (90 % efficiency) required as described in section 8.

Wear safety goggles as described in section 8.
Wear protective clothing as described in section 8.

2.3 EXPOSURE SCENARIO CONTROLLING WORKER EXPOSURE FOR PROC19

Product features
Concentration ≤ 40%
Physical state: liquid

Quantity used
Not applicable

Frequency and duration of use/exposure
Duration of exposure per day (concentration ≤ 25 %): 8 h (indoor and outdoor)
Duration of exposure per day (concentration >25% - ≤40%): 4 hours (indoors and outdoors)
Duration of exposure per year: 230 days

Human factors not influenced by risk management
Breathing volume in the conditions of use: 10 m³/8h-day (light activity)
Body weight: 70kg (worker)

Other operational conditions affecting worker exposure
Internal use
Use at room temperature

Technical conditions and measures to control dispersion from source to the worker
No special measures are required.

Organizational measures to prevent/limit releases, dispersion and exposure
Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection:
> 1 % (indoor): gloves (90 % efficiency) are required as described in section 8.
> 5% - 40% (outdoors): gloves (90 % efficiency) are required as described in section 8..

Wear safety goggles as described in section 8.
Wear protective clothing as described in section 8.

2.4 EXPOSURE SCENARIO CONTROLLING ENVIRONMENTAL EXPOSURE FOR ERC8a, ERC8b, ERC8d, ERC8e

Product features

Not relevant

Quantity used

Yearly amount used in the region: the 10% rule applies
ERC8a PC35/PC39: 1,785 t
ERC8b PC35/PC39: 190 t
ERC8d PC35/PC39: 1,775 t
ERC8e PC35/PC39: 190 t
Fraction of main local source: 0.002 (default)
Issue days per site: 365 days/year (default)

Frequency and duration of use

Continuous release: 365 days/year

Environmental factors not influenced by risk management

Local fresh water dilution factor: 10
Receiving surface water flow: 18,000 m³/d
Local seawater dilution factor local: 100

Other operational conditions affecting environmental exposure

No special measures are required.

Technical conditions and measures at process level (source) to prevent release

No special measures are required.

Local technical conditions and measures to reduce and limit discharges, atmospheric emissions and soil release

Waste water must be sent to a dedicated treatment plant or treated with other suitable techniques.

Organizational measures to prevent release from site

Only properly trained and authorized personnel can handle the substance. Substance handling procedures must be well documented and controlled.

Conditions and measures for the domestic sewage treatment plant

Dimensions of wastewater treatment plant: 2000 m³/d (removal rate: 87.4 %)

Conditions and measures for external treatment of waste for disposal

No specific measures. For general conditions and measures, see section 13.

Conditions and measures for external recovery of waste

No specific measures. For general conditions and measures, see section 13.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

Workers

Exposure assessment (human):

PROC8b, PROC9, PROC11, PROC13

ECETOC TRA model (April 2010 version). Dermal exposure estimates of ECETOC TRA have been corrected for concentration.

PROC8a, PROC10

ECETOC TRA model (April 2010 version). Dermal exposure estimates of ECETOC TRA have been linearly corrected for concentration. Local and systemic exposure via inhalation of ECETOC TRA has been linearly scaled based on the concentration.

PROC19

ECETOC TRA model (April 2010 version). The dermal exposure estimates of ECETOC TRA have been linearly corrected for the concentration and according to the EMFs of CEFIC for the duration of exposure. Local exposure via inhalation of ECETOC TRA has been linearly scaled based on the concentration and in accordance with the CEFIC EMFs for the duration of exposure. Systemic exposure via inhalation has been linearly scaled for the duration of exposure.

Exposure estimation:

Individual and combined (skin and inhalation) exposure values are below the DNELs (RCR ratios < 1).

Environment

ERC8a, ERC8b, ERC8d, ERC8e

Exposure assessment (environment):

EUSES 2.1.

Exposure estimation:

The predicted exposure concentrations for air, water and soil are lower than the derived PNECs, giving an RCR < 1.

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Environment:

Under the conditions listed above the process is considered safe. Direct release to water and soil should be avoided, air emissions should be minimised. Other conditions should be considered only when adequate measurements or calculations demonstrate that the RCR remains < 1.

Health:

Under the conditions listed above the process is considered safe. Other conditions should be considered only when adequate measurements or calculations demonstrate that the RCR remains < 1.

Further good practice advice beyond the REACH CSA

Environment: Not applicable

Health: On possible contact with the product (sampling, use, spills, product leaks, cleaning): wear protective clothing. Wear protective gloves and safety goggles. See section 8 for information on appropriate personal protective equipment.

m-phenylenebis(methylamine)

Substance identification
Chemical Name: m-phenylenebis(methylamine)
CAS number: CAS-1477-55-0
Date - Version: 10/03/2020 - 1.0

PROFESSIONAL USES - GENERALIZED USE BY PROFESSIONAL OPERATORS: VARIOUS PRODUCTS (PC9a, PC9b, PC1); CONSTRUCTION (SU19)

1. TITLE SECTION

Exposure scenario name: Professional use of coatings and paints - Use in composite and foundry materials
Life cycle stage: Professional uses
Sectors of use: Construction (SU19) - Professional uses (SU22)
Product categories: Coatings and paints, thinners, pickling solutions (PC9a) - Additives, fillers, plasters, modeling clay (PC9b) - Adhesives, Sealants (PC1)

CONTRIBUTION SCENARIO - ENVIRONMENT

CS1: Wet cure - Wet formulation ERC8c - ERC8f

CONTRIBUTION SCENARIO - WORKER

CS2: Application with rollers or brushes PROC10
CS3: Non-industrial spray application PROC11
CS4: Treatment of articles by dipping and pouring PROC13
CS5: Manual activities with direct contact PROC19
CS6: Low energy handling of substances included in or on materials and/or articles PROC21

2. CONDITIONS OF USE AFFECTING EXPOSURE

2.1. CS1: CONTRIBUTION SCENARIO - ENVIRONMENT: Wet cure - Wet formulation (ERC8c, ERC8f)

Environmental release categories

Widespread use resulting in inclusion in or on the surface of an article (indoor use) - Wide use leading to inclusion in/on article (outdoor use) (ERC8c, ERC8f)

Product features (article)

Physical form of the product: Liquid

Amount used, frequency and duration of use/(or duration of use)

Amounts used:
PROC10 ≤ 0,4 l/min
PROC11 ≤ 0,3 l/min
PROC13 ≤ 2 l/min
PROC19 ≤ 1 l/min
PROC21 ≤ 0,3 l/min

Measures and technical-organizational conditions

Control measures to prevent releases: No entry of substance into waste water.

Conditions and measures for waste treatment (including the product waste)

Waste treatment: This material and its container must be disposed of as hazardous.
Dispose of waste product or used containers according to local regulations.
Incineration of hazardous waste.

2.2. CS2: CONTRIBUTION SCENARIO - WORKER: Application with rollers or brushes (PROC10)

Product features (article)
Physical form of the product: Liquid.
Concentration of the substance in the product: Includes substance shares in the product up to 5%.

Amount used, frequency and duration of use/(or duration of use)
Amounts used: Quantity per use 0.4 l/min
Duration: ≤ 5 h/day
Frequency: 365 days/year

Technical organizational measures
Ensure that direct skin contact is avoided.
Avoid direct contact with the product, even with contaminated hands.
Ensure operating personnel are trained to minimize exposure.
See main part of the safety data sheet, Sections 7 and/or 8, for measures mitigating the risks deriving from the physical-chemical properties.
Ensure a sufficient amount of general ventilation (1 to 3 air changes per hour).

Conditions and measures related to personal protection, hygiene and health verification
Personal protective equipment:
Wear suitable face protection.
Use adequate eye protection.
Wear a suitable apron to avoid skin exposure.
Wear suitable gloves, tested according to EN347.
Use a respiratory protective device according to EN140.
Dermal: minimum efficiency of 80%.
Inhalation: minimum efficiency of 95%.

2.3. CS3: CONTRIBUTION SCENARIO - WORKER: Non-industrial spray application (PROC11)

Product features (article)
Physical form of the product: Liquid.
Concentration of the substance in the product: Includes substance shares in the product up to 5%.

Amount used, frequency and duration of use/(or duration of use)
Amounts used: Quantity per use 0.3 l/min
Duration: ≤ 6 h/day
Frequency: 365 days/year

Technical organizational measures
Ensure that direct skin contact is avoided.
Avoid direct contact with the product, even with contaminated hands.
Ensure operating personnel are trained to minimize exposure.
See main part of the safety data sheet, Sections 7 and/or 8, for measures mitigating the risks deriving from the physical-chemical properties.
Ensure a sufficient amount of general ventilation (1 to 3 air changes per hour).

Conditions and measures related to personal protection, hygiene and health verification
Personal protective equipment:
Wear suitable face protection.
Use adequate eye protection.
Wear a suitable apron to avoid skin exposure.
Wear suitable gloves, tested according to EN347.
Use a respiratory protective device according to EN140.
Dermal: minimum efficiency of 80%.
Inhalation: minimum efficiency of 95%.

2.4. CS4: CONTRIBUTION SCENARIO - WORKER: Treatment of articles by dipping and pouring (PROC13)

Product features (article)
Physical form of the product: Liquid.
Concentration of the substance in the product: Includes substance shares in the product up to 5%.

Amount used, frequency and duration of use/(or duration of use)
Amounts used: Quantity per use 2 l/min
Duration: ≤ 1 h/day
Frequency: 365 days/year

Technical organizational measures
Ensure that direct skin contact is avoided.
Avoid direct contact with the product, even with contaminated hands.
Ensure operating personnel are trained to minimize exposure.
See main part of the safety data sheet, Sections 7 and/or 8, for measures mitigating the risks deriving from the physical-chemical properties.
Ensure a sufficient amount of general ventilation (1 to 3 air changes per hour).

Conditions and measures related to personal protection, hygiene and health verification
Personal protective equipment:
Wear suitable face protection.
Use adequate eye protection.
Wear a suitable apron to avoid skin exposure.
Wear suitable gloves, tested according to EN347.
Use a respiratory protective device according to EN140.
Dermal: minimum efficiency of 80%.
Inhalation: minimum efficiency of 95%.

2.5. CS5: CONTRIBUTION SCENARIO - WORKER: Manual activities with direct contact (PROC19)

Product features (article)
Physical form of the product: Liquid.
Concentration of the substance in the product: Includes substance shares in the product up to 40%.

Amount used, frequency and duration of use/(or duration of use)
Amounts used: Quantity per use 1 l/min
Duration: ≤ 2 h/day
Frequency: 365 days/year

Technical organizational measures
Ensure that direct skin contact is avoided.
Avoid direct contact with the product, even with contaminated hands.
Ensure operating personnel are trained to minimize exposure.
See main part of the safety data sheet, Sections 7 and/or 8, for measures mitigating the risks deriving from the physical-chemical properties.
Ensure a sufficient amount of general ventilation (1 to 3 air changes per hour).

Conditions and measures related to personal protection, hygiene and health verification
Personal protective equipment:
Wear suitable face protection.
Use adequate eye protection.
Wear a suitable apron to avoid skin exposure.
Wear suitable gloves, tested according to EN347.
Use a respiratory protective device according to EN140.
Dermal: minimum efficiency of 80%.
Inhalation: minimum efficiency of 95%.

2.6. CS6: CONTRIBUTION SCENARIO - WORKER: Low energy handling of substances included in or on materials and/or articles (PROC21)

Product features (article)

Physical form of the product: Liquid.
Concentration of the substance in the product: Includes substance shares in the product up to 5%.

Amount used, frequency and duration of use/(or duration of use)

Amounts used: Quantity per use 0.3 l/min
Duration: ≤ 6 h/day
Frequency: 365 days/year

Technical organizational measures

Ensure that direct skin contact is avoided.
Avoid direct contact with the product, even with contaminated hands.
Ensure operating personnel are trained to minimize exposure.
See main part of the safety data sheet, Sections 7 and/or 8, for measures mitigating the risks deriving from the physical-chemical properties.
Ensure a sufficient amount of general ventilation (1 to 3 air changes per hour).

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment:
Wear suitable face protection.
Use adequate eye protection.
Wear a suitable apron to avoid skin exposure.
Wear suitable gloves, tested according to EN347.
Use a respiratory protective device according to EN140.
Dermal: minimum efficiency of 80%.
Inhalation: minimum efficiency of 95%.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. CS1: CONTRIBUTION SCENARIO - ENVIRONMENT: Wet cure - Wet formulation (ERC8c, ERC8f)

Protection goal	Degree of exposure	Calculation method	Risk Characterization Ratio (RCR)
fresh water	N.d.	ECETOC TRA environment v2.0	0.169
fresh water sediment	N.d.	ECETOC TRA environment v2.0	0.411
sea water	N.d.	ECETOC TRA environment v2.0	0.089
Marine sediment	N.d.	ECETOC TRA environment v2.0	0.412
Agricultural land	N.d.	ECETOC TRA environment v2.0	0.004

3.2. CS2: CONTRIBUTION SCENARIO - ENVIRONMENT: Application with rollers or brushes (PROC10)

Route of exposure, Impact on health, Exposure indicator	Degree of exposure	Calculation method	Risk Characterization Ratio (RCR)
skin contact, systemic, long-term	N.d.	RISKOFDERM v2.1	0.83
by inhalation, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.2

1 - m-phenylenebis(methylamine) - 1

3.3. CS3 CONTRIBUTION SCENARIO - ENVIRONMENT: Non-industrial spray application (PROC11)

Route of exposure, Impact on health, Exposure indicator	Degree of exposure	Calculation method	Risk Characterization Ratio (RCR)
skin contact, systemic, long-term	N.d.	RISKOFDERM v2.1	0.83
by inhalation, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.2

3.4. CS4 CONTRIBUTION SCENARIO - ENVIRONMENT: Treatment of articles by dipping and pouring (PROC13)

Route of exposure, Impact on health, Exposure indicator	Degree of exposure	Calculation method	Risk Characterization Ratio (RCR)
skin contact, systemic, long-term	N.d.	RISKOFDERM v2.1	0.83
by inhalation, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.2

3.5. CS5 CONTRIBUTION SCENARIO - ENVIRONMENT: Manual activities with direct contact (PROC19)

Route of exposure, Impact on health, Exposure indicator	Degree of exposure	Calculation method	Risk Characterization Ratio (RCR)
skin contact, systemic, long-term	N.d.	RISKOFDERM v2.1	0.83
by inhalation, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.2

3.6. CS6 CONTRIBUTION SCENARIO - ENVIRONMENT: Low energy handling of substances included in or on materials and/or articles (PROC21)

Route of exposure, Impact on health, Exposure indicator	Degree of exposure	Calculation method	Risk Characterization Ratio (RCR)
skin contact, systemic, long-term	N.d.	RISKOFDERM v2.1	0.83
by inhalation, systemic, long-term	N.d.	ECETOC TRA worker v2.0	0.2

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in Section 2 are implemented.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.